

## 1. Product and Company Identification

<b>Product identifier</b>	<b>Spray Adhesive (4080-04)</b>
<b>Other means of identification</b>	Not available
<b>Recommended use</b>	Adhesive.
<b>Recommended restrictions</b>	None known.
<b>Manufacturer information</b>	Nu-Calgon 2611 Schuetz Road St. Louis, MO 63043 US Phone: 314-469-7000 / 800-554-5499 Emergency Phone: 1-800-424-9300 (CHEMTREC)
<b>Supplier</b>	See above.

## 2. Hazards Identification

<b>Physical hazards</b>	Flammable aerosols	Category 1
	Gases under pressure	Liquefied gas
<b>Health hazards</b>	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2
	Reproductive toxicity	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Aspiration hazard	Category 1
<b>Environmental hazards</b>	Not classified.	
<b>WHMIS 2015 defined hazards</b>	Not classified	
<b>Label elements</b>		



**Signal word**

Danger

**Hazard statement**

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. Causes skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Suspected of damaging fertility or the unborn child.

**Precautionary statement**

**Prevention**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing gas. Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

**Response**

IF ON SKIN: Wash with plenty of water. Specific treatment (see information on this label). If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

IF exposed or concerned: Get medical advice/attention.

**Storage**

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Store locked up.

**Disposal**

Dispose of contents/container in accordance with local/regional/national/international regulations.

**WHMIS 2015: Health Hazard(s) not otherwise classified (HHNOC)**

None known

<b>WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC)</b>	None known
<b>Hazard(s) not otherwise classified (HNOC)</b>	None known.
<b>Supplemental information</b>	None.

### 3. Composition/Information on Ingredients

#### Mixture

Chemical name	Common name and synonyms	CAS number	%
Methyl acetate		79-20-9	20-40
Acetone		67-64-1	10-20
Propane		74-98-6	10-20
Naphtha (petroleum), hydrotreated light		64742-49-0	7-13
1,1-Difluoroethane		75-37-6	2.5-10
Methane, oxybis-		115-10-6	2.5-10
Heptane		142-82-5	3-7
Cyclohexane, methyl-		108-87-2	0.5-1.5
Cyclohexane		110-82-7	0.1-1
Hexane		110-54-3	0.1-1
Toluene		108-88-3	0.1-1

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

**Composition comments** US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

### 4. First Aid Measures

<b>Inhalation</b>	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
<b>Skin contact</b>	IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. Specific treatment (see information on this label).
<b>Eye contact</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
<b>Ingestion</b>	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.
<b>Most important symptoms/effects, acute and delayed</b>	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Symptoms may be delayed.
<b>General information</b>	If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse. Avoid contact with eyes and skin. Keep out of reach of children.

### 5. Fire Fighting Measures

<b>Suitable extinguishing media</b>	Carbon dioxide. Alcohol resistant foam. Dry chemical powder.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Contents under pressure. Static charges generated by emptying package in or near flammable vapor may cause flash fire. Pressurized container may explode when exposed to heat or flame.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire-fighting equipment/instructions</b>	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes.
<b>General fire hazards</b>	Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.
<b>Hazardous combustion products</b>	May include and are not limited to: Oxides of carbon.

## 6. Accidental Release Measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.  Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
<b>Environmental precautions</b>	Avoid discharge into drains, water courses or onto the ground. Do not discharge into lakes, streams, ponds or public waters.

## 7. Handling and Storage

<b>Precautions for safe handling</b>	Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not smoke while using or until sprayed surface is thoroughly dry. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Use only in well-ventilated areas. Avoid prolonged exposure. Wear appropriate personal protective equipment. Wash thoroughly after handling. Use good industrial hygiene practices in handling this material. When using do not eat or drink.
<b>Conditions for safe storage, including any incompatibilities</b>	Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not handle or store near an open flame, heat or other sources of ignition. Do not puncture, incinerate or crush. Store in a well-ventilated place. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Keep out of reach of children.

## 8. Exposure Controls/Personal Protection

### Occupational exposure limits

#### Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	1800 mg/m3 750 ppm
	TWA	1200 mg/m3 500 ppm
Cyclohexane (CAS 110-82-7)	TWA	344 mg/m3 100 ppm
	TWA	1610 mg/m3 400 ppm
Cyclohexane, methyl- (CAS 108-87-2)	TWA	1610 mg/m3 400 ppm
	TWA	1640 mg/m3 400 ppm
Heptane (CAS 142-82-5)	STEL	2050 mg/m3 500 ppm
	TWA	1640 mg/m3 400 ppm
Hexane (CAS 110-54-3)	TWA	176 mg/m3 50 ppm

**Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)**

Components	Type	Value
Methyl acetate (CAS 79-20-9)	STEL	757 mg/m <sup>3</sup>
		250 ppm
	TWA	606 mg/m <sup>3</sup> 200 ppm
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	TWA	1590 mg/m <sup>3</sup>
		400 ppm
Propane (CAS 74-98-6)	TWA	1000 ppm
Toluene (CAS 108-88-3)	TWA	188 mg/m <sup>3</sup>
		50 ppm

**Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)**

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	500 ppm
	TWA	250 ppm
Cyclohexane (CAS 110-82-7)	TWA	100 ppm
Cyclohexane, methyl- (CAS 108-87-2)	TWA	400 ppm
Heptane (CAS 142-82-5)	STEL	500 ppm
	TWA	400 ppm
Hexane (CAS 110-54-3)	TWA	20 ppm
Methane, oxybis- (CAS 115-10-6)	TWA	1000 ppm
Methyl acetate (CAS 79-20-9)	STEL	250 ppm
	TWA	200 ppm
Propane (CAS 74-98-6)	TWA	1000 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm

**Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)**

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	500 ppm
	TWA	250 ppm
Cyclohexane (CAS 110-82-7)	TWA	100 ppm
Cyclohexane, methyl- (CAS 108-87-2)	TWA	400 ppm
Heptane (CAS 142-82-5)	STEL	500 ppm
	TWA	400 ppm
Hexane (CAS 110-54-3)	TWA	50 ppm
Methyl acetate (CAS 79-20-9)	STEL	250 ppm
	TWA	200 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm

**Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)**

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	750 ppm
	TWA	500 ppm
Cyclohexane (CAS 110-82-7)	TWA	100 ppm

**Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)**

Components	Type	Value
Cyclohexane, methyl- (CAS 108-87-2)	TWA	400 ppm
Heptane (CAS 142-82-5)	STEL	500 ppm
	TWA	400 ppm
Hexane (CAS 110-54-3)	TWA	50 ppm
Methyl acetate (CAS 79-20-9)	STEL	250 ppm
	TWA	200 ppm
Propane (CAS 74-98-6)	TWA	1000 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm

**Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)**

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	2380 mg/m3 1000 ppm
	TWA	1190 mg/m3 500 ppm
Cyclohexane (CAS 110-82-7)	TWA	1030 mg/m3 300 ppm
Cyclohexane, methyl- (CAS 108-87-2)	TWA	1610 mg/m3 400 ppm
Heptane (CAS 142-82-5)	STEL	2050 mg/m3 500 ppm
	TWA	1640 mg/m3 400 ppm
Hexane (CAS 110-54-3)	TWA	176 mg/m3 50 ppm
Methyl acetate (CAS 79-20-9)	STEL	757 mg/m3 250 ppm
	TWA	606 mg/m3 200 ppm
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	TWA	1590 mg/m3 400 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3 1000 ppm
Toluene (CAS 108-88-3)	TWA	188 mg/m3 50 ppm

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
Acetone (CAS 67-64-1)	PEL	2400 mg/m3 1000 ppm
Cyclohexane (CAS 110-82-7)	PEL	1050 mg/m3 300 ppm
Cyclohexane, methyl- (CAS 108-87-2)	PEL	2000 mg/m3 500 ppm
Heptane (CAS 142-82-5)	PEL	2000 mg/m3 500 ppm
Hexane (CAS 110-54-3)	PEL	1800 mg/m3 500 ppm
Methyl acetate (CAS 79-20-9)	PEL	610 mg/m3

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	PEL	200 ppm
		400 mg/m3
Propane (CAS 74-98-6)	PEL	100 ppm
		1800 mg/m3
		1000 ppm

**US. OSHA Table Z-2 (29 CFR 1910.1000)**

Components	Type	Value
Toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

**US. ACGIH Threshold Limit Values**

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	500 ppm
	TWA	250 ppm
Cyclohexane (CAS 110-82-7)	TWA	100 ppm
Cyclohexane, methyl- (CAS 108-87-2)	TWA	400 ppm
Heptane (CAS 142-82-5)	STEL	500 ppm
	TWA	400 ppm
Hexane (CAS 110-54-3)	TWA	50 ppm
Methyl acetate (CAS 79-20-9)	STEL	250 ppm
	TWA	200 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	590 mg/m3
		250 ppm
Cyclohexane (CAS 110-82-7)	TWA	1050 mg/m3
		300 ppm
Cyclohexane, methyl- (CAS 108-87-2)	TWA	1600 mg/m3
		400 ppm
Heptane (CAS 142-82-5)	Ceiling	1800 mg/m3
		440 ppm
		350 mg/m3
Hexane (CAS 110-54-3)	TWA	85 ppm
		180 mg/m3
		50 ppm
Methyl acetate (CAS 79-20-9)	STEL	760 mg/m3
		250 ppm
		610 mg/m3
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	TWA	200 ppm
		400 mg/m3
		100 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3
		1000 ppm
Toluene (CAS 108-88-3)	STEL	560 mg/m3
		150 ppm
		375 mg/m3

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value
		100 ppm

**US. AIHA Workplace Environmental Exposure Level (WEEL) Guides**

Components	Type	Value
1,1-Difluoroethane (CAS 75-37-6)	TWA	2700 mg/m3
		1000 ppm
Methane, oxybis- (CAS 115-10-6)	TWA	1880 mg/m3
		1000 ppm

**Biological limit values**

**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	25 mg/L	Acetone	Urine	*
Hexane (CAS 110-54-3)	0.4 mg/L	2,5-Hexanedion, without hydrolysis	Urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/L	Toluene	Urine	*
	0.02 mg/L	Toluene	Blood	*

\* - For sampling details, please see the source document.

**Exposure guidelines**

**Canada - Alberta OELs: Skin designation**

Benzene (CAS 71-43-2)	Can be absorbed through the skin.
Hexane (CAS 110-54-3)	Can be absorbed through the skin.
Naphthalene (CAS 91-20-3)	Can be absorbed through the skin.
Toluene (CAS 108-88-3)	Can be absorbed through the skin.

**Canada - British Columbia OELs: Skin designation**

Benzene (CAS 71-43-2)	Can be absorbed through the skin.
Hexane (CAS 110-54-3)	Can be absorbed through the skin.
Naphthalene (CAS 91-20-3)	Can be absorbed through the skin.

**Canada - Manitoba OELs: Skin designation**

Benzene (CAS 71-43-2)	Can be absorbed through the skin.
Hexane (CAS 110-54-3)	Can be absorbed through the skin.
Naphthalene (CAS 91-20-3)	Can be absorbed through the skin.

**Canada - Ontario OELs: Skin designation**

Benzene (CAS 71-43-2)	Can be absorbed through the skin.
Hexane (CAS 110-54-3)	Can be absorbed through the skin.
Naphthalene (CAS 91-20-3)	Can be absorbed through the skin.

**Canada - Quebec OELs: Skin designation**

Hexane (CAS 110-54-3)	Can be absorbed through the skin.
Toluene (CAS 108-88-3)	Can be absorbed through the skin.

**Canada - Saskatchewan OELs: Skin designation**

Hexane (CAS 110-54-3)	Can be absorbed through the skin.
Naphthalene (CAS 91-20-3)	Can be absorbed through the skin.
Toluene (CAS 108-88-3)	Can be absorbed through the skin.

**US ACGIH Threshold Limit Values: Skin designation**

Benzene (CAS 71-43-2)	Can be absorbed through the skin.
Hexane (CAS 110-54-3)	Can be absorbed through the skin.
Naphthalene (CAS 91-20-3)	Can be absorbed through the skin.

**Appropriate engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin protection**

**Hand protection** Impervious gloves. Confirm with reputable supplier first.

<b>Other</b>	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. As required by employer code.
<b>Respiratory protection</b>	Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).
<b>Thermal hazards</b>	Not applicable.
<b>General hygiene considerations</b>	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace. When using do not eat or drink.

---

## 9. Physical and Chemical Properties

---

<b>Appearance</b>	Clear
<b>Physical state</b>	Gas.
<b>Form</b>	Spray
<b>Color</b>	Not available.
<b>Odor</b>	Not available.
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	Not available.
<b>Initial boiling point and boiling range</b>	122.79 °F (50.44 °C) (estimated)
<b>Pour point</b>	Not available.
<b>Specific gravity</b>	Not available.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Flash point</b>	-104.4 °F (-75.8 °C) (Propellant) (estimated)
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	> 2.1 (estimated)
<b>Flammability limit - upper (%)</b>	< 10.7 (estimated)
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	Not available.
<b>Vapor density</b>	Not available.
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Explosive properties</b>	Not explosive.
<b>Oxidizing properties</b>	Not oxidizing.

---

## 10. Stability and Reactivity

---

<b>Reactivity</b>	This product may react with strong oxidizing agents.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Conditions to avoid</b>	Do not mix with other chemicals.
<b>Incompatible materials</b>	Strong oxidizing agents. Nitrates. Fluorine. Chlorine.
<b>Hazardous decomposition products</b>	May include and are not limited to: Oxides of carbon.



## 11. Toxicological Information

**Routes of exposure** Eye, Skin contact, Inhalation, Ingestion.

**Information on likely routes of exposure**

**Ingestion** May be fatal if swallowed and enters airways. May cause stomach distress, nausea or vomiting.

**Inhalation** May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.

**Skin contact** Causes skin irritation.

**Eye contact** Causes serious eye irritation.

**Symptoms related to the physical, chemical and toxicological characteristics** Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

**Information on toxicological effects**

**Acute toxicity** Narcotic effects.

<b>Product</b>	<b>Species</b>	<b>Test Results</b>
Spray Adhesive (4080-04) (CAS Mixture)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	5300 mg/kg, 4 Hours, estimated
<i>Inhalation</i>		
LC100	Rabbit	5301 mg/L, 6 Hours, estimated
LC50	Dog	1442 mg/L, 1 Hours, estimated
	Mouse	2327 mg/L, 1 Hours, estimated
	Rat	39445 ppm, 24 Hours, estimated
		2327 mg/L, 1 Hours, estimated
<b>Components</b>		
<b>Species</b>		
<b>Test Results</b>		
1,1-Difluoroethane (CAS 75-37-6)		
<b>Acute</b>		
<i>Inhalation</i>		
LC50	Rat	> 437500 ppm, 4 Hours, ECHA > 64000 ppm
<i>Oral</i>		
LD50	Rat	> 1500 mg/kg
Acetone (CAS 67-64-1)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Guinea pig	> 7426 mg/kg, 24 Hours, ECHA > 9.4 ml/kg, 24 Hours, ECHA
	Rabbit	> 15800 mg/kg, 24 Hours, ECHA > 7426 mg/kg, 24 Hours, ECHA > 20 ml/kg, 24 Hours, ECHA > 9.4 ml/kg, 24 Hours, ECHA
<i>Inhalation</i>		
LC50	Rat	55700 ppm, 3 Hours, ECHA 50100 mg/m <sup>3</sup> , 8 hours, American Industrial Hygiene Association Journal 132 mg/L, 3 Hours, ECHA 76 mg/L, 4 Hours, ECHA/HSDB 50.1 mg/L, 4 Hours, ECHA 50.1 mg/L, 8 Hours
<i>Oral</i>		
LD50	Mouse	3000 mg/kg, Pharmaceutical Chemistry Journal

Components	Species	Test Results
	Rat	5800 mg/kg, Journal of Toxicology and Environmental Health 9.1 ml/kg, ECHA 8.5 ml/kg, ECHA 5.6 ml/kg, ECHA 2.2 ml/kg, ECHA
Cyclohexane (CAS 110-82-7)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg
	Rat	2000 mg/kg
<i>Inhalation</i>		
LC50	Rat	> 32880 mg/m <sup>3</sup> , 4 Hours > 9500 ppm, 4 Hours > 5540 ppm, 4 Hours
NOEL	Monkey	1243 mg/L, 6 Hours
<i>Oral</i>		
LD50	Mouse	813 mg/kg
	Rabbit	> 5000 mg/kg
	Rat	> 5000 mg/kg 8000 mg/kg
Cyclohexane, methyl- (CAS 108-87-2)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg, 24 Hours 86700 mg/kg
<i>Inhalation</i>		
LC100	Rabbit	59.9 mg/L, 6 Hours
LC25	Rabbit	7300 ppm
LC50	Dog	> 4071 ppm, 1 Hours > 16.3 mg/L, 1 Hours
	Mouse	> 6564 ppm, 1 Hours > 26.3 mg/L, 1 Hours 41500 mg/m <sup>3</sup>
	Rat	> 6564 ppm, 1 Hours > 26.3 mg/L, 1 Hours
<i>Oral</i>		
LD50	Mouse	2250 mg/kg
Heptane (CAS 142-82-5)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg, 24 Hours, HCHA
<i>Inhalation</i>		
LC50	Rat	> 73.5 mg/L, 4 Hours, ECHA > 29.3 mg/L, 4 Hours, ECHA 103 mg/L, 4 Hours, HSDB
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg, ECHA

Components	Species	Test Results
Hexane (CAS 110-54-3)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg, 4 Hours > 5 ml/kg, 4 Hours
	Rat	3000 mg/kg
<i>Inhalation</i>		
LC50	Mouse	48000 ppm, 4 Hours
	Rat	> 5000 ppm, 24 Hours > 31.9 mg/L, 4 Hours 73860 ppm, 4 Hours 38500 mg/l/4h
<i>Oral</i>		
LD50	Rat	28710 mg/kg 24 ml/kg
Methane, oxybis- (CAS 115-10-6)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Not available	
<i>Inhalation</i>		
LC50	Mouse	386 ppm, 30 Minutes, HSDB
	Rat	164000 ppm, 4 Hours, ECHA/HSDB 308.5 mg/L, 4 Hours, HSDB
<i>Oral</i>		
LD50	Not available	
Methyl acetate (CAS 79-20-9)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	> 5000 mg/kg
	Rat	> 2000 mg/kg, 24 Hours
<i>Inhalation</i>		
LC100	Rabbit	98.4 mg/L, 4 Hours
LC50	Rat	> 16000 ppm
<i>Oral</i>		
LD50	Rabbit	3705 mg/kg 3.7 g/kg
	Rat	> 5000 mg/kg 6482 mg/kg
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Guinea pig; Rabbit	> 9.4 ml/kg, 24 Hours
	Rabbit	> 1900 mg/kg, 24 Hours 3160 mg/kg
<i>Inhalation</i>		
LC50	Rat	> 4980 mg/m3, 4 Hours > 5 mg/L, 4 Hours 13700 ppm, 4 Hours 20 ppm 20 mg/l/4h

Components	Species	Test Results
<i>Oral</i> LD50	Rat	> 25 ml/kg 5000 mg/kg 4820 mg/kg
Propane (CAS 74-98-6) <b>Acute</b> <i>Dermal</i> LD50	Not available	
<i>Inhalation</i> LC50	Mouse	539600 ppm, 120 Minutes, ECHA 520400 ppm, 120 Minutes, ECHA 1237 mg/L, 120 Minutes 57 %, 120 Minutes, ECHA 52 %, 120 Minutes
	Rat	> 12000000 ppm, 4 hours > 800000 ppm, 10 Minutes, ECHA > 1464 mg/L, 15 Minutes, HSDB 1442738 mg/m3, 10 Minutes, ECHA 1354944 mg/m3, 10 Minutes, ECHA 570000 ppm, 10 Minutes, ECHA 1355 mg/L, 10 Minutes
<i>Oral</i> LD50	Not available	
Toluene (CAS 108-88-3) <b>Acute</b> <i>Dermal</i> LD50	Rabbit	> 5000 mg/kg, 24 Hours 12196 mg/kg 12125 mg/kg 8390 mg/kg 14.1 ml/kg
<i>Inhalation</i> LC50	Mouse	7100 mg/L, 4 Hours 6405 - 7436 ppm, 6 Hours 5320 ppm, 8 Hours 400 ppm, 24 Hours
	Rat	26700 ppm, 1 Hours <= 28800 mg/m <sup>3</sup> , 4 Hours 12200 ppm, 2 Hours 8000 ppm, 4 Hours 5879 - 6281 ppm, 6 Hours 25.7 mg/L, 4 Hours 12.5 mg/l/4h
<i>Oral</i> LD50	Rat	> 5580 mg/kg > 5000 mg/kg 636 mg/kg
<b>Skin corrosion/irritation</b>	Causes skin irritation.	
<b>Exposure minutes</b>	Not available.	

<b>Erythema value</b>	Not available.
<b>Oedema value</b>	Not available.
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.
<b>Corneal opacity value</b>	Not available.
<b>Iris lesion value</b>	Not available.
<b>Conjunctival reddening value</b>	Not available.
<b>Conjunctival oedema value</b>	Not available.
<b>Recover days</b>	Not available.
<b>Respiratory or skin sensitization</b>	
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.
<b>Skin sensitization</b>	Not available.
<b>Mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
<b>Carcinogenicity</b>	See below. Contains < 3% (w/w) DMSO-extract
<b>ACGIH Carcinogens</b>	
Benzene (CAS 71-43-2)	A1 Confirmed human carcinogen.
Benzene, ethyl- (CAS 100-41-4)	A3 Confirmed animal carcinogen with unknown relevance to humans.
Naphthalene (CAS 91-20-3)	A3 Confirmed animal carcinogen with unknown relevance to humans.
<b>Canada - Alberta OELs: Carcinogen category</b>	
Benzene (CAS 71-43-2)	Confirmed human carcinogen.
<b>Canada - Manitoba OELs: carcinogenicity</b>	
BENZENE (CAS 71-43-2)	Confirmed human carcinogen.
ETHYL BENZENE (CAS 100-41-4)	Confirmed animal carcinogen with unknown relevance to humans.
NAPHTHALENE (CAS 91-20-3)	Confirmed animal carcinogen with unknown relevance to humans.
<b>Canada - Quebec OELs: Carcinogen category</b>	
Benzene (CAS 71-43-2)	Detected carcinogenic effect in humans.
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>	
Benzene (CAS 71-43-2)	Volume 29, Supplement 7, Volume 100F 1 Carcinogenic to humans.
Benzene, ethyl- (CAS 100-41-4)	Volume 77 - 2B Possibly carcinogenic to humans.
Naphthalene (CAS 91-20-3)	Volume 82 - 2B Possibly carcinogenic to humans.
Toluene (CAS 108-88-3)	Volume 47, Volume 71 - 3 Not classifiable as to carcinogenicity to humans.
<b>US - California Proposition 65 - CRT: Listed date/Carcinogenic substance</b>	
Benzene (CAS 71-43-2)	
Benzene, ethyl- (CAS 100-41-4)	
Naphthalene (CAS 91-20-3)	
<b>US NTP Report on Carcinogens: Anticipated carcinogen</b>	
Naphthalene (CAS 91-20-3)	Reasonably Anticipated to be a Human Carcinogen.
<b>US NTP Report on Carcinogens: Known carcinogen</b>	
Benzene (CAS 71-43-2)	Known To Be Human Carcinogen.
<b>US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)</b>	
Benzene (CAS 71-43-2)	Cancer
<b>Reproductive toxicity</b>	Suspected of damaging fertility or the unborn child.
<b>Teratogenicity</b>	Not available.
<b>Specific target organ toxicity - single exposure</b>	May cause drowsiness and dizziness.
<b>Specific target organ toxicity - repeated exposure</b>	Not classified.
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.
<b>Chronic effects</b>	Prolonged inhalation may be harmful.

---

## 12. Ecological Information

---

**Ecotoxicity** See below

**Ecotoxicological data****Components**

		<b>Species</b>	<b>Test Results</b>
Acetone (CAS 67-64-1)			
Crustacea	EC50	Daphnia	13999 mg/L, 48 Hours
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia magna)	10294 - 17704 mg/L, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/L, 96 hours
Cyclohexane (CAS 110-82-7)			
Algae	IC50	Algae	500 mg/L, 72 Hours
<b>Aquatic</b>			
Fish	LC50	Fathead minnow (Pimephales promelas)	23.03 - 42.07 mg/L, 96 hours
Cyclohexane, methyl- (CAS 108-87-2)			
<b>Aquatic</b>			
Fish	LC50	Striped bass (Morone saxatilis)	5.8 mg/L, 96 hours
Heptane (CAS 142-82-5)			
<b>Aquatic</b>			
Fish	LC50	Mozambique tilapia (Tilapia mossambica)	375 mg/L, 96 hours
Hexane (CAS 110-54-3)			
<b>Aquatic</b>			
Fish	LC50	Fathead minnow (Pimephales promelas)	2.101 - 2.981 mg/L, 96 hours
Methyl acetate (CAS 79-20-9)			
Algae	IC50	Algae	120 mg/L, 72 hours
Crustacea	EC50	Daphnia	1026.7 mg/L, 48 hours
<b>Aquatic</b>			
Fish	LC50	Fathead minnow (Pimephales promelas)	295 - 348 mg/L, 96 hours
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia pulex)	2.7 - 5.1 mg/L, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	8.8 mg/L, 96 hours
			8.8 mg/L, 96 hours
Toluene (CAS 108-88-3)			
Algae	IC50	Algae	433 mg/L, 72 Hours
Crustacea	EC50	Daphnia	7.645 mg/L, 48 Hours
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia magna)	5.46 - 9.83 mg/L, 48 hours
Fish	LC50	Coho salmon,silver salmon (Oncorhynchus kisutch)	8.11 mg/L, 96 hours

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential**

**Mobility in soil**

**Mobility in general**

**Other adverse effects**

No data available.

Not available.

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation)

---

### 13. Disposal Considerations

---

**Disposal instructions**

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations**

Dispose in accordance with all applicable regulations.

**Hazardous waste code**

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Waste from residues / unused products**

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging**

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

---

## 14. Transport Information

---

**Transport of Dangerous Goods (TDG) Proof of Classification** In accordance with Part 2.2.1 (SOR/2014-152) of the Transportation of Dangerous Goods Regulations, we certify that the classification of this product is correct as of the SDS date of issue.

**U.S. Department of Transportation (DOT)**

**Basic shipping requirements:**

**UN number** UN1950  
**Proper shipping name** Aerosols, flammable, (each not exceeding 1 L capacity)  
**Hazard class** Limited Quantity - US

**Transportation of Dangerous Goods (TDG - Canada)**

**Basic shipping requirements:**

**UN number** UN1950  
**Proper shipping name** AEROSOLS, flammable  
**Hazard class** Limited Quantity - Canada

**IATA/ICAO (Air)**

**Basic shipping requirements:**


**UN number** UN1950  
**Proper shipping name** Aerosols, flammable  
**Hazard class** Limited Quantity - IATA

**IMDG (Marine Transport)**

**Basic shipping requirements:**

**UN number** UN1950  
**Proper shipping name** AEROSOLS  
**Hazard class** Limited Quantity - IMDG

**DOT; IMDG; TDG**



**IATA**



---

## 15. Regulatory Information

---

**Canadian federal regulations** This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

**Canada CEPA Schedule I: Listed substance**

1,1-Difluoroethane (CAS 75-37-6)	Listed.
Benzene (CAS 71-43-2)	Listed.
Naphthalene (CAS 91-20-3)	Listed.

**Canada DSL Challenge Substances: Listed substance**

Hexane (CAS 110-54-3)	Listed.
Naphthalene (CAS 91-20-3)	Listed.

**Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number**

Benzene (CAS 71-43-2)	1 TONNES
-----------------------	----------

Heptane (CAS 142-82-5)	1 TONNES
Hexane (CAS 110-54-3)	1 TONNES
Methane, oxybis- (CAS 115-10-6)	1 TONNES
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	1 TONNES
Propane (CAS 74-98-6)	1 TONNES
Toluene (CAS 108-88-3)	1 TONNES

**Export Control List (CEPA 1999, Schedule 3)**

Not listed.

**Greenhouse Gases**

1,1-Difluoroethane (CAS 75-37-6)

**Precursor Control Regulations**

Acetone (CAS 67-64-1)	Class B
Toluene (CAS 108-88-3)	Class B

**WHMIS 2015 Exemptions** Not applicable

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Acetone (CAS 67-64-1)	Listed.
Benzene (CAS 71-43-2)	Listed.
Benzene, ethyl- (CAS 100-41-4)	Listed.
Cyclohexane (CAS 110-82-7)	Listed.
Cyclohexane, methyl- (CAS 108-87-2)	Listed.
Heptane (CAS 142-82-5)	Listed.
Hexane (CAS 110-54-3)	Listed.
Methane, oxybis- (CAS 115-10-6)	Listed.
Methyl acetate (CAS 79-20-9)	Listed.
Naphthalene (CAS 91-20-3)	Listed.
Propane (CAS 74-98-6)	Listed.
Toluene (CAS 108-88-3)	Listed.

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Benzen (CAS 71-43-2)	Cancer Central nervous system Blood Aspiration Skin Eye respiratory tract irritation Flammability
----------------------	--

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

<b>Hazard categories</b>	Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No
--------------------------	---

**SARA 302 Extremely hazardous substance** No

**SARA 311/312 Hazardous chemical** No

**SARA 313 (TRI reporting)**  
Not regulated.

**Other federal regulations**

**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Benzen (CAS 71-43-2)  
Benzen, ethyl- (CAS 100-41-4)  
Hexane (CAS 110-54-3)  
Naphthalene (CAS 91-20-3)  
Toluene (CAS 108-88-3)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

1,1-Difluoroethane (CAS 75-37-6)  
Methane, oxybis- (CAS 115-10-6)  
Propane (CAS 74-98-6)

**US state regulations** See below



**US - California Hazardous Substances (Director's): Listed substance**

Acetone (CAS 67-64-1)	Listed.
Benzene (CAS 71-43-2)	Listed.
Benzene, ethyl- (CAS 100-41-4)	Listed.
Cyclohexane (CAS 110-82-7)	Listed.
Cyclohexane, methyl- (CAS 108-87-2)	Listed.
Heptane (CAS 142-82-5)	Listed.
Hexane (CAS 110-54-3)	Listed.
Methyl acetate (CAS 79-20-9)	Listed.
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	Listed.
Naphthalene (CAS 91-20-3)	Listed.
Toluene (CAS 108-88-3)	Listed.

**US - Illinois Chemical Safety Act: Listed substance**

Acetone (CAS 67-64-1)
Benzene (CAS 71-43-2)
Benzene, ethyl- (CAS 100-41-4)
Cyclohexane (CAS 110-82-7)
Cyclohexane, methyl- (CAS 108-87-2)
Heptane (CAS 142-82-5)
Hexane (CAS 110-54-3)
Methane, oxybis- (CAS 115-10-6)
Methyl acetate (CAS 79-20-9)
Naphthalene (CAS 91-20-3)
Propane (CAS 74-98-6)
Toluene (CAS 108-88-3)

**US - Louisiana Spill Reporting: Listed substance**

Acetone (CAS 67-64-1)	Listed.
Benzene (CAS 71-43-2)	Listed.
Benzene, ethyl- (CAS 100-41-4)	Listed.
Cyclohexane (CAS 110-82-7)	Listed.
Cyclohexane, methyl- (CAS 108-87-2)	Listed.
Heptane (CAS 142-82-5)	Listed.
Hexane (CAS 110-54-3)	Listed.
Methane, oxybis- (CAS 115-10-6)	Listed.
Methyl acetate (CAS 79-20-9)	Listed.
Naphthalene (CAS 91-20-3)	Listed.
Propane (CAS 74-98-6)	Listed.
Toluene (CAS 108-88-3)	Listed.

**US - Michigan Critical Materials Register: Parameter number**

Benzene (CAS 71-43-2)	BENZENE
Toluene (CAS 108-88-3)	TOLUENE

**US - Minnesota Haz Subs: Listed substance**

Acetone (CAS 67-64-1)	Listed.
Benzene (CAS 71-43-2)	Listed.
Benzene, ethyl- (CAS 100-41-4)	Listed.
Cyclohexane (CAS 110-82-7)	Listed.
Cyclohexane, methyl- (CAS 108-87-2)	Listed.
Heptane (CAS 142-82-5)	Listed.
Hexane (CAS 110-54-3)	Listed.
Methane, oxybis- (CAS 115-10-6)	Listed.
Methyl acetate (CAS 79-20-9)	Listed.
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	Listed.
Naphthalene (CAS 91-20-3)	Listed.
Propane (CAS 74-98-6)	Listed.
Toluene (CAS 108-88-3)	Listed.

**US - New Jersey RTK - Substances: Listed substance**

1,1-Difluoroethane (CAS 75-37-6)
Acetone (CAS 67-64-1)
Benzene (CAS 71-43-2)
Benzene, ethyl- (CAS 100-41-4)
Cyclohexane (CAS 110-82-7)
Cyclohexane, methyl- (CAS 108-87-2)
Heptane (CAS 142-82-5)
Hexane (CAS 110-54-3)
Methane, oxybis- (CAS 115-10-6)
Methyl acetate (CAS 79-20-9)
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

Naphthalene (CAS 91-20-3)  
Propane (CAS 74-98-6)  
Toluene (CAS 108-88-3)

**US - North Carolina Toxic Air Pollutants: Listed substance**

Benzene (CAS 71-43-2)  
Hexane (CAS 110-54-3)  
Toluene (CAS 108-88-3)

**US - Pennsylvania RTK - Hazardous Substances: Special hazard**

Benzene (CAS 71-43-2)

**US - Texas Effects Screening Levels Hazard Data: Simple asphyxiant**

Propane (CAS 74-98-6)

**US - Texas Effects Screening Levels: Listed substance**

1,1-Difluoroethane (CAS 75-37-6)	Listed.
Acetone (CAS 67-64-1)	Listed.
Benzene (CAS 71-43-2)	Listed.
Benzene, ethyl- (CAS 100-41-4)	Listed.
Cyclohexane (CAS 110-82-7)	Listed.
Cyclohexane, methyl- (CAS 108-87-2)	Listed.
Heptane (CAS 142-82-5)	Listed.
Hexane (CAS 110-54-3)	Listed.
Methane, oxybis- (CAS 115-10-6)	Listed.
Methyl acetate (CAS 79-20-9)	Listed.
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	Listed.
Naphthalene (CAS 91-20-3)	Listed.
Propane (CAS 74-98-6)	Listed.
Toluene (CAS 108-88-3)	Listed.

**US - Washington Chemical of High Concern to Children: Listed substance**

Benzene (CAS 71-43-2)  
Benzene, ethyl- (CAS 100-41-4)  
Toluene (CAS 108-88-3)

**US. Massachusetts RTK - Substance List**

1,1-Difluoroethane (CAS 75-37-6)  
Acetone (CAS 67-64-1)  
Benzene (CAS 71-43-2)  
Benzene, ethyl- (CAS 100-41-4)  
Cyclohexane (CAS 110-82-7)  
Cyclohexane, methyl- (CAS 108-87-2)  
Heptane (CAS 142-82-5)  
Hexane (CAS 110-54-3)  
Methane, oxybis- (CAS 115-10-6)  
Methyl acetate (CAS 79-20-9)  
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)  
Naphthalene (CAS 91-20-3)  
Propane (CAS 74-98-6)  
Toluene (CAS 108-88-3)

**US. New Jersey Worker and Community Right-to-Know Act**

1,1-Difluoroethane (CAS 75-37-6)  
Benzene (CAS 71-43-2)  
Benzene, ethyl- (CAS 100-41-4)  
Cyclohexane (CAS 110-82-7)  
Hexane (CAS 110-54-3)  
Methane, oxybis- (CAS 115-10-6)  
Naphthalene (CAS 91-20-3)  
Propane (CAS 74-98-6)  
Toluene (CAS 108-88-3)

**US. Pennsylvania Worker and Community Right-to-Know Law**

Acetone (CAS 67-64-1)  
Benzene (CAS 71-43-2)  
Benzene, ethyl- (CAS 100-41-4)  
Cyclohexane (CAS 110-82-7)  
Cyclohexane, methyl- (CAS 108-87-2)  
Heptane (CAS 142-82-5)  
Hexane (CAS 110-54-3)  
Methane, oxybis- (CAS 115-10-6)  
Methyl acetate (CAS 79-20-9)  
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)  
Naphthalene (CAS 91-20-3)  
Propane (CAS 74-98-6)

Toluene (CAS 108-88-3)

**US. Rhode Island RTK**

- Acetone (CAS 67-64-1)
- Benzene (CAS 71-43-2)
- Benzene, ethyl- (CAS 100-41-4)
- Cyclohexane (CAS 110-82-7)
- Cyclohexane, methyl- (CAS 108-87-2)
- Heptane (CAS 142-82-5)
- Hexane (CAS 110-54-3)
- Methane, oxybis- (CAS 115-10-6)
- Methyl acetate (CAS 79-20-9)
- Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)
- Naphthalene (CAS 91-20-3)
- Propane (CAS 74-98-6)
- Toluene (CAS 108-88-3)

**US. California Proposition 65**

**US - California Proposition 65 - CRT: Listed date/Carcinogenic substance**

- Benzene (CAS 71-43-2) Listed: February 27, 1987
- Benzene, ethyl- (CAS 100-41-4) Listed: June 11, 2004
- Naphthalene (CAS 91-20-3) Listed: April 19, 2002

**US - California Proposition 65 - CRT: Listed date/Developmental toxin**

- Benzene (CAS 71-43-2) Listed: December 26, 1997
- Toluene (CAS 108-88-3) Listed: January 1, 1991

**US - California Proposition 65 - CRT: Listed date/Male reproductive toxin**

- Benzene (CAS 71-43-2) Listed: December 26, 1997

**Inventory status**


Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Not available
Canada	Non-Domestic Substances List (NDSL)	Not available
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

**16. Other Information**

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

<b>HEALTH</b>	* 2
<b>FLAMMABILITY</b>	4
<b>PHYSICAL HAZARD</b>	0
<b>PERSONAL PROTECTION</b>	X



**Disclaimer**

The information in the sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

**Issue date**

15-January-2018

**Version #**

01

**Effective date**

15-January-2018

**Prepared by**

Nu-Calgon Technical Service Phone: (314) 469-7000

**Other information**

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.