

## 1. Product and Company Identification

<b>Product identifier</b>	<b>Degreasing Solvent LV (4083-83)</b>
<b>Other means of identification</b>	Not available
<b>Recommended use</b>	Degreaser
<b>Recommended restrictions</b>	None known.
<b>Manufacturer information</b>	Nu-Calgon 2008 Altom Court St. Louis, MO 63146 US Phone: 314-469-7000 / 800-554-5499 Emergency Phone: 1-800-424-9300 (CHEMTREC)
<b>Supplier</b>	See above.

## 2. Hazards Identification

<b>Physical hazards</b>	Flammable aerosols	Category 1
	Gases under pressure	Liquefied gas
<b>Health hazards</b>	Serious eye damage/eye irritation	Category 2A
	Germ cell mutagenicity	Category 1B
	Carcinogenicity	Category 1B
	Reproductive toxicity	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2
<b>Environmental hazards</b>	Not classified.	
<b>WHMIS 2015 defined hazards</b>	Not classified	

**Label elements**



**Signal word** Danger

**Hazard statement** Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer. Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

**Precautionary statement**

**Prevention** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/vapors/spray. Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

**Response** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.  
IF exposed or concerned: Get medical advice/attention.

**Storage** Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

**WHMIS 2015: Health Hazard(s) not otherwise classified (HHNOC)** None known

**WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC)** None known

<b>Hazard(s) not otherwise classified (HNOC)</b>	None known.
<b>Supplemental information</b>	None.

### 3. Composition/Information on Ingredients

#### Mixture

Chemical name	Common name and synonyms	CAS number	%
Acetone		67-64-1	59-97
Naphtha (petroleum), hydrotreated light		64742-49-0	4-9
Carbon dioxide		124-38-9	3-7
Toluene		108-88-3	1.1-2
Benzene		71-43-2	Trace
Heptane		142-82-5	Trace
Methanol		67-56-1	Trace
Xylene		1330-20-7	Trace

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

### 4. First Aid Measures

<b>Inhalation</b>	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
<b>Skin contact</b>	Flush with cool water. Wash with soap and water. Obtain medical attention if irritation persists.
<b>Eye contact</b>	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
<b>Ingestion</b>	Rinse mouth. Do not induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Never give anything by mouth if victim is unconscious, or is convulsing. Obtain medical attention.
<b>Most important symptoms/effects, acute and delayed</b>	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Prolonged exposure may cause chronic effects.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Symptoms may be delayed.
<b>General information</b>	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Keep out of reach of children.

### 5. Fire Fighting Measures

<b>Suitable extinguishing media</b>	Dry chemical. Foam. Carbon dioxide.
<b>Unsuitable extinguishing media</b>	None known.
<b>Specific hazards arising from the chemical</b>	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire-fighting equipment/instructions</b>	In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes.
<b>General fire hazards</b>	Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.
<b>Hazardous combustion products</b>	May include and are not limited to: Oxides of carbon.

---

## 6. Accidental Release Measures

---

**Personal precautions, protective equipment and emergency procedures**

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

**Methods and materials for containment and cleaning up**

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

**Environmental precautions**

Do not discharge into lakes, streams, ponds or public waters.

---

## 7. Handling and Storage

---

**Precautions for safe handling**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not smoke while using or until sprayed surface is thoroughly dry. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not re-use empty containers. Do not breathe vapors or spray mist. Avoid contact with eyes, skin and clothing. Pregnant or breastfeeding women must not handle this product. Use only in well-ventilated areas. Avoid prolonged exposure. Wear appropriate personal protective equipment. Wash thoroughly after handling. Use good industrial hygiene practices in handling this material. When using do not eat or drink.

**Conditions for safe storage, including any incompatibilities**

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not handle or store near an open flame, heat or other sources of ignition. Do not puncture, incinerate or crush. Store in a well-ventilated place. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Stored containers should be periodically checked for general condition and leakage.

---

## 8. Exposure Controls/Personal Protection

---

**Occupational exposure limits****Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)**

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	1800 mg/m3 750 ppm
	TWA	1200 mg/m3 500 ppm
Benzene (CAS 71-43-2)	STEL	8 mg/m3 2.5 ppm
	TWA	1.6 mg/m3 0.5 ppm
Carbon dioxide (CAS 124-38-9)	STEL	54000 mg/m3 30000 ppm
	TWA	9000 mg/m3 5000 ppm
Heptane (CAS 142-82-5)	STEL	2050 mg/m3 500 ppm
	TWA	1640 mg/m3 400 ppm
Methanol (CAS 67-56-1)	STEL	328 mg/m3 250 ppm
	TWA	262 mg/m3 200 ppm

**Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)**

Components	Type	Value
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	TWA	1590 mg/m <sup>3</sup>
		400 ppm
Toluene (CAS 108-88-3)	TWA	188 mg/m <sup>3</sup>
		50 ppm
Xylene (CAS 1330-20-7)	STEL	651 mg/m <sup>3</sup>
		150 ppm
	TWA	434 mg/m <sup>3</sup>
		100 ppm

**Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)**

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	500 ppm
	TWA	250 ppm
Benzene (CAS 71-43-2)	STEL	2.5 ppm
	TWA	0.5 ppm
Carbon dioxide (CAS 124-38-9)	STEL	15000 ppm
	TWA	5000 ppm
Heptane (CAS 142-82-5)	STEL	500 ppm
	TWA	400 ppm
Methanol (CAS 67-56-1)	STEL	250 ppm
	TWA	200 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm
Xylene (CAS 1330-20-7)	STEL	150 ppm
	TWA	100 ppm

**Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)**

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	500 ppm
	TWA	250 ppm
Benzene (CAS 71-43-2)	STEL	2.5 ppm
	TWA	0.5 ppm
Carbon dioxide (CAS 124-38-9)	STEL	30000 ppm
	TWA	5000 ppm
Heptane (CAS 142-82-5)	STEL	500 ppm
	TWA	400 ppm
Methanol (CAS 67-56-1)	STEL	250 ppm
	TWA	200 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm
Xylene (CAS 1330-20-7)	STEL	150 ppm
	TWA	100 ppm

**Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)**

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	750 ppm
	TWA	500 ppm
Benzene (CAS 71-43-2)	STEL	2.5 ppm
	TWA	0.5 ppm

**Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)**

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	STEL	30000 ppm
	TWA	5000 ppm
Heptane (CAS 142-82-5)	STEL	500 ppm
	TWA	400 ppm
Methanol (CAS 67-56-1)	STEL	250 ppm
	TWA	200 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm
Xylene (CAS 1330-20-7)	STEL	150 ppm
	TWA	100 ppm

**Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)**

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	2380 mg/m3 1000 ppm
	TWA	1190 mg/m3 500 ppm
Benzene (CAS 71-43-2)	STEL	15.5 mg/m3 5 ppm
	TWA	3 mg/m3 1 ppm
Carbon dioxide (CAS 124-38-9)	STEL	54000 mg/m3 30000 ppm
	TWA	9000 mg/m3 5000 ppm
Heptane (CAS 142-82-5)	STEL	2050 mg/m3 500 ppm
	TWA	1640 mg/m3 400 ppm
Methanol (CAS 67-56-1)	STEL	328 mg/m3 250 ppm
	TWA	262 mg/m3 200 ppm
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	TWA	1590 mg/m3 400 ppm
	TWA	188 mg/m3 50 ppm
Xylene (CAS 1330-20-7)	STEL	651 mg/m3 150 ppm
	TWA	434 mg/m3 100 ppm

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Components	Type	Value
Benzene (CAS 71-43-2)	STEL	5 ppm
	TWA	1 ppm

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
Acetone (CAS 67-64-1)	PEL	2400 mg/m3 1000 ppm
	PEL	9000 mg/m3 5000 ppm
Heptane (CAS 142-82-5)	PEL	2000 mg/m3

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
		500 ppm
Methanol (CAS 67-56-1)	PEL	260 mg/m <sup>3</sup> 200 ppm
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	PEL	400 mg/m <sup>3</sup>  100 ppm
Xylene (CAS 1330-20-7)	PEL	435 mg/m <sup>3</sup> 100 ppm

**US. OSHA Table Z-2 (29 CFR 1910.1000)**

Components	Type	Value
Benzene (CAS 71-43-2)	Ceiling	25 ppm
	TWA	10 ppm
Toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

**US. ACGIH Threshold Limit Values**

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	500 ppm
	TWA	250 ppm
Benzene (CAS 71-43-2)	STEL	2.5 ppm
	TWA	0.5 ppm
Carbon dioxide (CAS 124-38-9)	STEL	30000 ppm
	TWA	5000 ppm
Heptane (CAS 142-82-5)	STEL	500 ppm
	TWA	400 ppm
Methanol (CAS 67-56-1)	STEL	250 ppm
	TWA	200 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm
Xylene (CAS 1330-20-7)	STEL	150 ppm
	TWA	100 ppm

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	590 mg/m <sup>3</sup> 250 ppm
Benzene (CAS 71-43-2)	STEL	1 ppm
	TWA	0.1 ppm
Carbon dioxide (CAS 124-38-9)	STEL	54000 mg/m <sup>3</sup>  30000 ppm
	TWA	9000 mg/m <sup>3</sup> 5000 ppm
Heptane (CAS 142-82-5)	Ceiling	1800 mg/m <sup>3</sup> 440 ppm
	TWA	350 mg/m <sup>3</sup> 85 ppm
Methanol (CAS 67-56-1)	STEL	325 mg/m <sup>3</sup> 250 ppm
	TWA	260 mg/m <sup>3</sup> 200 ppm
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	TWA	400 mg/m <sup>3</sup>  100 ppm

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value
Toluene (CAS 108-88-3)	STEL	560 mg/m3
		150 ppm
	TWA	375 mg/m3
		100 ppm

**Biological limit values**

**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	25 mg/L	Acetone	Urine	*
Benzene (CAS 71-43-2)	25 µg/g	S-Phenylmercapuric acid	Creatinine in urine	*
Methanol (CAS 67-56-1)	15 mg/L	Methanol	Urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/L	Toluene	Urine	*
	0.02 mg/L	Toluene	Blood	*
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Exposure guidelines**

**Canada - Alberta OELs: Skin designation**

Benzene (CAS 71-43-2)	Can be absorbed through the skin.
Methanol (CAS 67-56-1)	Can be absorbed through the skin.
Toluene (CAS 108-88-3)	Can be absorbed through the skin.

**Canada - British Columbia OELs: Skin designation**

Benzene (CAS 71-43-2)	Can be absorbed through the skin.
Methanol (CAS 67-56-1)	Can be absorbed through the skin.

**Canada - Manitoba OELs: Skin designation**

Benzene (CAS 71-43-2)	Can be absorbed through the skin.
Methanol (CAS 67-56-1)	Can be absorbed through the skin.

**Canada - Ontario OELs: Skin designation**

Benzene (CAS 71-43-2)	Can be absorbed through the skin.
Methanol (CAS 67-56-1)	Can be absorbed through the skin.

**Canada - Quebec OELs: Skin designation**

Methanol (CAS 67-56-1)	Can be absorbed through the skin.
Toluene (CAS 108-88-3)	Can be absorbed through the skin.

**Canada - Saskatchewan OELs: Skin designation**

Methanol (CAS 67-56-1)	Can be absorbed through the skin.
Toluene (CAS 108-88-3)	Can be absorbed through the skin.

**US ACGIH Threshold Limit Values: Skin designation**

Benzene (CAS 71-43-2)	Can be absorbed through the skin.
Methanol (CAS 67-56-1)	Can be absorbed through the skin.

**US. NIOSH: Pocket Guide to Chemical Hazards**

Methanol (CAS 67-56-1)	Can be absorbed through the skin.
------------------------	-----------------------------------

**Appropriate engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Wear safety glasses with side shields (or goggles).

**Skin protection**

**Hand protection**

Impervious gloves. Confirm with reputable supplier first. PVC gloves. Neoprene. Nitrile

**Other**

Wear suitable protective clothing. Use of an impervious apron is recommended. As required by employer code.

**Respiratory protection**

Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).

**Thermal hazards**

Not applicable.

**General hygiene considerations**

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. When using do not eat or drink.

---

**9. Physical and Chemical Properties**

---

<b>Appearance</b>	Clear Liquid
<b>Physical state</b>	Gas.
<b>Form</b>	Aerosol. Spray
<b>Color</b>	Not available.
<b>Odor</b>	Sweet, Pungent
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	Not available.
<b>Initial boiling point and boiling range</b>	Not available.
<b>Pour point</b>	Not available.
<b>Specific gravity</b>	Not available.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Flash point</b>	Not available.
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	Not available.
<b>Flammability limit - upper (%)</b>	Not available.
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	Not available.
<b>Vapor density</b>	Not available.
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Density</b>	6.70609 lb/gal
<b>Explosive properties</b>	Not explosive.
<b>Oxidizing properties</b>	Not oxidizing.
<b>VOC (Weight %)</b>	9.50390 %

---

**10. Stability and Reactivity**

---

<b>Reactivity</b>	This product may react with strong oxidizing agents.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Conditions to avoid</b>	Heat. Do not mix with other chemicals.
<b>Incompatible materials</b>	Acids. Strong oxidizing agents. Reducing agents. Caustics.
<b>Hazardous decomposition products</b>	May include and are not limited to: Oxides of carbon.

---

**11. Toxicological Information**

---

<b>Routes of exposure</b>	Eye, Skin contact, Inhalation, Ingestion.
<b>Information on likely routes of exposure</b>	
<b>Ingestion</b>	May cause stomach distress, nausea or vomiting.



**Inhalation**

May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.

**Skin contact**

No adverse effects due to skin contact are expected.

**Eye contact**

Causes serious eye irritation.

**Symptoms related to the physical, chemical and toxicological characteristics**

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

**Information on toxicological effects****Acute toxicity**

Narcotic effects.

**Components****Species****Test Results**

Acetone (CAS 67-64-1)

**Acute***Dermal*

LD50

Rabbit

15800 mg/kg

20 ml/kg

*Inhalation*

LC50

Mouse

44000 mg/m<sup>3</sup>/4H

Rat

76 mg/L, 4 Hours

50.1 mg/L, 8 Hours

39 mg/l/4h

*Oral*

LD50

Human

2857 mg/kg

Mouse

3000 mg/kg

Rabbit

5340 mg/kg

Rat

5800 mg/kg

Benzene (CAS 71-43-2)

**Acute***Dermal*

LD50

Guinea pig

> 9400 mg/kg

Rabbit

8263 mg/kg

8260 mg/kg

*Inhalation*

LC50

Mouse

9980 ppm

Rat

44700 mg/m<sup>3</sup>, 4 Hours

13700 mg/l/4h

10000 ppm, 7 Hours

*Oral*

LD50

Mouse

4700 mg/kg

Rat

2990 mg/kg

690 mg/kg

Carbon dioxide (CAS 124-38-9)

**Acute***Inhalation*

LC50

Not available

*Oral*

LD50

Not available

Heptane (CAS 142-82-5)

**Acute***Inhalation*

LC50

Rat

103 mg/L, 4 Hours

LD50

Mouse

75 mg/L, 2 Hours

*Oral*

LD50

Rat

15000 mg/kg

Components	Species	Test Results
Methanol (CAS 67-56-1)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	15800 - 20000 mg/kg, HSDB
	Rat	> 450000 mg/kg, HSDB
<i>Inhalation</i>		
LC50	Cat	85.4 mg/l/4h, HSDB
		43.7 mg/L, 6 Hours
	Rat	64000 ppm, 4 Hours, HSDB
		87.5 mg/L, 6 Hours
		83.2 - 128.8 mg/l/4h
<i>Oral</i>		
LD50	Dog	8000 mg/kg, HSDB
	Human	143 - 300 mg/kg
	Monkey	3000 mg/kg
		2000 mg/kg, HSDB
	Mouse	7300 mg/kg, HSDB
	Rabbit	14200 - 14400 mg/kg
	Rat	790 - 13000 mg/kg, HSDB
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	3160 mg/kg
<i>Inhalation</i>		
LC50	Rat	61 mg/L, 4 Hours
		20 ppm
		20 mg/l/4h
<i>Oral</i>		
LD50	Rat	> 25 ml/kg
		5000 mg/kg
Toluene (CAS 108-88-3)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	12196 mg/kg
		12125 mg/kg
		8390 mg/kg
		14.1 ml/kg
<i>Inhalation</i>		
LC50	Mouse	7100 mg/L, 4 Hours
		5320 ppm, 8 Hours
		400 ppm, 24 Hours
	Rat	26700 ppm, 1 Hours
		<= 28800 mg/m <sup>3</sup> , 4 Hours
		12200 ppm, 2 Hours
		8000 ppm, 4 Hours
		12.5 mg/l/4h
<i>Oral</i>		
LD50	Rat	> 5580 mg/kg
		636 mg/kg

Components	Species	Test Results
Xylene (CAS 1330-20-7)		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	>= 1700 mg/kg
<i>Inhalation</i>		
LC50	Mouse	3907 ppm, 6 Hours
	Rat	6350 ppm, 4 Hours
		29.1 mg/L, 4 Hours
		27.6 mg/L, 4 Hours
		21.7 mg/L, 4 Hours
<i>Oral</i>		
LD50	Mouse	5251 mL/kg
		1590 mg/kg
	Rat	3523 - 8600 mg/kg
<b>Skin corrosion/irritation</b>	Prolonged skin contact may cause temporary irritation.	
<b>Exposure minutes</b>	Not available.	
<b>Erythema value</b>	Not available.	
<b>Oedema value</b>	Not available.	
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.	
<b>Corneal opacity value</b>	Not available.	
<b>Iris lesion value</b>	Not available.	
<b>Conjunctival reddening value</b>	Not available.	
<b>Conjunctival oedema value</b>	Not available.	
<b>Recover days</b>	Not available.	
<b>Respiratory or skin sensitization</b>		
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.	
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.	
<b>Mutagenicity</b>	May cause genetic defects.	
<b>Carcinogenicity</b>	May cause cancer. See below.	
<b>ACGIH Carcinogens</b>		
Benzene (CAS 71-43-2)	A1 Confirmed human carcinogen.	
<b>Canada - Alberta OELs: Carcinogen category</b>		
Benzene (CAS 71-43-2)	Confirmed human carcinogen.	
<b>Canada - Manitoba OELs: carcinogenicity</b>		
ACETONE (CAS 67-64-1)	Not classifiable as a human carcinogen.	
BENZENE (CAS 71-43-2)	Confirmed human carcinogen.	
TOLUENE (CAS 108-88-3)	Not classifiable as a human carcinogen.	
XYLENE (O, M AND P ISOMERS) (CAS 1330-20-7)	Not classifiable as a human carcinogen.	
<b>Canada - Quebec OELs: Carcinogen category</b>		
Benzene (CAS 71-43-2)	Detected carcinogenic effect in humans.	
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>		
Benzene (CAS 71-43-2)	Volume 29, Supplement 7, Volume 100F 1 Carcinogenic to humans.	
Toluene (CAS 108-88-3)	Volume 47, Volume 71 - 3 Not classifiable as to carcinogenicity to humans.	
Xylene (CAS 1330-20-7)	Volume 47, Volume 71 - 3 Not classifiable as to carcinogenicity to humans.	
<b>US - California Proposition 65 - CRT: Listed date/Carcinogenic substance</b>		
Benzene (CAS 71-43-2)		
<b>US NTP Report on Carcinogens: Known carcinogen</b>		
Benzene (CAS 71-43-2)	Known To Be Human Carcinogen.	
<b>US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)</b>		
Benzene (CAS 71-43-2)	Cancer	
<b>Reproductive toxicity</b>	Suspected of damaging fertility or the unborn child.	

<b>Teratogenicity</b>	Toluene (benzene, methyl-) has caused fetotoxicity (reduced fetal weight), behavioural effects (effects on learning and memory) and hearing loss (in males). These effects have been observed in the offspring of rats exposed by inhalation to 1200 or 1800 ppm toluene. These effects were observed in the absence of maternal toxicity.
<b>Specific target organ toxicity - single exposure</b>	May cause drowsiness and dizziness.
<b>Specific target organ toxicity - repeated exposure</b>	May cause damage to organs through prolonged or repeated exposure.
<b>Aspiration hazard</b>	Not an aspiration hazard.
<b>Chronic effects</b>	May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful.

---

## 12. Ecological Information

---

**Ecotoxicity** See below

**Ecotoxicological data**

Components		Species	Test Results
Acetone (CAS 67-64-1)			
Crustacea	EC50	Daphnia	13999 mg/L, 48 Hours
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia magna)	10294 - 17704 mg/L, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/L, 96 hours
Benzene (CAS 71-43-2)			
Algae	IC50	Algae	29 mg/L, 72 Hours
Crustacea	EC50	Daphnia	12.18 mg/L, 48 Hours
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia magna)	8.76 - 15.6 mg/L, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	7.2 - 11.7 mg/L, 96 hours
Heptane (CAS 142-82-5)			
<b>Aquatic</b>			
Fish	LC50	Mozambique tilapia (Tilapia mossambica)	375 mg/L, 96 hours
Methanol (CAS 67-56-1)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia magna)	> 10000 mg/L, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	> 100 mg/L, 96 hours
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia pulex)	2.7 - 5.1 mg/L, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	8.8 mg/L, 96 hours
			8.8 mg/L, 96 hours
Toluene (CAS 108-88-3)			
Algae	IC50	Algae	433 mg/L, 72 Hours
Crustacea	EC50	Daphnia	7.645 mg/L, 48 Hours
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia magna)	5.46 - 9.83 mg/L, 48 hours
Fish	LC50	Coho salmon,silver salmon (Oncorhynchus kisutch)	8.11 mg/L, 96 hours
Xylene (CAS 1330-20-7)			
<b>Aquatic</b>			
Fish	LC50	Bluegill (Lepomis macrochirus)	7.711 - 9.591 mg/L, 96 hours
<b>Persistence and degradability</b>	No data is available on the degradability of this product.		
<b>Bioaccumulative potential</b>			

<b>Mobility in soil</b>	No data available.
<b>Mobility in general</b>	Not available.
<b>Other adverse effects</b>	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

---

### 13. Disposal Considerations

---

<b>Disposal instructions</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Hazardous waste code</b>	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

---

### 14. Transport Information

---

**Transport of Dangerous Goods (TDG) Proof of Classification** In accordance with Part 2.2.1 (SOR/2014-152) of the Transportation of Dangerous Goods Regulations, we certify that the classification of this product is correct as of the SDS date of issue.

**U.S. Department of Transportation (DOT)**

**Basic shipping requirements:**

<b>UN number</b>	UN1950
<b>Proper shipping name</b>	Aerosols, flammable, (each not exceeding 1 L capacity)
<b>Hazard class</b>	Limited Quantity - US
<b>Special provisions</b>	N82
<b>Packaging exceptions</b>	306
<b>Packaging non bulk</b>	None
<b>Packaging bulk</b>	None

**Transportation of Dangerous Goods (TDG - Canada)**

**Basic shipping requirements:**

<b>UN number</b>	UN1950
<b>Proper shipping name</b>	AEROSOLS, flammable
<b>Hazard class</b>	Limited Quantity - Canada
<b>Special provisions</b>	80, 107

**IATA/ICAO (Air)**

**Basic shipping requirements:**

<b>UN number</b>	UN1950
<b>Proper shipping name</b>	Aerosols, flammable
<b>Hazard class</b>	2.1
<b>ERG code</b>	10L

**IMDG (Marine Transport)**

**Basic shipping requirements:**

<b>UN number</b>	UN1950
<b>Proper shipping name</b>	AEROSOLS
<b>Hazard class</b>	2

**DOT; TDG**





## 15. Regulatory Information

**Canadian federal regulations** This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

### Canada CEPA Schedule I: Listed substance

Benzene (CAS 71-43-2) Listed.  
Carbon dioxide (CAS 124-38-9) Listed.

### Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number

Benzene (CAS 71-43-2) 1 TONNES  
Heptane (CAS 142-82-5) 1 TONNES  
Methanol (CAS 67-56-1) 1 TONNES  
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0) 1 TONNES  
Toluene (CAS 108-88-3) 1 TONNES  
Xylene (CAS 1330-20-7) 1 TONNES

### Export Control List (CEPA 1999, Schedule 3)

Not listed.

### Greenhouse Gases

Carbon dioxide (CAS 124-38-9)

### Precursor Control Regulations

Acetone (CAS 67-64-1) Class B  
Toluene (CAS 108-88-3) Class B

**WHMIS 2015 Exemptions** Not applicable

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

### CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1) Listed.  
Benzene (CAS 71-43-2) Listed.  
Heptane (CAS 142-82-5) Listed.  
Methanol (CAS 67-56-1) Listed.  
Toluene (CAS 108-88-3) Listed.  
Xylene (CAS 1330-20-7) Listed.

### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Benzene (CAS 71-43-2) Cancer  
Central nervous system  
Blood  
Aspiration  
Skin  
Eye  
respiratory tract irritation  
Flammability

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

**Hazard categories** Immediate Hazard - Yes  
Delayed Hazard - Yes  
Fire Hazard - Yes  
Pressure Hazard - Yes  
Reactivity Hazard - No

**SARA 302 Extremely hazardous substance** No

**SARA 311/312 Hazardous chemical** No

**SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
Toluene	108-88-3	1.1-2

**Other federal regulations**

**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

- Benzene (CAS 71-43-2)
- Methanol (CAS 67-56-1)
- Toluene (CAS 108-88-3)
- Xylene (CAS 1330-20-7)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**US state regulations**

See below

**US - California Hazardous Substances (Director's): Listed substance**

- Acetone (CAS 67-64-1) Listed.
- Benzene (CAS 71-43-2) Listed.
- Carbon dioxide (CAS 124-38-9) Listed.
- Heptane (CAS 142-82-5) Listed.
- Methanol (CAS 67-56-1) Listed.
- Naphtha (petroleum), hydrotreated light (CAS 64742-49-0) Listed.
- Toluene (CAS 108-88-3) Listed.
- Xylene (CAS 1330-20-7) Listed.

**US - Illinois Chemical Safety Act: Listed substance**

- Acetone (CAS 67-64-1)
- Benzene (CAS 71-43-2)
- Heptane (CAS 142-82-5)
- Methanol (CAS 67-56-1)
- Toluene (CAS 108-88-3)
- Xylene (CAS 1330-20-7)

**US - Louisiana Spill Reporting: Listed substance**

- Acetone (CAS 67-64-1) Listed.
- Benzene (CAS 71-43-2) Listed.
- Heptane (CAS 142-82-5) Listed.
- Methanol (CAS 67-56-1) Listed.
- Toluene (CAS 108-88-3) Listed.
- Xylene (CAS 1330-20-7) Listed.

**US - Michigan Critical Materials Register: Parameter number**

- Benzene (CAS 71-43-2) BENZENE
- Toluene (CAS 108-88-3) TOLUENE
- Xylene (CAS 1330-20-7) XYLENE (ALL ISOMERS)

**US - Minnesota Haz Subs: Listed substance**

- Acetone (CAS 67-64-1) Listed.
- Benzene (CAS 71-43-2) Listed.
- Carbon dioxide (CAS 124-38-9) Listed.
- Heptane (CAS 142-82-5) Listed.
- Methanol (CAS 67-56-1) Listed.
- Naphtha (petroleum), hydrotreated light (CAS 64742-49-0) Listed.
- Toluene (CAS 108-88-3) Listed.
- Xylene (CAS 1330-20-7) Listed.

**US - New Jersey RTK - Substances: Listed substance**

- Acetone (CAS 67-64-1)
- Benzene (CAS 71-43-2)
- Carbon dioxide (CAS 124-38-9)
- Heptane (CAS 142-82-5)
- Methanol (CAS 67-56-1)
- Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)
- Toluene (CAS 108-88-3)
- Xylene (CAS 1330-20-7)

**US - North Carolina Toxic Air Pollutants: Listed substance**

- Benzene (CAS 71-43-2)
- Toluene (CAS 108-88-3)
- Xylene (CAS 1330-20-7)

**US - Pennsylvania RTK - Hazardous Substances: Special hazard**

- Benzene (CAS 71-43-2)

**US - Texas Effects Screening Levels Hazard Data: Simple asphyxiant**

Carbon dioxide (CAS 124-38-9)

**US - Texas Effects Screening Levels: Listed substance**

Acetone (CAS 67-64-1)	Listed.
Benzene (CAS 71-43-2)	Listed.
Carbon dioxide (CAS 124-38-9)	Listed.
Heptane (CAS 142-82-5)	Listed.
Methanol (CAS 67-56-1)	Listed.
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)	Listed.
Toluene (CAS 108-88-3)	Listed.
Xylene (CAS 1330-20-7)	Listed.

**US - Washington Chemical of High Concern to Children: Listed substance**

Benzene (CAS 71-43-2)  
Toluene (CAS 108-88-3)

**US. Massachusetts RTK - Substance List**

Acetone (CAS 67-64-1)
Benzene (CAS 71-43-2)
Carbon dioxide (CAS 124-38-9)
Heptane (CAS 142-82-5)
Methanol (CAS 67-56-1)
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)
Toluene (CAS 108-88-3)
Xylene (CAS 1330-20-7)

**US. New Jersey Worker and Community Right-to-Know Act**

Benzene (CAS 71-43-2)  
Methanol (CAS 67-56-1)  
Toluene (CAS 108-88-3)  
Xylene (CAS 1330-20-7)

**US. Pennsylvania Worker and Community Right-to-Know Law**

Acetone (CAS 67-64-1)
Benzene (CAS 71-43-2)
Carbon dioxide (CAS 124-38-9)
Heptane (CAS 142-82-5)
Methanol (CAS 67-56-1)
Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)
Toluene (CAS 108-88-3)
Xylene (CAS 1330-20-7)

**US. Rhode Island RTK**

Acetone (CAS 67-64-1)  
Benzene (CAS 71-43-2)  
Methanol (CAS 67-56-1)  
Toluene (CAS 108-88-3)  
Xylene (CAS 1330-20-7)

**US. California Proposition 65**

**US - California Proposition 65 - CRT: Listed date/Carcinogenic substance**

Benzene (CAS 71-43-2) Listed: February 27, 1987

**US - California Proposition 65 - CRT: Listed date/Developmental toxin**

Benzene (CAS 71-43-2)	Listed: December 26, 1997
Methanol (CAS 67-56-1)	Listed: March 16, 2012
Toluene (CAS 108-88-3)	Listed: January 1, 1991

**US - California Proposition 65 - CRT: Listed date/Male reproductive toxin**

Benzene (CAS 71-43-2) Listed: December 26, 1997

**Inventory status**

<b>Country(s) or region</b>	<b>Inventory name</b>	<b>On inventory (yes/no)*</b>
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes


\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)



## 16. Other Information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	*	2
FLAMMABILITY		4
PHYSICAL HAZARD		0
PERSONAL PROTECTION		X



### Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

### Issue date

02-March-2017

### Version #

01

### Effective date

02-March-2017

### Prepared by

Nu-Calgon Technical Service Phone: (314) 469-7000

### Other information

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.