

1. Product and Company Identification

Product identifier	Visual Defects 'Crack Finder' Heat Exchanger Leak Detector (4385-06)
Other means of identification	Not available
Recommended use	Heat Exchanger Leak Detection Solution
Recommended restrictions	None known.
Manufacturer information	Nu-Calgon 2611 Schuetz Road St. Louis, MO 63043 US Phone: 314-469-7000 / 800-554-5499 Emergency Phone: 1-800-424-9300 (CHEMTREC)
Supplier	See above.

2. Hazards Identification

Physical hazards	Flammable liquids	Category 3
Health hazards	Serious eye damage/eye irritation	Category 2A
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
Environmental hazards	Not classified.	
WHMIS 2015 defined hazards	Not classified	
Label elements		



Signal word	Warning
Hazard statement	Flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or dizziness.
Precautionary statement	
Prevention	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves, protective clothing, eye protection and face protection. Wash thoroughly after handling. Avoid breathing mist or vapor. Use only outdoors or in a well-ventilated area.
Response	In case of fire: Use appropriate media to extinguish. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER if you feel unwell.
Storage	Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
Disposal	Dispose of container in accordance with local, regional, national and international regulations.
WHMIS 2015: Health Hazard(s) not otherwise classified (HHNOC)	None known
WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC)	None known
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	Not applicable.

3. Composition/Information on Ingredients

Mixture

Chemical name	Common name and synonyms	CAS number	%
Isopropanol		67-63-0	10-30*

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (j) of §1910.1200.
*CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First Aid Measures

Inhalation	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.
Skin contact	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
Ingestion	Rinse mouth. If ingestion of a large amount does occur, call a poison control center immediately.
Most important symptoms/effects, acute and delayed	Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. Take off all contaminated clothing immediately. Wash contaminated clothing before reuse.

5. Fire Fighting Measures

Suitable extinguishing media	Dry chemical. Alcohol foam. Carbon dioxide.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire-fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Flammable liquid and vapor.
Hazardous combustion products	May include and are not limited to: Oxides of carbon. Oxygen.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep out of low areas. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Avoid inhalation of vapors or mists. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop the flow of material, if this is without risk. Large Spills: Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
Environmental precautions	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

7. Handling and Storage

Precautions for safe handling	Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep cool. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid breathing mist or vapor. Avoid contact with eyes, skin and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure Controls/Personal Protection

Occupational exposure limits

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	984 mg/m ³ 400 ppm
	TWA	492 mg/m ³ 200 ppm

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm

Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	1230 mg/m ³ 500 ppm
	TWA	983 mg/m ³ 400 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Isopropanol (CAS 67-63-0)	PEL	980 mg/m ³ 400 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	1225 mg/m ³ 500 ppm
	TWA	980 mg/m ³ 400 ppm

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
------------	-------	-------------	----------	---------------

Isopropanol (CAS 67-63-0)	40 mg/L	Acetone	Urine	*
---------------------------	---------	---------	-------	---

* - For sampling details, please see the source document.

Appropriate engineering controls Not available.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Impervious gloves. Confirm with reputable supplier first.

Other Wear suitable protective clothing.

Respiratory protection Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).

Thermal hazards Not available.

General hygiene considerations When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and Chemical Properties

Appearance	Translucent
Physical state	Liquid.
Form	Liquid.
Color	Fluorescent Green
Odor	Not available.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	205 °F (96.11 °C)
Pour point	Not available.
Specific gravity	Not available.
Partition coefficient (n-octanol/water)	Not available.
Flash point	102.0 °F (38.9 °C) Tag Closed Cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	2
Relative density	0.98
Solubility(ies)	Complete
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.

10. Stability and Reactivity

Reactivity This product may react with strong oxidizing agents.

Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Chemical stability	Material is stable under normal conditions.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point.
Incompatible materials	Strong oxidizing agents. Acetyl chloride.
Hazardous decomposition products	May include and are not limited to: Oxides of carbon. Oxygen.

11. Toxicological Information

Routes of exposure	Inhalation. Ingestion. Skin contact. Eye contact.	
Information on likely routes of exposure		
Ingestion	May cause stomach distress, nausea or vomiting.	
Inhalation	Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Prolonged inhalation may be harmful.	
Skin contact	No adverse effects due to skin contact are expected.	
Eye contact	Causes serious eye irritation.	
Symptoms related to the physical, chemical and toxicological characteristics	Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.	
Information on toxicological effects		
Acute toxicity	Narcotic effects.	
Components	Species	Test Results
Isopropanol (CAS 67-63-0)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	12800 mg/kg, HSDB 16.4 ml/kg, 24 Hours, ECHA
<i>Inhalation</i>		
LC50	Rat	> 10000 ppm, 6 Hours, ECHA 16970 mg/l/4h, HMIRA
<i>Oral</i>		
LD50	Dog	4797 mg/kg, HSDB
	Mouse	3600 mg/kg, HSDB
	Rabbit	5030 mg/kg, HSDB 5 g/kg, HSDB
	Rat	5.8 g/kg, ECHA
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Exposure minutes	Not available.	
Erythema value	Not available.	
Oedema value	Not available.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Corneal opacity value	Not available.	
Iris lesion value	Not available.	
Conjunctival reddening value	Not available.	
Conjunctival oedema value	Not available.	
Recover days	Not available.	
Respiratory or skin sensitization		
Respiratory sensitization	Not available.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	This product is not considered to be a carcinogen by IARC, NTP, or OSHA.	

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Teratogenicity	Not available.
Specific target organ toxicity - single exposure	Narcotic effects.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not available.
Chronic effects	Prolonged inhalation may be harmful.

12. Ecological Information

Ecotoxicity	See below		
Ecotoxicological data			
Components	Species	Test Results	
Isopropanol (CAS 67-63-0)			
Algae	IC50	Algae	1000 mg/L, 72 Hours
Crustacea	EC50	Daphnia	13299 mg/L, 48 Hours
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	> 1400 mg/L, 96 hours
Persistence and degradability	No data is available on the degradability of this product.		
Bioaccumulative potential	No data available.		
Mobility in soil	No data available.		
Mobility in general	Not available.		
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		

13. Disposal Considerations

Disposal instructions	Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport Information

Transport of Dangerous Goods (TDG) Proof of Classification	Classification Method: Classified as per Part 2, Sections 2.1 – 2.8 of the Transportation of Dangerous Goods Regulations. If applicable, the technical name and the classification of the product will appear below.
---	--

U.S. Department of Transportation (DOT)

Basic shipping requirements:

UN number	UN1993
Proper shipping name	Flammable liquids, n.o.s
Technical name	Isopropanol
Hazard class	Limited Quantity - US
Packing group	III
Special provisions	B1, B52, IB3, T4, TP1, TP29
Packaging exceptions	<1.3 Gallons - Limited Quantity

Transportation of Dangerous Goods (TDG - Canada)

Basic shipping requirements:

UN number	UN1993
Proper shipping name	FLAMMABLE LIQUID, N.O.S.
Technical name	Isopropanol
Hazard class	Limited Quantity - Canada

Packing group III
Special provisions 16, 150
Packaging exceptions <5L - Limited Quantity

IATA/ICAO (Air)

Basic shipping requirements:

UN number UN1993
Proper shipping name Flammable liquid, n.o.s.
Technical name Isopropanol
Hazard class 3
Packing group III

IMDG (Marine Transport)

Basic shipping requirements:

UN number UN1993
Proper shipping name FLAMMABLE LIQUID, N.O.S.
Technical name Isopropanol
Hazard class 3
Packing group III

DOT; TDG



IATA; IMDG



15. Regulatory Information

Canadian federal regulations This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number

Isopropanol (CAS 67-63-0) 1 TONNES

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

WHMIS 2015 Exemptions Not applicable

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All chemicals used are on the TSCA inventory.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Isopropanol (CAS 67-63-0) Listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
 Delayed Hazard - No
 Fire Hazard - Yes
 Pressure Hazard - No
 Reactivity Hazard - No

SARA 302 Extremely hazardous substance No

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Isopropanol	67-63-0	10-30*

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

US state regulations

US - California Hazardous Substances (Director's): Listed substance

Isopropanol (CAS 67-63-0) Listed.

US - Illinois Chemical Safety Act: Listed substance

Isopropanol (CAS 67-63-0)

US - Louisiana Spill Reporting: Listed substance

Isopropanol (CAS 67-63-0) Listed.

US - Minnesota Haz Subs: Listed substance

Isopropanol (CAS 67-63-0) Listed.

US - New Jersey RTK - Substances: Listed substance

Isopropanol (CAS 67-63-0)

US - Texas Effects Screening Levels: Listed substance

Isopropanol (CAS 67-63-0) Listed.

US. Massachusetts RTK - Substance List

Isopropanol (CAS 67-63-0)

US. New Jersey Worker and Community Right-to-Know Act

Isopropanol (CAS 67-63-0)

US. Pennsylvania Worker and Community Right-to-Know Law

Isopropanol (CAS 67-63-0)

US. Rhode Island RTK

Isopropanol (CAS 67-63-0)

US. California Proposition 65

Not Listed.

Inventory status


Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other Information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	/ 1
FLAMMABILITY	2
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X



Disclaimer

Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date

12-August-2019

Version #

02

Effective date

23-August-2019

Prepared by

Nu-Calgon Technical Service Phone: (314) 469-7000