## QUALITY PRODUCTS FOR AIR CONDITIONING, REFRIGERATION & HEATING



## WHAT'S NEW!



#### **Gallo Gun (Available Spring 2020)**

The Gallo Gun is a lightweight portable tool designed to blow out condensate drain lines instantly. Simply insert a Gallo Gun CO<sub>2</sub> cartridge into the Gallo Gun and with a press of the trigger, oil-free, food-grade air instantly clears the line. **See more on page 15.** 



#### **Ice Guard Plus**

Ice Guard Plus contains advanced technology to dramatically reduce ice machine maintenance and cleaning. This technology utilizes the known properties of silver and copper, incorporated into a drop-in device, to control bacterial slime growth. The device is placed directly into the recirculating water sump, providing treatment of the machine in one easy step. **See more on page 34.** 



Thermo-Trap Putty is a reusable putty material that is referred to as a heat sink. When applied to the metal working surface, Thermo-Trap soaks up heat and reduces heat transfer to protect sensitive components.

See more on page 23.





#### **Complete Care Mini-Split Kit**

The Complete Care Mini-Split Kit contains everything you need to clean The coils on four mini-split units. The kit includes two packages of Gel Tabs Mini condensate pan treatment, two cans of Tri-Pow'r HD Aerosol coil cleaner, one Clean Guard maintenance bag and a reusable bucket. **See more on page 15.** 



#### **Quick Seal Repair Patch**

Quick Seal Repair Patch is a UV light activated fiberglass reinforced self-adhesive repair patch. The fiberglass reinforced repair patch is made of polyester/plastic and is designed for quick, in-the-field repairs.

See more on page 22.



#### Gel Tabs™ - Condensate Drain Pan Treatment

Formulated with a breakthrough technology for treating air conditioning drain pans and lines. Keeps the drain pan from clogging and eliminates foul and musty odors. New size designed for Mini-Splits! **See more on page 13.** 

| Table of Contents                   |       |  |  |  |  |  |
|-------------------------------------|-------|--|--|--|--|--|
| Total System Protection             | 1-3   |  |  |  |  |  |
| Coil Cleaners and Sprayers          | 4-10  |  |  |  |  |  |
| Indoor Air Quality                  | 11-15 |  |  |  |  |  |
| Gas Leak Detectors                  | 16    |  |  |  |  |  |
| Refrigeration Oil & Vacuum Pump Oil | 17-18 |  |  |  |  |  |
| Aerosol Products                    | 19-21 |  |  |  |  |  |
| Specialty Products                  | 22-24 |  |  |  |  |  |
| Insulation Products                 | 25    |  |  |  |  |  |
| Glycols                             | 26-27 |  |  |  |  |  |
| Closed Systems                      | 28    |  |  |  |  |  |
| Water Treatment & Plumbing Products | 29-33 |  |  |  |  |  |
| Water Filtration Maintenance        | 34    |  |  |  |  |  |
| Everpure®                           | 35-38 |  |  |  |  |  |
| Water Filtration                    | 39-40 |  |  |  |  |  |
| Training Classes                    | 41    |  |  |  |  |  |

#### THE ULTIMATE IN REFRIGERANT LEAK SEALANTS











#### **EasySeal® Ultimate**

The EasySeal® line has proven to be the number one trusted leak sealant brand for years, with millions of leaks sealed. Now Nu-Calgon has made EasySeal even better with EasySeal Ultimate – the strongest and fastest leak sealant on the market, now with the ability to treat systems up to 10 tons in one application. EasySeal Ultimate features Rapid Fusion Technology™ for a stronger bond and a new injector design for easier installation. The UV dye versions – now with brighter UV dye – allow you to see where larger leaks are with the use of a UV light.

| EasySeal Ultimate LS    | Systems 2-10 tons                              | 4050-08 |
|-------------------------|--|---------|
| EasySeal Ultimate LS/UV | Systems 2-7.5 tons (with UV dye)               | 4050-11 |
| EasySeal Ultimate SS    | Systems up to 2 tons                           | 4050-05 |
| EasySeal Ultimate SS/UV | Systems up to 2 tons (with UV dye)             | 4050-21 |
| LS Bulk 6-Pack          | Systems 2-10 tons                              | 4050-07 |
| LS/UV Bulk 6-Pack       | Systems 2-7.5 tons (with UV dye/UV flashlight) | 4050-12 |
| UV Leak Detection Kit   | UV flashlight and glasses                      | 4050-15 |











#### A/C EasySeal®

A/C EasySeal prevents and seals refrigerant leaks in residential and light commercial ACR systems. It is perfect for those hard-to-find and expensive-to-fix leaks and works with all refrigerants (except ammonia). It is easily installed with the reusable piercing valve and hose. A/C EasySeal circulates with the system's refrigerant, and if a leak should occur, it will quickly and permanently seal the leak and prevent the system from losing refrigerant and shutting down.

| A/C EasySeal                | Pressurized can - treats 1.5 to 5 ton systems                  | 4050-06 |
|-----------------------------|--|---------|
| A/C EasySeal-SS             | Pressurized can - treats fractional to 1.5 ton systems         | 4050-01 |
| "2+1" Display Pack          | 2 cans of A/C EasySeal and an A/C Piercing Valve and Hose      | 4050-02 |
| A/C EasySeal-XL             | Treats systems with refrigerant charge of 125 lbs. to 250 lbs. | 4050-10 |
| A/C Piercing Valve and Hose | Use with A/C EasySeal and A/C EasySeal-SS                      | 4051-99 |



Endorsed by York®, Goodman®, Nordyne®, Coleman®, and Daikin®







#### R<sub>X</sub>11-flush<sup>®</sup>

 $R_X$ 11-flush is a unique solvent engineered specifically for flushing refrigeration and air conditioning systems.  $R_X$ 11-flush is ozone-safe, non-toxic, and non-flammable. Its patented HFC-based solvent formulation is powerful enough to flush away sludge, carbon residues, oils, acids, water and other particulates.  $R_X$ 11-flush is ideal for system flushing after burnouts, during retrofits, and for flushing line sets for R-410A conversions.  $R_X$ 11-flush has been the industry's standard for over a decade, and contractors agree — it's the best flush for R-410A retrofits and after compressor burnouts.

| Rx11-flush Starter Kit | Contains a 1 lb. canister, Rx11-flush Gun and Hose, and Injection Valve | 4300-08 |
|------------------------|---|---------|
| 1 lb. canister         | Flushes 1-2 line sets   | 4300-09 |
| "2+1" Display Pack     | Contains one Injection Valve and two 2 lb. canisters                    | 4300-10 |
| 2 lb. canister         | Flushes up to 5 line sets   | 4300-11 |
| 13 lb. canister        | Recommended for up to 50 ton system or 30+ line sets                    | 4300-15 |
| 26 lb. canister        | Recommended for systems over 50 tons or 60+ line sets                   | 4300-26 |



#### R<sub>x</sub>11-flush® Liquid

 $R_X$ 11-flush Liquid is a unique solvent engineered specifically for flushing refrigeration and air conditioning systems. It remains a constant boiling solvent, and its stronger, faster-acting formula dissolves more oil, moisture, and contaminants than any other flush. It is ideal for line sets, burnouts, and other flushing requirements.

| 19.5 ounce can                | 4300-30 |
|-------------------------------|---------|
| Rx11-flush Liquid Starter Kit | 4300-38 |



TOTAL SYSTEM PROTECTION

#### R<sub>X</sub>11-flush® Accessories

The  $R_X11$ -flush product family also includes various support tools. This includes the Injection Valve for hooking up to a charging hose for flushing and the Flushing Tool for facilitating line set flushing. In addition, the  $R_X11$ -flush Gun with a built-in flushing attachment and the  $R_X11$ -flush Hose (24″) are available.

| Flushing Tool         | 4300-50 |
|-----------------------|---------|
| Rx11-flush Gun        | 4300-51 |
| Rx11-flush Hose (24") | 4300-52 |
| Injection Valve       | 4300-89 |

(Injection Valve fits Pneu-flush® and pressurized Rx-Acid Scavenger® as well)

#### **Total System Protection**



A/C Re-New is a highly formulated, OEM approved product that has established an outstanding track record enhancing the performance of air conditioning and refrigeration systems. A/C Re-New frees sticky valves, quiets noisy compressors, reduces energy consumption by lowering starting and running amps, and improves heat transfer in the evaporator and condenser. It's great for new systems as a preventative or to reinstate performance of older systems. It can also assist in oil return with R-22 replacement refrigerants. It's available in a quick, injectable treatment (using the Connect Injector Tool) or in a four-ounce can to be used with the A/C Re-New Injector Tool.

| 1 quart can               | 4057-54 |
|---------------------------|---------|
| 4 fluid ounce can         | 4057-55 |
| A/C Re-New Injector Tool  | 4057-99 |
| A/C Re-New Connect Inject | 4057-56 |
| Connect Injector Tool     | 4155-01 |



#### A/C ReStart™

A/C ReStart is a POE lubricant treatment designed specifically for R-22 retrofits. It eliminates oil change-out by boosting oil return. A/C ReStart also includes Rx-Acid Scavenger for addressing trace acids during retrofits. It's available in a quick, injectable treatment (using the Connect Injector Tool) or in a four-ounce can to be used with the A/C Re-New Injector Tool.

| 4 fluid ounce can          | 4060-55 |
|----------------------------|---------|
| A/C ReStart Connect Inject | 4060-56 |
| Connect Injector Tool      | 4155-01 |



#### Rx-Acid Scavenger®

The most effective way to neutralize or "scavenge" acid in refrigeration and air conditioning systems. Rx-Acid Scavenger is perfect for use after burnouts or during normal on-going system maintenance. In addition, Rx-Acid Scavenger can be used with all lubricants: mineral, alkylbenzene, and polyol ester. Now available in a pressurized can for easy injection into charged systems or hermetically sealed systems. Connect Inject version is a quick, injectable treatment that uses the Connect Injector Tool.

| 2 fluid ounce unpressurized bottle | 4301-02 |
|------------------------------------|---------|
| 3.8 ounce pressurized can          | 4301-05 |
| Injector Valve                     | 4300-89 |
| Rx-Acid Scavenger Connect Inject   | 4301-06 |
| Connect Injector Tool              | 4155-01 |

(Injection Valve fits R<sub>X</sub>11-flush® and Pneu-flush® as well)

#### Phase III<sup>®</sup> Refrigeration Oil Acid Test Kit

Formulated for use with POEs as well as mineral oils and alkylbenzene, Phase III is an inexpensive, disposable test kit that provides proof-positive that acid level in refrigeration oil is either safe or unsafe. Phase separation makes it easy to see change in color of acid indicator (even if a leak detection dye has been added to the oil). With just two bottles to use, it is simple, safe, accurate, and small enough that you can carry several in your tool box.

| 1 each | 4320-W8 |
|--------|---------|
|        |         |

Nu-Calgon Coil

Cleaners Found

Nu-Calgon Coil Cleaners Found on Pages 6-9



|                                  |                          |          | EQUIP    | MENT USEI  | D ON     |          |          |          |          |
|----------------------------------|--------------------------|----------|----------|------------|----------|----------|----------|----------|----------|
| Condenser Coils                  | •                        | •        | •        | •          | •        | •        | •        | •        | •        |
| Mini-Split Condenser Coils       |                          |          |          |            | •        | •        | •        | •        | •        |
| Small Condenser Coils            | •                        | •        | •        | •          | •        | •        | •        | •        | •        |
| Evaporator Coils                 |                          |          |          | •          | •        | •        | •        |          |          |
| Mini-Split Evaporator Coils      |                          |          |          |            | •        | •        | •        |          |          |
| Small Evaporator Coils           |                          |          |          | •          | •        | •        | •        |          |          |
| Microchannel Coils               |                          |          |          |            | •        | •        | •        | •        | •        |
| Electronic Air Filters           |                          |          |          |            |          |          | •        |          |          |
| Fan Blades,<br>Permanent Filters |                          |          |          | •          | •        | •        | •        | •        | •        |
|                                  |                          |          | FORMULA  | ATED TO F  | REMOVE   |          |          |          |          |
| Greasy Dirt & Oil                | •                        | •        | •        | •          | •        | •        | •        | •        | •        |
| Cooking Grease                   | •                        | •        | •        |            | •        |          | •        |          | •        |
| Lint, Dust, Dirt & Grime         | •                        | •        | •        | •          | •        | •        | •        | •        | •        |
| Tobacco Tars                     |                          |          |          |            |          |          | •        |          |          |
| Oxide (Corrosion) Deposits       | •                        | •        | •        | •          |          |          |          |          |          |
| Cottonwood/ Bugs                 | •                        | •        | •        | •          |          |          | •        |          |          |
|                                  |                          |          | FEATU    | RES & BENI | EFITS    |          |          |          |          |
| Product Type                     | Alkaline  Aerosol Liquid | Alkaline | Alkaline | Acidic     | Alkaline | Alkaline | Alkaline | Alkaline | Alkaline |
| Foaming                          | Aerosor Liquid           | •        | •        | •          |          |          |          |          |          |
| Brightening                      | • •                      | •        | •        | •          |          |          |          |          |          |
| Degreasing                       | • •                      | •        | •        | •          | •        | •        | •        | •        | •        |
| EPA Registered Disinfectant      |                          |          |          |            |          |          |          |          |          |
| No Rinse (Evaporators)           |                          |          |          |            | •*       | •*       | •*       |          |          |
| No Rinse (Condensers)            |                          |          |          |            |          |          |          |          | •        |
| Biodegradable                    | • •                      | •        | •        | •          | •        | •        | •        | •        | •        |
| USDA Authorized                  | • •                      |          |          |            |          | •        | •        |          |          |
| U.S. EPA's Safer Choice          |                          |          |          |            |          |          |          |          |          |
| NSF Registered                   | •                        | •        | •        |            | •        |          |          | •        |          |

| on Pages 6-9                     |               | times   | - 10+           | 0          | 0           |             |            |            |           |            |  |
|----------------------------------|---------------|---------|-----------------|------------|-------------|-------------|------------|------------|-----------|------------|--|
|                                  | Evap-Pow'r®-C | No R    | resh® †<br>inse | Cal-Green™ | Evap-Green™ | Green Clean | Evap-Foam® | Blackhawk® | Nu-Blast® | Cal-Blast® |  |
|                                  |               |         |                 | FOUIP      | MENT USEI   | OON         |            |            |           |            |  |
| Condenser Coils                  |               |         |                 | •          |             | •           |            | •          | •         | •          |  |
| Mini-Split Condenser Coils       |               |         |                 | •          |             | •           |            | •          | •         | •          |  |
| Small Condenser Coils            |               |         |                 | •          |             | •           |            | •          | •         | •          |  |
| Evaporator Coils                 | •             |         | •               |            | •           | •           | •          | •          |           |            |  |
| Mini-Split Evaporator Coils      | •             |         | •               |            | •           | •           | •          | •          |           |            |  |
| Small Evaporator Coils           | •             |         | •               |            | •           | •           | •          | •          |           |            |  |
| Microchannel Coils               | •             |         | •               | •          | •           | •           | •          | •          | •         | •          |  |
| Electronic Air Filters           |               |         |                 |            |             |             |            |            |           |            |  |
| Fan Blades,<br>Permanent Filters | •             |         |                 | •          | •           | •           | •          | •          | •         | •          |  |
| FORMULATED TO REMOVE             |               |         |                 |            |             |             |            |            |           |            |  |
| Greasy Dirt & Oil                | •             |         |                 | •          | •           | •           | •          | •          | •         | •          |  |
| Cooking Grease                   |               |         |                 |            |             |             |            | •          | •         | •          |  |
| Lint, Dust, Dirt & Grime         | •             | •       | •               | •          | •           | •           | •          | •          | •         | •          |  |
| Tobacco Tars                     |               |         |                 |            |             |             |            |            |           |            |  |
| Oxide (Corrosion) Deposits       |               |         |                 |            |             |             |            |            |           |            |  |
| Cottonwood/ Bugs                 |               |         |                 |            |             |             |            |            |           |            |  |
|                                  |               |         | _               | FEATUR     | RES & BEN   | EFITS       |            |            |           |            |  |
| Product Type                     | Alkaline      | Alka    |                 | Alkaline   | Alkaline    | Alkaline    | Alkaline   | Alkaline   | Solvent   | Alkaline   |  |
| Foaming                          |               | Aerosol | Liquid          |            |             |             | •          | •          |           |            |  |
| Brightening                      |               |         |                 |            |             |             |            |            |           |            |  |
| Degreasing                       |               |         |                 |            |             | •           |            | •          | •         | •          |  |
| EPA Registered Disinfectant      |               | •       | •               |            |             |             |            |            |           |            |  |
| No Rinse (Evaporators)           | •             | •       | •               |            | •           | •*          | •          | •          |           |            |  |
| No Rinse (Condensers)            |               |         |                 |            |             |             |            |            | •         | •          |  |
| Biodegradable                    | •             | •       | •               | •          | •           | •           | •          | •          |           |            |  |
| USDA Authorized                  | •             |         |                 |            |             |             |            |            |           |            |  |
| U.S. EPA's Safer Choice          |               |         |                 | •          | •           |             |            |            |           |            |  |
| NSF Registered                   |               |         |                 |            |             |             | •          | •          |           |            |  |

+ Product not registered for sale in Canada.

5

COIL CLEANER SELECTION GUIDE

<sup>\*</sup> Dilution ratios for no rinse applications: Tri-Pow'r HD = 10:1, Liquid CalClean = 10:1, Special HD CalClean = 40:1, Green Clean = 10:1





#### **Nu-Brite®**

Nu-Brite is the most effective coil cleaner available today. It foams, brightens, and cleans more effectively than acids, particularly in removing grease. Biodegradable. The liquid versions are USDA approved and NSF registered.

| 18 ounce can            | 4291-18  |       |
|-------------------------|----------|-------|
| 1 gallon bottle         | 4291-08  |       |
| 2.5 gallon pail         | 4291-05† | (NSF) |
| 55 gallon drum          | 4291-01  |       |
| 4x concentrate 1 quart* | 4291-90  |       |

<sup>\*</sup> Use with CleanConnect Sprayer (4773-0)



#### Foam-Brite®

The ultimate in foaming alkaline cleaners, Foam-Brite cleans and brightens while at the same time providing tremendous foaming to push dirt and grime out of the coil. Can easily be used in place of the more dangerous HF acid-based products. Biodegradable. NSF registered.

| 1 gallon bottle | 4178-08  |       |
|-----------------|----------|-------|
| 2.5 gallon pail | 4178-05† | (NSF) |
| 55 gallon drum  | 4178-01  |       |



#### **Alka-Brite® Plus**

A non-acid, alkaline based product for brightening and cleaning air-cooled condensers, Alka-Brite Plus contains the best available detergents to quickly penetrate and remove oxidation. Its foaming action helps to lift greasy soils out of the coil. Biodegradable. NSF registered.

| 1 gallon bottle         | 4120-08  |       |
|-------------------------|----------|-------|
| 2.5 gallon pail         | 4120-05† | NCT   |
| 55 gallon drum          | 4120-01  | (NSF) |
| 4x concentrate 1 quart* | 4120-90  |       |

<sup>\*</sup> Use with CleanConnect Sprayer (4773-0)



#### Cal-Brite® Plus

Cal-Brite Plus is a low pH cleaner developed for cleaning evaporator coils, air-cooled condensers, and other finned cooling and heating coils. Its versatility is based upon a synergistic acid formulation and other unique ingredients. It provides moderate foaming and brightening and is safe for use indoors as well as outdoors. It's particularly suitable when lime scale must be removed from outdoor coils.

| 1 gallon bottle | 4133-08 |
|-----------------|---------|
| 55 gallon drum  | 4133-01 |

†A 2.5 gallon pail wrench is also available. Part Number ZE64.



#### Tri-Pow'r® HD

Tri-Pow'r HD is an outstanding general purpose coil cleaner, providing detergency and degreasing as well as deodorizing capability. Its positive emulsion technology is very effective against oily grime as it converts the deposits into a more liquid form that can be easily rinsed. It is non-acid, non-toxic, and biodegradable. NSF registered. Also great for microchannel coils.

| 19 ounce can            | 4371-75          |       |
|-------------------------|------------------|-------|
| 1 gallon bottle         | 4371-88          | (NSF) |
| 2.5 gallon pail         | <b>4371-86</b> † |       |
| 55 gallon drum          | 4371-81          |       |
| 4x concentrate 1 quart* | 4371-90          |       |

<sup>\*</sup> Use with CleanConnect Sprayer (4773-0)



#### CalClean®

CalClean is an alkaline detergent formulated for cleaning evaporator coils, air-cooled condenser coils, metal filters, fan blades, and other surfaces soiled with grease, dust and dirt. Biodegradable. USDA approved. Also great for microchannel coils.

| 1 gallon bottle | 4135-08  |       |
|-----------------|----------|-------|
| 2.5 gallon pail | 4135-06† | (NSF) |
| 55 gallon drum  | 4135-01  |       |

#### Special HD CalClean®

The best non-foaming cleaner available, Special HD CalClean is specifically formulated to remove tobacco tars from electronic air cleaners as well as the most stubborn deposits from finned coils. USDA approved. Also great for microchannel coils.

| 1 gallon bottle | 4143-08  |
|-----------------|----------|
| 2.5 gallon pail | 4143-06† |
| 55 gallon drum  | 4143-01  |



#### **Evap Pow'r®-C**

A no-rinse product formulated for cleaning evaporator coils, Evap Pow'r-C is metal-safe, and it cleans and emulsifies even the most stubborn soils and deposits. Biodegradable. USDA approved. Also great for microchannel coils.

| 1 gallon bottle | 4168-08  |
|-----------------|----------|
| 2.5 gallon pail | 4168-05† |
| 55 gallon drum  | 4168-01  |

<sup>†</sup> A 2.5 gallon pail wrench is also available. Part Number ZE64.



#### TriClean 2x™

The new way to clean a condenser coil. Simply connect to hose, clean, and rinse. TriClean 2x is metal-safe, designed for rapid emulsion of soils from the coil. Restores efficiency and is ideal for painted fin and microchannel coils. Eliminates the need for a sprayer.

| quart sprayer with hose connector | 4372-24 | (NSF) |  |
|-----------------------------------|---------|-------|--|
|                                   |         |       |  |



#### Nu-Solve™ NR

Ready-to-use, no-rinse condenser coil cleaner for situations with limited water availability for rinsing. Nu-Solve NR is also for other applications where it is desirable to have less diluted cleaning solution on a commercial roof or when a solvent-based aerosol approach is not practical. It effectively emulsifies dirt and grime and provides a benefit of leaving a protective treatment on the aluminum for added corrosion protection, making the next cleaning easier. Nu-Solve NR can be applied with any of Nu-Calgon's poly sprayers or the Nu-Solve NR Sprayer.

| 1 gallon bottle     | 4295-08 |
|---------------------|---------|
| Nu-Solve NR Sprayer | 4775-0  |

**COIL CLEANERS** 





#### **Evap Foam No Rinse®**

Evap Foam No Rinse is a high-performing, heavy-duty detergent. It is formulated with special surfactants and alkaline cleaners that have been developed into a foaming, no-rinse product. Evap Foam is ideal for use on most coils, but it is particularly suited for use on cooling or evaporator coils. The aerosol can be sprayed either right side up or upside down. NSF registered. Can be used with Talon Flexible Aerosol Wand (4776-0) for hard to reach locations (see page 19).

| 18 ounce can | 4171-75 | NSI | $\left[ \cdot \right]$ |  |
|--------------|---------|-----|------------------------|--|
|              |         |     |                        |  |



#### **Evap-Fresh® No Rinse Evaporator Coil Cleaner & Disinfectant**†

Evap-Fresh is a ready-to-use, no-rinse cleaner and disinfectant for evaporator coils. It effectively cleans, as well as controls, mold and bacteria. This one-step no-rinse disinfectant cleaner is perfect for air conditioners, commercial air handling units, HVAC cooling coils, refrigeration equipment, and evaporator coils. EPA registered specifically for use on HVAC equipment. Aerosol can be used with Talon Flexible Aerosol Wand (4776-0) for hard to reach locations (see page 19).

| 18 ounce can    | 4166-75 |
|-----------------|---------|
| 1 gallon bottle | 4166-08 |



#### **Green Clean**

Green Clean is a pleasantly scented, all-purpose, environmentally friendly cleaner designed for the rapid removal of grease and other heavy soils on coils and other surfaces. It can be used right out of the bottle or diluted for milder jobs. Biodegradable. Also great for microchannel coils.

| 1 quart spray bottle | 4186-24 |
|----------------------|---------|
| 1 gallon bottle      | 4186-08 |
| 55 gallon drum       | 4186-01 |

The following products are part of Nu-Calgon's Environmentally Friendly Green Select line. These coil cleaners meet the U.S. EPA Safer Choice Program standards, making them a safer choice for the user and the environment.







#### **Cal-Green™ Condenser Cleaner**

Cal-Green is a plant-based, natural condenser cleaner that is powerful enough to remove dirt, grease, and grime. It meets the U.S. EPA Safer Choice Direct Release Program standards, making it a safer choice for the user and the environment. This non-foaming, non-toxic concentrate is perfect for cleaning residential or commercial systems and restores their efficiency while being environmentally responsible. Also OEM approved for microchannel coils.

| 1 gallon bottle         | 4190-08 |
|-------------------------|---------|
| 4x concentrate 1 quart* | 4190-90 |
| 55 gallon drum          | 4190-01 |

<sup>\*</sup> Use with CleanConnect Sprayer (4773-0)



#### **Evap-Green™ Evaporator Cleaner**

Evap-Green is a no-rinse product that is perfect for numerous heating and air conditioning applications, such as evaporator coils, roof top units, window units, metal filters, fan blades, and more. Evap-Green meets the U.S. EPA Safer Choice Direct Release Program standards, making it a safer choice for the user and the environment. It is also biodegradable and will not harm plants, animals, or aquatic life. Metal-safe — meets OEM guidelines for all aluminum coils, including microchannel types.

| 1 gallon bottle | 4191-08 |
|-----------------|---------|
| 55 gallon drum  | 4191-01 |

+ Product not registered for sale in Canada.

#### **Coil Cleaners**



#### **Nu-Blast®**

Nu-Blast is a no-rinse condenser coil cleaner in a convenient aerosol package. Double action of high-pressure blast and solvent cleaning restores design efficiency of condenser coils. It is non-flammable and non-conductive. No rinse required cleaning solvent evaporates completely. Use with adequate ventilation. Not for sale in California.



#### **Blackhawk®**

Blackhawk is an expanding foam coil cleaner formulated to deeply penetrate the coil. It liquefies to quickly remove grease, grime, or oily soils from deep within the coil. Blackhawk's formulation is safe and problem-free for cleaning evaporator or condenser coils in an occupied building; produces no objectional fumes. It is particularly effective on coils on refrigerators, coolers, and freezers located in restaurants and other commercial establishments. NSF registered. Can be used with Talon Flexible Aerosol Wand (4776-0) for hard to reach locations (see page 19).

| 18 ounce can | 4127-75 | NSt. |  |
|--------------|---------|------|--|
|              |         |      |  |



#### Cal-Blast®

Cal-Blast is a no-rinse condenser cleaner that will powerfully separate undesirable materials from the surface, offering maximum cleaning of finned coils. It's a high-performance aerosol with excellent solvency and blasting spray. Not for sale in California.

| 20 ounce can | 4132-20 |
|--------------|---------|
|              |         |

#### **Coil Protectants**



#### DuraCoil™

DuraCoil is a long-lasting coating for coils and surfaces in corrosive environments. It uses a durable, OEM-approved Heresite® coating. DuraCoil has a fast, air-dry formula that bonds to all metals and causes negligible heat transfer loss across the coil. Great for repairing an OEM-approved coil coating that has been compromised while in service!

| 11 ounce can    | 4083-90 |
|-----------------|---------|
| i i dulice call | 4003-30 |



#### Cal-Shield®

Cal-Shield is a synergistic fluoro-additive liquid formulation pretreatment of the coil for special duty circumstances. It's designed for application on air-cooled condensers, evaporator coils, and other finned heating and cooling coils. Cal-Shield will shield and protect the coil from adverse conditions.

| 1 quart spray bottle | 4148-32 |
|----------------------|---------|
| 1 gallon bottle      | 4148-08 |





Coil Gun is a "hose-end" sprayer that features five different mix ratio settings designed for coil cleaners. Utilizes a 2 quart capacity bottle and includes a foam wand as well as "quick disconnect" capability. The Coil Gun Probe accessory has a 90° direction of spray that allows cleaning from inside the coil. It also provides easy access in tough-to-reach locations.

| Coil Gun       | 4774-0 |
|----------------|--------|
| Coil Gun Probe | 4774-1 |

4770-2



#### **Coil Mate™ Coil Cleaning Hose**

Durable 5/8 inch diameter reinforced hose with Flex-Guard protection. The 50-foot hose is equipped with solid brass wrench fittings. The Coil Mate is a necessity when using the popular Coil Gun® or rinsing an air-cooled coil with water after using a Nu-Calgon coil cleaner.

| Coil Mate Hose             | 61231 |
|----------------------------|-------|
| Hot Water Hose             | 61238 |
| Plastic Pistol Grip Nozzle | 61241 |





#### **Turbo Tank Rinsing Sprayer**

The Turbo Tank is a battery-operated, portable sprayer designed for use with water to rinse cleaning solutions off of HVAC coils. The sprayer is ideally suited for rinsing wall mini-splits, ceiling cassette units and coils in remote areas. Designed for use only with clean water, the sprayer includes a heavy-duty rechargeable battery, battery charger, spray gun, shoulder strap, two spray nozzles and an eight-inch, 90-degree spray wand.

| Turbo Tank Sprayer             | 4778-0  |  |
|--------------------------------|---------|--|
| Optional 39-inch Spray Wand    | 4778-11 |  |
| Optional AC/DC Power Converter | 4778-12 |  |
| Optional Coil Gun Connector    | 4778-26 |  |

|           | POLY SPRAYERS         |                                       |           |                                  |         |
|-----------|-----------------------|---------------------------------------|-----------|----------------------------------|---------|
| Model     |                       | Construction                          | Capacity  | Features                         | Part #  |
| No. 50P   |                       | High-density translucent polyethylene | 3 pints   | Plastic adjustable nozzle        | 4770-0  |
|           | No. 100P              | High-density translucent polyethylene | 1 gallon  | Brass wand & adjustable nozzle   | 4770-2  |
|           | No. 200P              | High-density translucent polyethylene | 2 gallons | Brass wand & adjustable nozzle   | 4771-2  |
| No. 220CP |                       | High-density translucent polyethylene | 2 gallons | Plastic wand & adjustable nozzle | 4771-3  |
|           | No. 300P              | High-density translucent polyethylene | 3 gallons | Brass wand & adjustable nozzle   | 4772-0  |
|           | Multi-purpose Sprayer | Plastic bottle with trigger sprayer   | 24 ounces | Bottle marked for dilutions      | 4768-W3 |





#### Breathe cleaner, fresher air!

With the technology installed in over 100,000 applications worldwide, iWave is a complete line of bi-polar, high-output ion generators designed specifically for treating air in air conditioning systems. As the air flows past the iWave, positive and negative ions actively purify the supply



air, killing mold, bacteria, and viruses in the coil and living space. The ionization process also reduces allergens, smoke, and static electricity, as well as controls odors (cooking, pet, VOCs) and other particles (no more sunbeams) in the air without creating ozone or any harmful byproducts. Easily installs between air filter and cooling coil to treat the indoor coil; as an alternative, the iWave can be installed in supply air. UL and cUL approved. Includes three-year limited warranty. \* Visit iwaveair.com to learn more.

#### iWave®-R Residential Air Cleaner


- Patent-pending self-cleaning design, no maintenance needed
- For duct systems up to 6 tons (2400 CFM)
- Universal voltage 24VAC to 240VAC
- Universal mounting
- Programmable cleaning cycle with integral alarm contact
- No replacement parts needed

| 1 each 4900-20 | 1 each | 4900-20 |
|----------------|--------|---------|
|----------------|--------|---------|

#### iWave®-C Commercial Air Cleaner

- Patent-pending self-cleaning design, no maintenance needed
- Duct-mount install for systems up to 12 tons (4800 CFM)
- Waterproof housing for installation inside or outside
- Universal voltage 24VAC to 240VAC
- Programmable cleaning cycle with integral alarm contact





#### iWave®-M Mini-Flexible Air Purifier for Ductless Systems

- Versatile ion needles mounted in a flexible bar circuit
- For HVAC cooling coils up to 36" wide
- For ductless systems (mini-split, PTAC) and ice machines
- Chemical and temperature resistant, durable for long service life
- Voltage input 110VAC to 240VAC

| 1 each | 4900-35 |
|--------|---------|
|        |         |

#### **iWave®-F Flexible Air Cleaner**

- Versatile ion needles mounted in a flexible bar circuit
- For HVAC cooling coils up to 48" wide
- For ductless systems (mini-split, PTAC), duct systems and ice machines
- Durable bar is chemical and temperature resistant
- Voltage input 110VAC to 240VAC

| 1 each | 4900-30 |
|--------|---------|
|--------|---------|

#### iWave®-V Residential Air Cleaner

- Low maintenance air purifier
- For systems up to 6 tons (2400 CFM)
- Universal mounting with integrated
- magnets
- Small compact design with no replacement parts
- Voltage input 24VAC



1 each 4900-40

4770-0

<sup>\*</sup> For a valid warranty claim within three years, proof of purchase and proof of installation by a licensed HVAC or electrical contractor must be provided. See full warranty for complete details.

12













#### **The Original ClenAir™ Odor Neutralizer**

ClenAir's unique odor neutralizing formula removes odors quickly and permanently. It is a true odor eliminator, not a mask. Originally designed for use in central air systems, on fire and flood restoration jobs and in sewage facilities, ClenAir is a professional product, yet it leaves no lingering antiseptic or perfume smell. It is great for odors caused by fuel oil, smoke, pets, mold and mildew, cigarette and cigar smoke, decay, cleaning solvents, and even skunks. ClenAir has three different scents: Original, CherryAir, and OrangeAir. The scents come in multiple sizes for multiple applications.

| Original                | Nu-Calgon | ClenAir |
|-------------------------|-----------|---------|
| Mini Tub                | 61000     | CA1500M |
| 1/2 lb. Tub display box | 61001     | 1500D   |
| 1/2 lb. Tub             | 61002     | 1500    |
| 1 lb. Tub               | 61003     | 1501    |
| 3 lb. Tub               | 61004     | 1503    |

| Original                       | Nu-Calgon | ClenAir |
|--------------------------------|-----------|---------|
| 10 lb. Tub                     | 61005     | 1510    |
| 30 lb. Tub                     | 61006     | 1530    |
| Wall Unit (White)              | 61007     | 1300    |
| Gel Brick for Wall Unit (1lb.) | 61008     | 1401    |

| CherryAir               | Nu-Calgon | ClenAir |
|-------------------------|-----------|---------|
| Mini Tub                | 61018     | CA1800M |
| 1/2 lb. Tub display box | 61010     | 1800D   |
| 1 lb. Tub               | 61011     | 1801    |
|                         |           |         |
| OrangeAir               | Nu-Calgon | ClanAir |

| 3 lb. Tub  | 61013     | 1803    |
|------------|-----------|---------|
| 10 lb. Tub | 61015     | 1810    |
| 30 lb. Tub | 61017     | 1830    |
| OrangeAir  | Nu-Calgon | ClenAir |

| OrangeAir               | Nu-Calgon | ClenAir |
|-------------------------|-----------|---------|
| Mini Tub                | 61028     | CA1300M |
| 1/2 lb. Tub display box | 61020     | CA1300D |
| 1 lb. Tub               | 61021     | CA1301  |

| OrangeAir  | Nu-Calgon | ClenAir |
|------------|-----------|---------|
| 3 lb. Tub  | 61023     | CA1303  |
| 10 lb. Tub | 61025     | CA1310  |
| 30 lb. Tub | 61027     | CA1330  |

#### **HVAC Odor Block®**

ClenAir HVAC Odor Block is not a perfume mask or cover-up. The unique ClenAir formula molecularly reacts with the airborne odor-causing compounds and eliminates them and other indoor pollutants, leaving clean, fresh air behind. The HVAC Odor Block makes it easy to remove odors and improve the indoor air quality in the entire home or building by treating the air through the HVAC system. Use in A/C units, furnaces, rooftop units, fan coil units, and air handlers. Part numbers 61060 and 61061 last up to 3 months. The HVAC Odor Block XL (61070) lasts up to 6 months.

|                                | Nu-Calgon Number | ClenAir Number |
|--------------------------------|------------------|----------------|
| Residential HVAC Odor Block    | 61060            | 1502           |
| Residential HVAC Odor Block XL | 61070            |                |
| Commercial HVAC Odor Block     | 61061            | CA1015         |

The ClenAir MiniFresh eliminates odors caused by mold, mildew, bacteria, pets, smoke, water damage, fire damage, paints, chemicals, stale air, and more! The unique ClenAir formula molecularly reacts with the airborne odor-causing compounds and eliminates them and other indoor pollutants leaving clean, fresh, air behind. Use in mini split, PTAC, or other ductless systems. The MiniFresh can be installed on the return louvers of indoor units. It will be out of view and will work quietly to eliminate odors. MiniFresh mini split odor eliminator treats up to one 12,000 BTU indoor unit for 3 months.

| MiniFresh   | 61065 |  |
|-------------|-------|--|
| MILLI ICOLI | 01005 |  |

#### **ClenAir Liquid Formula**

ClenAir Liquid is a fast acting deodorizing product. It eliminates odors via an oxidation process while leaving a fresh scent. Applications include HVACR equipment, such as evaporator coils, duct work, condensate pans, refrigeration cases, reach-ins, and walk-in boxes. It can also be poured down drains, garbage disposals, and in trash cans. Spray in restrooms, locker rooms, and on fouled carpeting and upholstery. Used by hospitals, nursing homes, and HVACR technicians.

|                         | Nu-Calgon | ClenAir |
|-------------------------|-----------|---------|
| Unscented Spray 16 oz.  | 61030     | 1600D   |
| Unscented Liquid 1 gal. | 61031     | 1610    |
| Citrus Spray 16 oz.     | 61033     | 1700D   |

|                         | Nu-Calgon | ClenAir |
|-------------------------|-----------|---------|
| Citrus Liquid 1 gal     | 61035     | 1710    |
| CherryAir Spray 16 oz.  | 61037     | 1900D   |
| CherryAir Liquid 1 gal. | 61038     | 1910    |

#### **Indoor Air Quality**



#### **Gel Tabs™ - Condensate Drain Pan Treatment**

Formulated with a breakthrough technology for treating air conditioning drain pans and lines. Keeps the drain pan from clogging and eliminates foul and musty odors. When activated by condensation, the tablet will turn to gel and lock into place. Dissolves continuously and completely for up to three months. Stack together to increase duration. New Gel Tabs Mini is designed to fit in mini-split pans.

| 3 ton tab (12 in tube)           | 4185-03 |
|----------------------------------|---------|
| 3 ton Contractor Pack (80 count) | 4185-80 |
| 3 ton tab bulk (200)             | 4185-04 |
| 5 ton tab (6 in tube)            | 4185-05 |
| 5 ton Contractor Pack (40 count) | 4185-40 |

| 5 ton tab bulk (100) | 4185-06 |
|----------------------|---------|
| 15 ton tab (1 each)  | 4185-15 |
| 20 ton tab (1 each)  | 4185-20 |
| Gel Tabs Mini        | 4185-95 |

#### PanPads<sup>†</sup>

PanPads are formulated to eliminate the build-up of bacteria and slime growth in air conditioning and refrigeration condensate drain pans. In laboratory tests, they have been proven effective against a wide spectrum of harmful bacteria, including Legionella. The product is EPA registered for this application. NSF registered.

| 5 (up to 5 tons)      | 4295-34 | NCE  |
|-----------------------|---------|------|
| 5 Slim (up to 5 tons) | 4295-36 | INOL |

| 15 (up to 15 tons) | 4296-24 | NCE  |
|--------------------|---------|------|
| 45 (up to 45 tons) | 4296-45 | INOL |



#### Pan-Treat®

Pan-Treat condensate tablets control odors and prevent overflows caused by plugged condensate drain lines. They can also be used in humidifiers. They are very easy to use, as well as non-corrosive, non-toxic, and biodegradable.

| 1.55 (255 (455)) | 1 bottle (200 tablets) | 4296-60 |
|------------------|------------------------|---------|
|------------------|------------------------|---------|

#### **PurCool® Green Strips and Tablet**

Visit us at www.nucalgon.com or call 1-800-554-5499

PurCool Strips/Tablets prevent sludge, odors, and overflow of condensate pans. Time release formula adheres to pan and fully dissolves over time. PurCool Green Strips/Tablets use plantbased suspending and dispersing action to keep drain pans clean and free flowing. Products are available for commercial, residential, and mini split applications. Sizes are based on system tonnage, with each strip/tablet lasting up to six months. Biodegradable and environmentally friendly. Will not harm aquatic life.



| e.i.a.y                               |                  |                |
|---------------------------------------|------------------|----------------|
|                                       | Nu-Calgon Number | ClenAir Number |
| PurCool Green Mini Strip              | 61044            | PCG5MS         |
| PurCool Green Commercial Strip 10 ton | 61045            | PCG10T         |
| PurCool Green Commercial Strip 30 ton | 61046            | PCG30T         |
| PurCool Green 3 ton tablet            | 61048            |                |
| PurCool Green 3 ton bulk (200)        | 61049            |                |
| PurCool Green 5 ton tablet            | 61051            | PCG5T          |
| PurCool Green 5 ton bulk (100)        | 61052            | PCG5T-100      |

† Product not registered for sale in Canada.

QUALITY

AIR

INDOOR

# Pan Strips Pan Strips

#### **PurCool® Strips**

PurCool Strips keep A/C and refrigeration condensate drain pans clean and free flowing. Use PurCool Strips to prevent condensate drain clogs, costly overflows, and corrosion. Just place them anywhere in the drain pan where the PurCool Strip will contact the condensate water and enjoy up to six months of economical protection. PurCool Strips will adhere to the drain pan and will not float or move. Dissolves completely, leaving no residue. Safe for metal and plastic drain pans.

|                        | Nu-Calgon | ClenAir   |
|------------------------|-----------|-----------|
| 3 ton strip            | 61043     | 1903D     |
| 3 ton strip bulk (100) | 61047     | 1903D-100 |
| 5 ton strip            | 61042     | 2001D     |

|              | Nu-Calgon | ClenAir |
|--------------|-----------|---------|
| 10 ton strip | 61041     | 2003D   |
| 30 ton strip | 61040     | 2009    |



#### **PurCool® Tablets**

PurCool Tablets utilize a powerful formulation to keep condensate drain pans clean and free flowing. Use PurCool Tablets to remove sludge and slime in A/C condensate pans to prevent costly water damage caused by overflows. They will control clogs, build-up, odors, and corrosion in drain pans, condensate pumps, and humidifiers.

|                        | Nu-Calgon Number | ClenAir Number |
|------------------------|------------------|----------------|
| 1 bottle (200 tablets) | 61053            | PC200          |



#### **HVAC Carbon Block® In-Duct Air Purification System**

HVAC Carbon Block is an add-on carbon purifier for all HVAC systems. Improves indoor air quality by removing odors, indoor air pollutants, and VOCs. Treats up to 10 tons for up to nine months.

|                   | Nu-Calgon Number | ClenAir Number |
|-------------------|------------------|----------------|
| HVAC Carbon Block | 61062            | CACB10         |



#### **Humidifier Panel™ Replacements**

ClenAir Universal Humidifier Panels provide optimum moisture output, performance, and durability. They replace Aprilaire, Honeywell, Carrier, Bryant, Lennox, ICP, and others. Ultra Upgrade Humidifier Panels' material retains water, increasing moisture output and reducing water waste by up to 50%. They replace Aprilaire, Honeywell, Carrier, Bryant, Lennox, ICP, and others.

|   | Nu-Calgon Number | ClenAir Number |
|---|------------------|----------------|
| Universal Humidifier Panel - #10 size     | 61250            | CA10           |
| Universal Humidifier Panel - #12 size     | 61251            | CA12           |
| Universal Humidifier Panel - #35 size     | 61252            | CA35           |
| Ultra Upgrade Humidifier Panel - #10 size | 61254            | CA10UP         |



#### **Spacegard® Filter Media Replacements**

These Merv 11 filter media are direct replacements for the Aprilaire Spacegard 201 and 401. Merv 11 media removes pollen, allergens, smoke, dust, dust mites, bacteria, spores, and pet dander. The large filter surface area provides for low resistance and longer filter life - more than 6 months!

| J |   | Nu-Calgon Number |       |  |
|---|---|------------------|-------|--|
|   | Replacement for Aprilaire Spacegard 201 | 61256            | CA201 |  |
|   | Replacement for Aprilaire Spacegard 401 | 61257            | CA401 |  |

 ${\it *Aprilaire and Spacegard are registered trademarks of Research Products Corporation}$ 

#### **Indoor Air Quality**



#### **Gallo Gun (Available Spring 2020)**

The Gallo Gun is a lightweight portable tool designed to blow out condensate drain lines instantly. Simply insert a Gallo Gun  $\mathrm{CO}_2$  cartridge into the Gallo Gun and with a press of the trigger, oil-free, food-grade air instantly clears the line. Revolutionary housing fits the standard 16g cartridge or the larger 20g cartridge for 25% more clearing power! Each unit comes equipped with a tapered fitting to work on 3/8in. – 3/4in. drain openings. The extremely light and flexible hose assembly maneuvers through tight openings, cabinets and coils. Cartridges are environmentally safe and recyclable.

| Gallo Gun (includes 20G cartridge) | 4179-01 |
|------------------------------------|---------|
| 20G Cartridges (12 pack)           | 4179-20 |
| 16G Cartridges (12 pack)           | 4179-16 |



#### **Complete Care Mini-Split Kit**

The Complete Care Mini-Split Kit contains everything you need to clean the coils on four mini-split units. The kit includes two packages of Gel Tabs Mini condensate pan treatment, two cans of Tri-Pow'r HD Aerosol coil cleaner, one Clean Guard maintenance bag and a reusable bucket.

| 1 each | 4151-18 |
|--------|---------|
|--------|---------|



#### **Clean Guard™ Mini-Split Bag**

Clean Guard is a professional mini-split maintenance bag that protects walls and flooring from cleaning solutions when cleaning the indoor coil. It installs in seconds, with an elastic collar that snaps around the unit. Product offers 360-degree coverage with an eight-foot drain line. Heavy duty plastic can be reused on repeated maintenance calls.

| Clean Guard – units up to 12,000 BTU               | 4150-01 |
|--|---------|
| Clean Guard XL – units 18,000 to 36,000 BTU        | 4150-02 |
| <b>Clean Guard CC Commercial Ceiling Cassettes</b> | 4150-03 |



#### Bio-Fresh® cd<sup>†</sup>

A ready-to-use bacteriostatic, fungistatic, and deodorizer based upon chlorine dioxide technology. Inhibits the growth of bacteria, mold, mildew, fungi, and yeasts in IAQ applications, and it may be applied to occupied spaces. EPA registered for use in HVACR ventilating equipment, including coils, condensate pans, filters, and duct-work. Easily applied by spraying, brushing, sponging, or wiping. Use Bio-Fresh Fogger for spraying in duct work and large areas.

| 1 quart spray bottle | 4126-34 |
|----------------------|---------|
| 1 gallon bottle      | 4126-38 |
| Bio-Fresh Fogger     | 4693-0  |



#### A/C Drain Sucker®

Visit us at www.nucalgon.com or call 1-800-554-5499

A/C condensate drain pan overflow is caused by slime and sludge that builds up and clogs the drain line. The A/C Drain Sucker quickly removes the clog and the excess water, resolving the overflow problem. The kit includes a PurCool® Green 3 ton tablet to provide months of preventive treatment and free flowing drains, as well as all fittings and hoses for suction or pressure applications.

|                         | Nu-Calgon Number | ClenAir Number |
|-------------------------|------------------|----------------|
| A/C Drain Sucker kit    | 61308            | CADS1          |
| PurCool Green 3 ton tab | 61048            |                |

+ Product not registered for sale in Canada.

INDOOR AIR QUALITY





#### Cal-Blue® Plus Gas Leak Detector

Cal-Blue Plus is a complete gas leak detector with freeze protection to 5°F. Its high viscosity formula enables it to remain in contact with the applied surface for an extended period of time, allowing it to detect the smallest of leaks. The longest lasting bubbles in the industry! It is also non-corrosive to metal, and it will not affect ultraviolet or black lights. Now available in a non-aerosol pressurized container that can be sprayed at any angle! NSF registered.

| 6 ounce bottle with dauber | 4182-53 |
|----------------------------|---------|
| 7 ounce pressurized spray  | 4182-35 |
| 1 quart spray bottle       | 4182-24 |
| 1 gallon bottle            | 4182-08 |





The same high quality formulation as regular Cal-Blue Plus, but it has added freeze protection to -20°F. It is the ideal detector for geographical areas that may experience very cold temperatures. The longest lasting bubbles in the industry! NSF registered.

| 1 quart spray bottle | 4183-24 | NCE |
|----------------------|---------|-----|
| 1 gallon bottle      | 4183-08 | NOL |





#### **Gas Leak Detector**

The original industry leak detector. A high viscosity liquid that forms bubbles when daubed on a gas leak. Non-corrosive, non-staining, and harmless to skin. Detects any type of gas leak, such as air, compressed air, carbon dioxide, nitrogen, natural gas, and refrigerant gases. Freeze protection to -20°F. Six ounce plastic bottles have dauber in cap. USDA approved.

| 6 ounce bottle with dauber | 4180-53 |
|----------------------------|---------|
|----------------------------|---------|

#### **Fluorescent Gas Leak Detector**

A fluorescent formulation that provides improved visibility and long lasting bubbles. It is non-corrosive to metals and is freeze protected to 5°F. Suitable for high and low temperature applications. Can be used for most refrigerants, natural gas and oxygen systems. USDA approved.

| 8 ounce bottle with dauber | 4184-53 |
|----------------------------|---------|
| 1 quart spray bottle       | 4184-24 |
| 1 gallon bottle            | 4184-08 |

#### **Refrigeration Oils**



#### **Emkarate® POE Lubricants**

The Emkarate family of polyol ester refrigeration lubricants are designed specifically for use with HFC refrigerants. They are available in a range of viscosities. They have excellent thermal and chemical stability, and they are compatible with a wide range of elastomers, polymeric materials, and other materials of construction. Fully miscible and compatible with mineral oils and alkylbenzene lubricants, as well as with CFCs, HCFCs, and HFCs.

| Emkarate RL | Viscosity | 1 Quart | 1 Gallon | 5 Gallon | 53 Gallon |
|-------------|-----------|---------|----------|----------|-----------|
| 22H         | 100 SUS   |         | 4313-46  |          |           |
| 32H         | 150 SUS   | 4314-44 | 4314-46  | 4314-45  | 4314-41   |
| 32HB        | 150 SUS   |         |          | 4314-62  |           |
| 32-3MAF     | 150 SUS   | 4314-64 | 4314-66  | 4314-65  | 4314-67   |
| 46H         | 200 SUS   |         | 4315-46  |          | 4315-41   |
| 68H         | 300 SUS   | 4316-44 | 4316-46  | 4316-45  | 4316-41   |
| 68HB        | 300 SUS   |         | 4316-86  | 4316-85  |           |
| 68HP        | 300 SUS   |         | 4316-76  |          | 4316-71   |
| 85HB        | 425 SUS   |         | 4316-91  |          |           |
| 100E        | 500 SUS   |         | 4317-66  |          | 4317-61   |
| 100H        | 500 SUS   |         | 4317-46  |          |           |
| 170H        | 850 SUS   |         | 4318-26  | 4318-25  | 4318-21   |
| 220H+       | 1100 SUS  |         | 4318-66  | 4318-65  | 4318-61   |
| 220XL       | 1100 SUS  |         |          | 4318-75  |           |



#### C-3s, C-4s, C-5s Mineral Oil

These are mineral naphthenic lubricants manufactured by Calumet Lubricant Company and available in three viscosities. They are specifically designed for today's high performance air conditioning and refrigeration compressors using CFC and HCFC refrigerants. These compressors run at higher speeds and generate higher temperatures, and as a result, they require better lubrication. Use of these oils will ensure continued efficient operation.

| Nu-Calgon | Viscosity | 1 Gallon | 5 Gallon | 55 Gallon |
|-----------|-----------|----------|----------|-----------|
| C-3s      | 150 SUS   | 4303-07  | 4303-05  | 4303-01   |
| C-4s      | 300 SUS   | 4304-07  | 4304-05  | 4304-01   |
| C-5s      | 500 SUS   | 4305-07  |          | 4305-01   |



#### **Zerol® Alkylbenzene Refrigeration Oil**

Zerol Refrigeration Oil is recommended for use in all refrigeration and air conditioning applications using CFC and HCFC refrigerants. It is highly recommended by refrigerant and compressor manufacturers for use with R-22 and other HCFC blends such as R-409A as it provides many distinct advantages: excellent miscibility, excellent thermal stability, and low temperature performance compatibility with mineral oils. It is the oil of choice for R-22 and R-502.

| Zerol | Viscosity | 1 Gallon | 55 Gallon |
|-------|-----------|----------|-----------|
| 150   | 150 SUS   | 4310-07  | 4310-01   |
| 200TD | 200 SUS   | 4308-07  | 4308-01   |
| 300   | 300 SUS   | 4311-07  | 4311-01   |

GAS LEAK DETECTORS

18





#### **Idemitsu Polyvinyl Ether Lubricant**

PVE lubricants provide for increased stability and lubrication. They do not hydrolyze in the presence of moisture, a very important feature in HVÁCR applications. Additionally, they are compatible with other refrigeration oils and process fluids. PVE lubricants also exhibit compatibility and performance with frequently used anti-wear additives.

| Idemitsu | Viscosity  | 1 Quart |
|----------|------------|---------|
| FVC32D   | 150 32 SUS | 4319-14 |
| FVC68D   | 300 68 SUS | 4319-24 |



#### **PAG Oil**

Polyalkylene glycol (PAG) oil is a synthetic compressor lubricant used by OEMs for R-134a refrigerant and other specialty applications. It has outstanding lubricity and biodegradable properties, and recently has been FDA approved for use with equipment that may come in contact with food.

| Zerol RFL-68EP 5 gallon pail |
|------------------------------|
|------------------------------|



#### **Vacuum Pump Oil**

Nu-Calgon's Vacuum Pump Oil is a quality, high-grade lubricant that performs at the deepest vacuum. It has a very low vapor pressure, and it has excellent lubricity for complete surface protection. It contains no additives or detergents.

| 1 pint bottle   | 4383-34 |
|-----------------|---------|
| 1 quart bottle  | 4383-24 |
| 1 gallon bottle | 4383-07 |

#### **Refrigeration Oil Products**



#### **Refrigeration Oil Charging Pump**

An oil pump for charging refrigeration oil into a system, even while it's running. This pump can be used for 1 gallon, 2.5 gallon, and 5 gallon containers. Incorporates an automatic bleed valve that keeps pressure equalized inside the container and includes a tapered rubber adapter that fits all container openings without the need for additional adaptors.

| 0 |
|---|
| ĺ |



#### **Total Lube Refrigeration Oil Test Kit**

Have a professional lab analyze the oil to help detect potential problems such as metal wear or burnouts. The analysis will provide information on the oil's moisture, total acid number, viscosity, color, and spectrochemical analysis on 20 plus metals and compounds. Help prevent potential downtime, burnouts, and costly oil changes by incorporating regular testing of the refrigeration oil.

|  | 1 each |  | 4996-0 |  |
|--|--------|--|--------|--|
|--|--------|--|--------|--|



#### **Oil Refractometer**

The Oil Refractometer is a precision optical instrument that allows for the rapid and accurate determination of the refractive index of oil solutions. It will specifically assist in determining the percent of residual oil remaining in a refrigeration system when converting it to a new refrigeration oil. Such retrofits require converting the mineral oil to a polyol ester (POE) or polyalkylene glycol (PAG), an alkylbenzene lubricant (Zerol®) to a POE, or a mineral oil to an alkylbenzene.

| 1 each 4815-0 |
|---------------|
|---------------|



#### **CanVerter®**

Canverter is a hand-held pump used to remove or add oil to hermetic compressors. Easy to use; each stroke pumps 1 ounce of oil.

| 1 each | 4814-0 |
|--------|--------|
|        | l .    |

#### **Aerosol Coil Cleaners**



#### **Blackhawk®**

Blackhawk is an expanding foam coil cleaner formulated to deeply penetrate the coil. It liquefies to quickly remove grease, grime, or oily soils from deep within the coil. Blackhawk's formulation is safe and problem-free for cleaning evaporator or condenser coils in an occupied building; produces no objectional fumes. It is particularly effective on coils on refrigerators, coolers, and freezers located in restaurants and other commercial establishments. NSF registered. Can be used with the Talon Flexible Aerosol Wand (4776-0) for hard to reach locations.

| ounce can | 4127-75 | (NSF |
|-----------|---------|------|
|           |         |      |

#### Tri-Pow'r® HD

Tri-Pow'r HD aerosol provides a powerful foaming spray to assist in lifting debris off of coils. It's a detergent, degreaser and deodorizer - all in one convenient spray. Suitable for any coil design, including microchannel. Tri-Pow'r HD can be used for evaporator "no-rinse" applications where ample condensate will self-rinse the coil.

| ounce can | 4371-75 |
|-----------|---------|
|-----------|---------|





#### Nu-Brite®

Nu-Brite is a very effective degreaser and cleaner on condenser coils. Its high foaming characteristic will help push soil deposits out of the coil, leaving it clean and bright. With proper ventilation, it can also be used as a kitchen degreaser by emulsifying stubborn, resistive grease deposits found on coils located in kitchens. Product should be used where adequate rinsing is possible.

| 18 ounce can 429 | 1-18 |
|------------------|------|
|------------------|------|



#### **Evap Foam No Rinse®**

Evap Foam No Rinse is a high-performing, heavy-duty detergent. It is formulated with special surfactants and alkaline cleaners that have been developed into a foaming, no-rinse product. Evap Foam is ideal for use on most coils, but it is particularly suited for use on cooling or evaporator coils. The aerosol can be sprayed either right side up or upside down. NSF registered. Can be used with the Talon Flexible Aerosol Wand (4776-0) for hard to reach locations.

| 18 ounce can | 4171-75 |
|--------------|---------|
|              |         |



#### Cal-Blast®

Cal-Blast is a no-rinse condenser cleaner that will powerfully separate undesirable materials from the surface, offering maximum cleaning of finned coils. It's a high-performance aerosol with excellent solvency and blasting spray.

| 20 ounce can | 4132-20 |
|--------------|---------|
|              |         |

Not available for sale in California



#### Nu-Blast®

A no-rinse condenser coil cleaner in a convenient aerosol package. Double action of high-pressure blast and solvent cleaning restores design efficiency of condenser coils. It is non-flammable and nonconductive. No rinse required — cleaning solvent evaporates completely. Use with adequate ventilation.

| ounce can | 4290-75 |
|-----------|---------|
|-----------|---------|

Not available for sale in California



#### Evap-Fresh® No Rinse†

Evap-Fresh is a ready-to-use, no-rinse cleaner and disinfectant for evaporator coils. It effectively cleans, as well as controls, mold and bacteria. This onestep no-rinse disinfectant cleaner is perfect for air conditioners, commercial air handling units, HVAC cooling coils, refrigeration equipment, and evaporator coils. EPA registered specifically for use on HVAC equipment. Can be used with the Talon Flexible Aerosol Wand (4776-0) for hard to reach locations.

| 10           | 4466 75 |
|--------------|---------|
| 18 ounce can | 4166-75 |



#### **Talon**

Talon is a flexible aerosol wand for Nu-Calgon's Evap Foam No Rinse, Blackhawk, Evap-Fresh No Rinse or PenetrateHD products. Provides focused cleaner spray or penetrant in tough-to-reach locations. The Talon is highly flexible, retains shape memory, and provides 27 inches of added length to an aerosol canister for navigating in tight quarters inside the equipment. The reusable Talon is a must-have service tool!

| 1 each | 4776-0 |
|--------|--------|
|--------|--------|

+ Product not registered for sale in Canada.

19



## A/C SHINE


#### A/C Shine®

#### **Superior Cleaner/Protectant**

A/C Shine is specially formulated to clean and protect the painted metal surfaces of outdoor A/C condensing units. It sprays on and wipes off quickly and easily without water. For use on all outdoor unit painted surfaces.

|        | Nu-Calgon | ClenAir |
|--------|-----------|---------|
| 12 oz. | 61118     | ACS12   |

#### **DuraCoil**



11 ounce can

4083-90



#### CleanVu Glass Cleaner

CleanVu is a highly effective aerosol cleaner for glass and all hard, non-porous surfaces. Its fast-drying, non-filming formula cleans dirt and grime, providing streak-free shine.

#### **Stainless Steel Cleaner**

Nu-Calgon's aerosol Stainless Steel Cleaner removes light soil and restores shine to stainless steel, chrome and hard, washable surfaces.

| CleanVu 19 ounce can         | 4081-85 |
|------------------------------|---------|
| Stainless Steel 15 ounce can | 4084-75 |

Zinc Rich is highly resistant to nearly all forms

of corrosion. Perfect for repairing factory

galvanized material damaged in shipment,

welding, assembly, etc. Its 95% pure zinc film

fuses itself to iron, steel, or aluminum. Blends

well with hot-dip coating. Meets or exceeds

military specifications MIL-P- 26915A, MIL-

T- 26433, MIL-P- 21035, MIL-P-46105 and the

4087-03

**Zinc Rich Cold Galvanizing** 

## Pipe-Dri

#### Pipe-Dri®

Pipe-Dri aerosol insulation provides a moisture barrier to stop sweating and dripping on refrigeration lines, air conditioning lines, and other cold surfaces. Quickly adheres and dries to a hard waterproof coating. Pipe-Dri makes it possible to insulate hard-to-reach areas.

Protects seasonally operated pumps against

corrosion during shutdowns by "winterizing"

them. When corrosion occurs in close-tolerance

areas, it can cause the impeller to stick or bind. It

is safe for all types of water pumps and requires

4299-T8

18 ounce can 4297-75

**Pump Protector** 

10 ounce can

no special rinsing at start-up.

Not available for sale in California



**Degreasing Solvent EF** 

Preece Test.

13 ounce can

A degreasing solvent, specially formulated for cleaning and degreasing equipment where washing or flushing is not possible. Simply spray on and wipe off. Penetrates quick and deep, loosening and liquefying heavy greases and tar. Non-corrosive and non-staining with a dielectric strength over 26,000 volts.

| 14 ounce can       | 4083-75 |
|--------------------|---------|
| 14 ounce can - LV* | 4083-83 |
|                    |         |

\*LV = Low VOC for California Utah and New Hampshire

#### **Aerosol Specialty Products**

# Pan-Spray

#### **Pan-Spray®**

Pan-Spray is an effective, easy-to-use waterproof rubberized coating that won't chip, flake, or peel. It's ideal for sealing out rust and corrosion as well as repairing leaky condensate pans, cooling towers, swamp coolers, roofing, gutters, and down spouts. Pan Spray is the perfect solution for emergency and permanent repair.

| 16 ounce can - White | 4296-50 |
|----------------------|---------|
| 16 ounce can - Black | 4296-51 |



#### Nu-Kill® Max Strike Wasp and Hornet Killer†

A "quick-kill" spray formulation EPA registered to instantly and effectively kill wasps, hornets, yellow jackets and scorpions, from distances up to 20 feet. Nu-Kill also kills with residual action as wasps and hornets return to a treated nest. The formula is safe in and around electrical equipment, having a dielectric strength of 57,200 volts.

| 13.5 ounce can | 4292-75 |
|----------------|---------|



Clen Air,

#### PenetrateHD® Super Penetrating Lubricant

PenetrateHD loosens rusted and frozen metal parts. Frees stuck fan blades, blower shafts, pulleys, rusted nuts and bolts, and any frozen, rusted, or seized metal part. Unique low surface tension formula penetrates into the smallest spaces and breaks and dissolves the bonds of rust and corrosion. Lubricates, protects metals and displaces water. Dielectric strength 40,000 volts. Can be used with the Talon Flexible Aerosol Wand (4776-0) for hard to reach locations.

| 12 ounce can       | 61105 |
|--------------------|-------|
| 17 ounce can       | 61106 |
| 12 ounce can - LV* | 61107 |
| 17 ounce can - LV* | 61108 |

\* LV = Low VOC for California



#### **Electrical Contact Cleaner**

Cleans and protects electrical contacts from corrosion. Safe on most plastics. Quickly removes greases, dust, and oxidation, restoring and maintaining precision and efficiency to the instrument and component. Includes extension tube for accuracy. Dielectric strength over 25,000 volts. USDA approved.

| 11 ounce can       | 4082-03 |
|--------------------|---------|
| 14 once can - LV * | 4082-04 |

\* LV = Low VOC for California and Canada



#### Food-Grade Silicone

Food-Grade Silicone sprays a perfect non-stick surface on ice machine surfaces, vending machines, coin slots, slicing machines, dairy machinery, and other food processing and packaging equipment. An excellent lubricant that prevents binding and sticking. Contains ingredients approved by the FDA for food contact use. USDA approved.

| 11 ounce can | 4084-03 |
|--------------|---------|
|              |         |



#### V-Belt Dressing

V-Belt Dressing is specially formulated to penetrate and extend modern V-Belt life. It is particularly effective in maintaining V-Belt efficiency and performance under today's increasing performance requirements. It keeps belts pliable, prevents slippage, and does away with squealing and chattering. Also good for leather, rubber, canvas and other fabric belts, flat or round. USDA approved.

| 11 ounce can | 4086-03 |
|--------------|---------|
|--------------|---------|

#### **Aerosol Adhesives**



#### **Spray-n-Bond**<sup>™</sup>

Spray-n-Bond is a wide web spray adhesive formulated specifically for insulation and duct liner applications. Ideal for porous surfaces, it is waterproof, flexible, transparent, and non-staining. Formulated with the environment in mind, it contains no chlorinated solvents or ozone depleters. Will work with cardboard, most plastics and cloth. Cleans easily with degreasing solvent.

| 12 ounce can     | 4369-75 |
|------------------|---------|
| 12 ounce can-LV* | 4369-85 |
|                  |         |

\* LV = Low VOC for California



#### **Spray Adhesive**

Spray Adhesive is a fast-drying, all-purpose product that provides a strong, water-resistant, flexible bond. It is translucent and does not penetrate or soak material causing bleed-through. Spray Adhesive is excellent for labeling, bonding, splicing and sealing paper, cardboard, cloth, rubber, styrofoam, canvas, leather, wood, and most plastics.

| 12 ounce can | 4080-04 |
|--------------|---------|
|              |         |

† Product not registered for sale in Canada.



Visit us at www.nucalgon.com or call 1-800-554-5499

# Quick Seal Mepair Patch Quick Seal Repair Patch is a UV light activated fiberglass reinforced self-adhesive repair patch. The fiberglass reinforced repair patch is made of polyester/plastic and is designed for quick, in-the-field repairs. It can be used on both cold or hot water as well as HVAC/R and plumbing applications, and bonds to all types of pipes. 3"x 6" Patch 4299-25 6"x 9" Patch 4299-26 9"x 12" Patch 4299-27



#### Quick Seal™ Pipe Repair

A permanent knitted fiberglass impregnated tape that is designed for quick, in-the-field repair of leaks for all types of pipes. It can be used on both cold or hot water, as well as refrigeration, plumbing, industrial, commercial, and residential applications. It is safe for potable water and is UL listed. ANSI/NSF Standard 61.

| 2" x 4' wrap  | 4299-10 |
|---------------|---------|
| 4" x 12' wrap | 4299-11 |



#### **Great Wipes**

Great Wipes Industrial Strength Hand Towels are waterless wipes made specifically for the air conditioning, refrigeration, and plumbing service technician. Each premoistened, heavy duty towel has strong pumice scrubbing power that conveniently cleans anywhere and anytime.

| 75 count canister | 4185-75 | (NSF |   |
|-------------------|---------|------|---|
|                   |         |      | _ |



#### Scrubs-In-A-Bucket® HVAC80

The original Scrubs — disposable, pumice-performance waterless hand cleaner towels that effectively and quickly clean hands on a wide variety of industrial soils and greases. Each self-dispensing portable canister contains perforated disposable heavy-duty towels and are pre-moistened with the famous Scrubs cleaning formulation. Effective yet gentle to the skin. Use anywhere, anyplace, anytime.

| 30 count canister | 4366-24 | NCE   |
|-------------------|---------|-------|
| 80 count canister | 4366-87 | (NSF) |

#### **Specialty Products**





#### Thermo-Trap® Gel

Thermo-Trap Spray gel is designed to form a protective barrier to keep flames and heat from damaging areas beyond direct work surfaces during brazing or soldering. It will protect drywall, wiring, joists, and surrounding areas that a flame could also come in contact with. Cleans up easily with no residue.

| 1 quart spray bottle       | 4371-32 |
|----------------------------|---------|
| 4 fluid ounce spray bottle | 4371-53 |



#### Thermo-Trap® Paste

Thermo-Trap is the industry's original heat absorbing paste designed to isolate heat encountered in soldering, welding, and brazing, thereby preventing damage to nearby heat sensitive controls or fittings. USDA approved. Biodegradable.

| 11 ounce tube | 4371-36 |
|---------------|---------|
|---------------|---------|



#### Pneu-flush®

A flushing and cleaning system specifically designed for pneumatic control air lines. It utilizes DuPont® Vertrel® XM, a premier ozone-safe HFC cleaning solvent. Pneu-Flush works quickly and easily to clean and purge the compressed air lines in HVAC control and other pneumatic systems.

| 2 lb. canister  | 4298-01 |
|-----------------|---------|
| Injection Valve | 4300-89 |

(Injection Valve fits  $R_X$ 11-flush\* and Pressurized Rx-Acid Scavenger\* as well)

SPECIALTY PRODUCTS



#### **Grez-Off® Heavy Duty Degreaser**

Grez-Off works hard so you don't have to. This heavy-duty answer to heavy-duty grease and grime leaves engines, machinery, asphalt, garage floors and more whistle clean. Biodegradable, non-flammable formula hits hard and fast with less impact on user and environment.

|              | Nu-Calgon Number | ClenAir Number |
|--------------|------------------|----------------|
| 1 gallon     | 61116            | 22701          |
| 32 oz. spray | 61117            | 23732          |



#### **Spray Nine® Cleaner & Disinfectant**

Spray Nine is a tough task cleaner and broad spectrum disinfectant. EPA-registered disinfectant kills harmful germs like HIV-1, Influenza, H1N1, Staphylococcus Aureus, Salmonella Choleraesuis and E. Coli in 45 seconds. Also helps prevent cross contamination. Authorized by USDA for use in federally inspected meat and poultry plants with a C-1 rating.

|              | Nu-Calgon Number | Clen Air Number |
|--------------|------------------|-----------------|
| 1 gallon     | 61110            | 26801           |
| 32 oz. spray | 61113            | 26832           |

#### **Other Specialty Products**



#### Elite® Performance Windshield Washer Fluid -20°

Elite Performance Windshield Washer fluid is independently tested to provide freeze protection to -20°F. Don't take chances with generic washer products; only Elite Performance offers certified protection.

|          | Nu-Calgon Number | ClenAir Number |
|----------|------------------|----------------|
| 1 gallon | 61115            | CAWW1G         |



#### ClenHands: Orange Smoothie™, Orange Crush™ and Cherry Crush™

Premium antimicrobial hand cleaners that quickly dissolve dirt, grease, fuel oil, pipe dope, resin, ink, paint, glue, rubber gasket and tile cements, and many other hard-to-remove soils. ClenHands Orange Smoothie is a smooth non-pumice formula. ClenHands Orange Crush is enhanced with fine-ground American pumice. ClenHands Cherry Crush is a cherry-scented antimicrobial hand cleaner with pumice. For use with or without water.

|                            |          | Nu-Calgon Number | ClenAir Number |
|----------------------------|----------|------------------|----------------|
| Orange Crush with Pumice   | 1 gallon | 61201            | 2201           |
| Orange Crush with Pumice   | 15 oz.   | 61203            | 2215           |
| Orange Smoothie Non Pumice | 15 oz.   | 61202            | 2202           |
| Cherry Crush with Pumice   | 15 oz.   | 61204            | 2315           |
| ClenHands Super Gel        | 11 oz.   | 61205            | 2414           |



#### **Smoke Pens**

Smoke Pens are excellent for observing ventilation, air balancing, smoke detectors, drafts, leakage, and air flow. Smoke tests will effectively and inexpensively reveal leaks in heating and air conditioning duct work, furnaces, fire boxes, exhaust fans, and smoke detectors.

|                          | Nu-Calgon Number | ClenAir Number |
|--------------------------|------------------|----------------|
| Smoke Pen with 6 wicks   | 61305            | CASP1          |
| Refill Package - 6 wicks | 61306            | CASP1RW        |





#### Perma-Wrap™ Foam Insulation Tape

Perma-Wrap is formulated from the highest quality elastomeric thermal insulation material. Its closed cell construction seals out air and moisture, slowing down heat transfer, and can be used on hot or cold water pipes, chilled water, and refrigerant lines to prevent sweating and condensation. Service temps as low as -40°F with a high continuous temperature of 160°F and a high intermittent temperature of 220°F.

| 2" x 1/8" x 30' roll                        | 4218-W3 |
|---|---------|
| 2" x 1/8" x 30' roll -<br>dispenser package | 4218-12 |



#### | Cork Tape

Cork Tape is formulated and manufactured as an insulating material for preventing sweating and condensation on refrigerant lines, cold pipes, and other commercial refrigeration and A/C systems. Serves as an excellent insulator on hot pipes, and can also be used as a gasketing material, a sound-deadening material, and for wrapping valves, tees, and fittings. Service at temps as low as -30°F, as high as 200°F and won't sag up to 350°F.

| 2″ x | 1/8 | x 30° | roll | 4217-W3 |
|------|-----|-------|------|---------|
|      |     |       |      |         |



#### Foam-Tite®

Foam-Tite is an economically priced tape formulated from quality thermal insulation material. With closed cell construction, it can be used on cold water pipes and chilled water and refrigerant lines to prevent sweating and condensation. Can also be used on hot water lines for better insulation against heat loss. Service temperatures of -15°F to 160°F.

| 2 X 1/8 X 30 POII   42 19-1 | 2" x 1/8" x 30' roll | 4219-12 |
|-----------------------------|----------------------|---------|
|-----------------------------|----------------------|---------|



#### Cork-Tite®

Cork-Tite is an economically priced tape used to insulate cold pipes and stop condensation problems. Ideal for preventing heat loss in hot pipes, and used as an effective sound dampening material. Also sticks to dry metals and seals tightly without drying, while staying flexible within the service temperatures of -5°F to 200°F.

| 2″ x | 1/8 | x 30 | ′ roll | 4217-1 |
|------|-----|------|--------|--------|
|      |     |      |        |        |



#### **Foam Tape PE**

Foam-Tape PE is an insulation tape with closed cell construction, providing an economical way to prevent sweating or condensation on air conditioning, refrigeration, chilled water, or other cold lines. Also used on hot water lines for insulation against heat loss, with service temperatures of -70°F to 175°F.

| 2" x 1       | /8" x 30' roll | 4219-20 |
|--------------|----------------|---------|
| <b>4 A</b> I | O X SU IUII    | 4213-20 |



#### Thumb-Tite®

Thumb-Tite is formulated and manufactured for use in many sealing, insulating, and general indoor/outdoor maintenance applications. Excellent adhesion capability and is non-staining, non-hardening, and unaffected by wide variations in temperature - an excellent thumbing grade. Each box contains two 1-pound bars. Service temperatures of -20°F to 350°F.

| 2 lb. box | 4216-92  |
|-----------|----------|
| Z ID. DUX | 42 IU-22 |



#### Nu-Foam®

Nu-Foam is double expansion polyurethane foam with all-direction dispersing. Used as a sealant and insulating product on openings created for refrigeration, air conditioning and heating tubes or pipes, duct joints, and other areas where unwanted air penetration might occur. Contains no CFCs or HCFCs, and is fire retardant and UL listed.

| 20 ounce can 4293-75 | 12 ounce can | 4293-04 |
|----------------------|--------------|---------|
|                      | 20 ounce can | 4293-75 |



#### **Sealing and Caulking Cords**

Sealing and Caulking Cords are nonstaining sealers formulated to be water-resistant, dust-resistant, and white in color. They securely adhere to most surfaces and provide excellent insulation value. They are available in 3/8" pre-shaped extruded cords, with serrated release paper. Used indoors and outdoors, it stays flexible at -20°F and non-sagging at 350°F.

| 3/8" x 25' roll | 4216-27 |
|-----------------|---------|
|-----------------|---------|

**INSULATION PRODUCTS** 

## Freez Kontr

#### Freez-Kontr'l®

Freez-Kontr'l 35

Freez-Kontr'l is an expanded family of heat transfer fluids (anti-freeze) based upon non-toxic propylene glycol. All products are fully formulated to provide optimum freeze protection, as well as corrosion protection in chilled water, hydronic, and other closed systems. Safe to use where contact with potable water is possible. GRAS certified.

Freez-Kontr'l provides greater than -60°F freeze protection and greater than -100°F burst protection

Freez-Kontr'l 95/5 — a fully concentrated (~100%), inhibited propylene glycol product

 formulated with 35% propylene glycol for use as a secondary coolant in supermarket rack applications

Freez-Kontr'l FG — non-dyed, fully concentrate glycol ideally suitable for use in food and beverage equipment or other HVAC applications where a

NSF listed HT-1 formulated propylene glycol-based product is required

Freez-Kontr'l HD

a heavy-duty 70% propylene glycol-based heat transfer fluid formulated for hydronic applications where its multi-component inhibitor formulation provides better

service life

| Freez-Kontr'l          | 1 gallon bottle | 4188-07       |
|------------------------|-----------------|---------------|
|                        | 5 gallon pail   | 4188-05       |
|                        | 55 gallon drum  | 4188-02       |
| Freez-Kontr'l 95/5     | 5 gallon pail   | 4188-06       |
|                        | 55 gallon drum  | 4188-03       |
| Freez-Kontr'l 35       | 5 gallon pail   | 4188-16       |
|                        | 55 gallon drum  | 4188-35       |
| Freez-Kontr'l FG Clear | 5 gallon pail   | 4188-11 (NSF) |
|                        | 55 gallon drum  | 4188-14 NSF   |
| Freez-Kontr'l HD       | 5 gallon pail   | 4188-12 NSF   |
|                        | 55 gallon drum  | 4188-13       |



#### **Burst-Kontr'l® AP-100**

Burst-Kontr'l is a specially formulated propylene glycol heat transfer solution for use in boilers having aluminum heat exchangers. It has corrosion inhibitors to protect aluminum, copper, solder, brass, and steel. Provides burst protection to -100°F and freeze protection to -60°F.

| gallon | pail | 4187-15 |
|--------|------|---------|
| gailon | pali | 4187-13 |



#### **Total Glycol Test Kit**

Nu-Calgon's Total Glycol Antifreeze/Heat Transfer Analysis Program is integral to a comprehensive maintenance schedule with the use of Nu-Calgon's glycol products. The test kit includes a sampling bottle to capture glycol from the system and an analytical request form to be completed with the sample submittal. The analysis program provides a detailed report and recommendations to assist in making informed, proactive decisions to manage the system's health and the customer's bottom line.

| 1 each | 4997-0 |
|--------|--------|
| i each | 4997-0 |

#### **Ethylene Glycol**



#### Freez-Therm®

Freez-Therm is an inhibited heat transfer fluid and anti-freeze based upon ethylene glycol. It can be used in chilled water, hydronic, and other closed systems for both freeze point suppression and corrosion inhibition. An uninhibited version is also available in drums on special order.

| 1 gallon bottle | 4189-07 |
|-----------------|---------|
| 5 gallon pail   | 4189-05 |
| 55 gallon drum  | 4189-01 |

#### Glycol Tools and Equipment



#### **Glycol Refractometer**

An accurate and economical tool for ensuring proper levels of glycol treatment in HVAC fluid systems. Removes guess work and prevents wasteful over-treatment. It has metal body with cushioned eyepiece, focus adjustment, and a rubber hand grip. A calibration screwdriver, calibration fluid, a plastic pipette, optical cleaning cloth, and a rugged carrying case are included.

|        | Nu-Calgon Number | ClenAir Number |
|--------|------------------|----------------|
| 1 each | 61301            | GLY32          |



#### **Glycol/Oil Transfer Pump**

Heavy-duty pump designed to transfer Freez-Kontr'l®, Freez-Therm®, or oil products (up to 1000 sus) from Nu-Calgon supplied 55 gallon drums to their application.

| 1 each 4817-0 | ) |
|---------------|---|
|---------------|---|

#### **Water Test Kits**

#### **Bacteria Test Kit**

Kit contains 10 agar paddle tests that are used to monitor bacterial contamination in cooling tower and evaporative condenser water. Test can be performed in a lab or on site. Each side of the paddle is coated with TTC Agar, material that supports growth of most common bacteria. Regular testing will detect and show when bacteria counts are rising.

| 1 each | 4802-0 |
|--------|--------|
|        |        |

#### **Bromine/Chlorine Test Kit**

Kit measures free and combined halogen (chlorine, bromine), and it should be used to support treatment with Bromicide Tablets. Residual can be expressed as 0.2 ppm or 0.5 ppm of free halogens. Dropper technique is used.

| 1 each | 4803-0 |  |
|--------|--------|--|
|        |        |  |

#### **Complete Test Kit**

The complete test kit for cooling water and boiler water application testing. In addition to pH, this kit also provides tests for obtaining alkalinity, nitrite, hardness, sulfite, and chloride levels.

#### **Nitrite Test Kit**

Used for testing treatment residual of Ty-Ion B20 and Ty-Ion B14A. It is a cerric ammonium nitrate (can) titration method, and it can be used in systems containing glycol. Each drop equals 40 ppm of nitrite.

| 1 each | 4797-0 |
|--------|--------|
| i each | 4/9/-0 |

#### No. 89A Test Kit

No. 89A Test Kit contains tests for determining hardness, pH, chloride and alkalinity, as well as treatment residual tests for Ty-Ion C70, Cal-Treat 233, No. 340 Liquid Scale Inhibitor, and Ty-Ion B20.

| 2 |
|---|
| 2 |

#### **Organic Phosphonate Test Kit**

Used to determine the treatment residual of No. 340 Liquid Scale Inhibitor, Ty-Ion C70, and Cal-Treat 233.

| 1 each | 4804-0 |  |
|--------|--------|--|
|        |        |  |



#### Ty-lon® B20

Ty-lon B20 is a liquid nitrite-borax corrosion inhibitor and dispersant for closed recirculating systems. It combines corrosion inhibitors, a unique copolymer dispersant, and a color indicator to facilitate leak detection, into a complete treatment for hot and chilled water closed systems containing ferrous and non-ferrous metal components.

| 5 gallon pail | 7537-0  |
|---------------|---------|
| o gallon pall | /55/-03 |



#### Ty-lon® B14A

Ty-Ion B14A is an all-in-one boiler treatment product that controls scale, corrosion, and condensate line corrosion in low pressure, low make-up steam heating boilers where 90% or more of the condensate is returned. It is chromate-free and contains a color indicator for visual determination of treatment residual. Its balanced formulation provides an energyefficient way of heating.

| 5 gallon pail | 7519-05 |
|---------------|---------|
|---------------|---------|



#### **System Cleaner**

System Cleaner is a liquid, heavy-duty industrial alkaline cleaner specifically formulated to emulsify and clean equipment surfaces and pipe fouled by cutting oils, grease, lubricants, corrosion products, and other debris.

| 5 gallon pail | 4370-08 |
|---------------|---------|
|---------------|---------|

#### **Other Water Treatment Products**



#### No. 215 and No. 1075 Drip Feeders

Used for feeding No. 340 Liquid Scale Inhibitor, Cal-Treat 233, Ty-Ion C70 and No. 85 Algaecide. Calibrated at the factory to ensure accurate feeding. Provides the benefits of continuous treatment for small systems without the high cost usually associated with automatic feeding equipment.

| No. 215 Drip Feeder  | 4669-W3 |
|----------------------|---------|
| No. 1075 Drip Feeder | 4670-W3 |



#### No. 20L and No. 100L Feeders

Steel tanks suitable for pressures up to 150 psi and temperatures up to 212°F. Uses 3/4 inch FNPT connections for installing on bypass to any size line. Use No. 20L Feeder for initial charges up to 20 pounds (or 2 gallons). Use No. 100L Feeder for initial charges up to 100 pounds (or 10 gallons). Inlet/outlet strainers not included.

| No. 20L Feeder  | 4628-0 |
|-----------------|--------|
| No. 100L Feeder | 4650-0 |

#### Scale Removal



Working

Neutralized

### Strength

#### Competitive Product with **Dangerous Foam**

Nu-Calgon Low-Foaming Liquid Scale Dissolver



#### **Low-Foaming Performance**

To demonstrate its greater low-foam property, Liquid Scale Dissolver was added to a beaker containing lime scale. A leading competitive liquid product was added to another beaker containing an equal amount of lime scale. See the difference! When cleaning towers and evaporator condensers, low-foam is the preferred approach as high foam is dangerous to both personnel and surroundings.

#### **Liquid Scale Dissolver**

Liquid Scale Dissolver is a hydrochloric (muriatic) acid formulated to remove calcium scales from cooling towers and other water-cooled equipment. It contains low-foaming corrosion inhibitors and a built-in pH color indicator to let you know when the acid has been neutralized. pH test paper is also included. USDA approved.

| 1 gallon bottle | 4330-08 |
|-----------------|---------|
| 5 gallon pail   | 4330-05 |
| 55 gallon drum  | 4330-01 |



#### **Eco-Lyme®**

Eco-Lyme is a new chemistry for the HVACR market that provides a unique blend of performance with a desired eco-profile. The product is specially formulated to achieve descaling behavior of competing hydrochloric acid-based chemistry descalers. However, the active ingredient is substantially safer on equipment metals. Eco-Lyme is ideal for stainless steel construction to eliminate potential issues of localized corrosion/pitting caused by repeated use of hydrochloric acid. Eco-Lyme is odorless, making it safer to use in the field. NSF registered.

| 1 gallon bottle | 4167-08 |       |
|-----------------|---------|-------|
| 5 gallon pail   | 4167-05 | (NSF) |
| 55 gallon drum  | 4167-01 |       |



#### Season Start® "Imperial Grade" Scale Remover

Season Start is a powdered sulfamic acid formulation that contains the best inhibitors available for protecting all metals, including galvanized metal. It is the best and the safest dry acid cleaner available. It contains a built-in pH color indicator to let you know when the acid solution has been neutralized, as well as wetting and anti-foaming agents. USDA approved.

| 10 lb. container | 4360-88 |
|------------------|---------|
| 50 lb. pail      | 4360-84 |

| Initial Dosage Recommendation |                        |            |              |
|-------------------------------|------------------------|------------|--------------|
| Tons of Horsepower            | Liquid Scale Dissolver | Eco-Lyme   | Season Start |
| 10                            | 2 gallons              | 4 gallons  | 10 lbs.      |
| 30                            | 5 gallons              | 10 gallons | 30 lbs.      |
| 50                            | 10 gallons             | 20 gallons | 50 lbs.      |
| 90                            | 15 gallons             | 30 gallons | 75 lbs.      |



#### **Vital-Flo® Tankless Water Heater Descaler Kit**

The Vital-Flo Tankless Water Heater Descaler Kit is a complete service tool for descaling tankless water heaters. It consists of a submersible descaler pump, a set of 5-foot long hoses with 3/4" female hose threaded assemblies, formulated descaler solution packaged in a lidded 4 gallon chemical resistant container. The solution is also available separately. NSF registered.

| Vital-Flo kit               | 4387-01 | (NSF) |
|-----------------------------|---------|-------|
| Vital-Flo descaler solution | 4387-02 | NOL   |



#### **Season Treat**

Season Treat utilizes 6Rsp Micromet, a slowly dissolving phosphate, contained in a unique flow-through package. The package design makes it simple to treat small cooling towers and evaporative condensers. Simply unwrap the package and place it in the sump. One canister treats up to 10 tons for scale (5 tons for corrosion) for five to six months.

| 1 canister | 4364-88 |
|------------|---------|
|------------|---------|



#### Ty-lon<sup>®</sup> C70

Ty-lon C70 is an all-organic liquid scale, deposit, and corrosion inhibitor for use in open recirculating cooling water systems, evaporative condensers, and air washer systems. This treatment program is particularly effective in preventing scale deposits in systems that utilize make-up water with high scaling potentials.

| 5 gallon pail  | 7597-05 |
|----------------|---------|
| 15 gallon pail | 7597-P3 |
| 55 gallon drum | 7597-01 |



#### No. 340 Liquid Scale Inhibitor

No. 340 is an extremely concentrated scale inhibitor that is effective in hard, highly alkaline water. It is very stable and does not form any sludge. It is most effective at treatment levels between 10 and 15 parts per million. A constant, accurate feed is accomplished with a Drip Feeder or CMS Feed Pump. USDA approved.

| 1 gallon bottle     | 4340-08 |
|---------------------|---------|
| 5 gallon pail       | 4340-05 |
| 55 gallon drum      | 4340-01 |
| 1 gallon jug holder | 4606-0  |





#### No. 31-TX1 Acid Pump

Compact submersible pump designed for circulating strong acids and cleaning solutions. All parts are constructed of acid-resistant materials.

| 1 each 4603-0 |  |
|---------------|--|
|---------------|--|



#### **HK-31 Hose Kit**

An accessory item available for use with the No. 31-TX Acid Pump. Kit includes two 1/2 inch tubing adapters, two 10 foot sections of 1/2 inch clear plastic tubing and three hose clamps.

| 1 each 4604-0 | 1 each | 4604-0 |
|---------------|--------|--------|
|---------------|--------|--------|

|  | To Inhibit Scale Formation    |                                  |  |  |
|--|-------------------------------|----------------------------------|--|--|
| Tons of Refrigeration<br>or Horsepower | Containers of<br>Season Treat | Ty-lon C70<br>Required per Month | No. 340 Liquid Scale Inhibitor<br>Required per Month | Bleed-off for Most<br>Scale-forming Waters |
| 10                                     | 1                             | 1/4 gallon                       | 1/4 gallon   | 1/8 gpm                                    |
| 30                                     | 3                             | 2/3 gallon                       | 1/2 gallon   | 1/3 gpm                                    |
| 50                                     | 5                             | 1 gallon                         | 3/4 gallon   | 1/2 gpm                                    |
| 100                                    |                               | 2 gallons                        | 1 1/2 gallons  | 1 gpm                                      |
| 120                                    |                               | 2 1/2 gallons                    | 2 gallons  | 1 1/4 gpm                                  |
| 150                                    |                               | 3 gallons                        | 2 1/2 gallons  | 1 1/2 gpm                                  |

#### **Corrosion Prevention**



#### Cal-Treat® No. 233

Cal-Treat No. 233 is a liquid formulation that is used for controlling severe corrosion in evaporative condensers and cooling tower systems. It is based upon a synergistic formulation of zinc, molybdate, and organic phosphonate. Provides superior corrosion control and inhibits scale accumulation.

| gallon pail 4149-05 |
|---------------------|
|---------------------|

| To Control Corrosion  |          |    |
|---|----------|----|
| Cal-Treat No. 233 Required per Month Bleed-off for Most Corrosive Waters Capacity of System in Tons of Horsepower |          |    |
| 1/3 gallon  | 1/10 gpm | 10 |
| 1 gallon  | 1/4 gpm  | 30 |
| 2 gallons   | 3/8 gpm  | 50 |
| 3 gallons   | 1/2 gpm  | 90 |

#### **Algae Prevention**



#### No. 85 Algaecide<sup>†</sup>

No. 85 Algaecide is a polymeric, cationic biocide that has been developed for controlling biological growth in equipment. It is an EPA registered product to kill algae, bacteria, and fungi in recirculating water systems, industrial air washing systems, and closed systems.

| 1 gallon bottle     | 4108-08 |
|---------------------|---------|
| 1 gallon jug holder | 4606-0  |



#### **Bromicide Tablets<sup>†</sup>**

A chlorine-bromine donating organic compound in tablet form. It slowly releases powerful oxidizing hypohalous acids, which prevent algae and slime bacteria fouling in open recirculating cooling water systems and evaporative coolers. It also has the capability of breaking up and removing existing biological mass from system surfaces. USDA approved and EPA registered.

| 50 lb. | pail | 4109-M9 |
|--------|------|---------|
|        |      |         |

| To Kill Algae or Slime Growth  |            |   |
|--|------------|---|
| Tons of Refrigeration or Horsepower Gallons of No. 85 Algaecide per Month Number of No. 90 Bromicide Tablets for an Average System |            | Number of No. 90 Bromicide Tablets<br>for an Average System |
| 10   | 1/6 gallon | 5   |
| 30   | 1/3 gallon | 15  |
| 50   | 1/2 gallon | 25  |
| 90   | 2/3 gallon | 45  |

#### **Other Water Treatment Products**



#### **Humidi-Pro**<sup>™</sup>

Humidi-Pro is designed for humidifiers using up to 25 gallons per day and will inhibit scale for one season. Install Humidi-Pro on the water line that supplies water directly to the humidifier.

| 1 each | 4190-02 |
|--------|---------|
|--------|---------|



#### **Evap-Treat®**

Evap-Treat is used in evaporative coolers or "swamp coolers" to prevent scale and corrosion. Place it in the cooler sump and it will last all season long, thereby increasing pad life. Utilizes 6R Micromet®, a slow dissolving polyphosphate.

| 1 each (coolers up to 6,500 cfm)  | 4173-04 |
|-----------------------------------|---------|
| 1 each (coolers up to 10,000 cfm) | 4173-06 |

+ Product not registered for sale in Canada

**WATER TREATMENT** 

#### **pH-Treat<sup>™</sup> Condensate Neutralizers**



4720-06



4720-10





4720-12



4/20-14

#### pH-Treat™

pH-Treat is an in-line treatment product specifically for the treatment of the acidic nature of the condensate water produced by today's high efficiency furnaces. Includes fitting kit for easy installation.

#### **pH-Treat™ Condensate Neutralizer Kit**

- Prevents acidic condensate from corroding drain systems
- Helps maintain a neutral environment for bacteria in septic systems
- Refillable capsule design- refilling media only saves cost overtime
- Appliance Sizing: 400,000 BTU/hr or 1.6 gal/hr condensate flow rate
- Cartridge housing: 3.0" dia. X 13.75" long

#### **pH-Treat™ Condensate Neutralizer with Pump**

- Prevents acidic condensate from corroding drain systems
- Helps maintain a neutral environment for bacteria in septic systems
- Refillable tank design
- Pump removes neutralized condensate when drain is not nearby
- · Equipped with high level float switch to connect to system interlock
- Maximum pump head: 20 feet
- Appliance Sizing: 500,000 BTU/hr or 1.9 gal/hr condensate flow rate
- · Install orientation: horizontal
- Made from corrosion resistance materials

#### **pH-Treat**<sup>™</sup> Condensate Neutralizer Tank

- Appliance Sizing: 3,000,000 BTU/hr or 20 gal/hr condensate flow rate
- Constructed with durable and corrosion resistant polypropylene
- 3.5 gallon tank with baffles to channel flow for complete neutralization
- Two option piping configuration for fast and versatile installation
- Supplied with two 1" NPT x PVC unions and 1" NPT x PVC plug
- Supplied with initial charge of pH-Treat neutralizer media
- Integral bypass feature prevents condensate backflow into appliance
- Media service life is one year or when pH falls below 6

| Nu-Calgon   |                                   |   | High Efficiency Applicance Sizing |                         |
|-------------|-----------------------------------|---|-----------------------------------|-------------------------|
| Part Number | Description                       | Features  | BTU/Hr at<br>Operating Efficiency | Condensate<br>Flow Rate |
| 4720-06     | pH-Treat Neutralizer Kit          | Throwaway cartridge design, vertical installation.<br>Includes barb fittings and brackets.  | 225,000 @ 93%                     | 1.0 gal./hr             |
| 4720-10     | pH-Treat Neutralizer Kit          | Refillable low-profile design, horizontal or vertical<br>installations, refill saves cost over service life.<br>Includes media, barb fittings and brackets. | 400,000 @ 93%                     | 1.6 gal./hr             |
| 4720-12     | pH-Treat Neutralizer with<br>Pump | Refillable low-profile design, for condensate<br>neutralization and removal, high level alarm contact,<br>supplied with 20 ft. of tubing and media.         | 500,000 @ 93%                     | 4 gal./hr               |
| 4720-14     | pH-Treat Neutralizer Tank         | Refillable low-profile design for commercial installations. Supplied with fittings and media.   | 3,000,000 @ 93%                   | 20 gal./hr              |
| 4720-11     | pH-Treat Neutralization Media     | Refill media for 4720-10 pH-Treat neutralizer   |                                   |                         |
| 4720-13     | pH-Treat Neutralization Media     | Refill media for 4720-12 pH-Treat neutralizer   |                                   |                         |
| 4720-15     | pH-Treat Neutralization Media     | Refill media for 4720-14 pH-Treat neutralizer   |                                   |                         |

#### **Plumbing Products**



#### **Drain Solve**

Ideal for condensate pan drains, Drain Solve saves time and money with its ease of use. It eliminates application concerns associated with more reactive, fuming drain openers. Simply pour it down the drain and let it work without fear of noxious fumes or reactions. Does not contain sulfuric acid.

| 1 quart        | 4165-24 | NSE  |
|----------------|---------|------|
| 1 gallon       | 4165-08 | NOL. |
| 55 gallon drum | 4165-01 |      |



#### Calci-Solve

Remove scale from lines and clear clogged drains easily and effectively with Calci-Solve. The product includes a special inhibitor that coats the inside of the pipes with a protective film, allowing the acid in Calci-Solve to quickly dissolve calcium, magnesium, sodium, lime, rust, and other elements without harming pipes.

| 1 quart  | 4134-24 |
|----------|---------|
| 1 gallon | 4134-08 |



#### UrinaKleen

Keep urinals free flowing with UrinaKleen. Use it to dissolve urinary salts, mineral scale, and rust deposits which are found in urinals. It also attacks the primary source of odors.

| 1 quart  | 4590-24 |  |
|----------|---------|--|
| 1 gallon | 4590-08 |  |



#### A/C Drain Sucker®

A/C condensate drain pan overflow is caused by slime and sludge that builds up and clogs the drain line. The A/C Drain Sucker quickly removes the clog and the excess water, resolving the overflow problem. The kit includes a PurCool® Green 3 ton tablet to provide months of preventive treatment and free flowing drains, as well as all fittings and hoses for suction or pressure applications.

|      |                             | Nu-Calgon Number | ClenAir Number |
|------|-----------------------------|------------------|----------------|
|      | A/C Drain Sucker kit        | 61308            | CADS1          |
| lgon | PurCool Green 3 tons tablet | 61048            |                |



#### Vital-Flo® Tankless Water Heater Descaler Kit

The Vital-Flo Tankless Water Heater Descaler Kit is a complete service tool for descaling tankless water heaters. It consists of a submersible descaler pump, a set of 5-foot long hoses with 3/4" female hose threaded assemblies, and a formulated descaler solution packaged in a lidded four gallon chemical resistant container. The solution is also available separately. NSF registered.

| Vital-Flo kit               | 4387-01 | NCE |
|-----------------------------|---------|-----|
| Vital-Flo descaler solution | 4387-02 | NOL |

**PRODUCTS** 

PLUMBING



#### **Ice Guard Plus**

Ice Guard Plus contains advanced technology to dramatically reduce ice machine maintenance and cleaning. This technology utilizes the known properties of silver and copper, incorporated into a drop-in device, to control bacterial slime growth. The device is placed directly into the recirculating water sump, providing treatment of the machine in one easy step.

| 1 each | 4209-7 |
|--------|--------|
|        |        |



#### **Nickel-Safe Ice Machine Cleaner**

The original Nickel-Safe Ice Machine Cleaner. It is a food-grade citric-phosphoric acid product for removing scale deposits from ice machines having nickel-plated or tin-plated evaporators, and it is acceptable for use in all ice machines containing nickel. It mixes to form a green solution, which makes rinsing easier. USDA approved.

| 16 fluid ounce bottle | 4287-34 |
|-----------------------|---------|
| 1 gallon bottle       | 4287-08 |



#### **Liquid Ice Machine Cleaner**

Liquid Ice Machine Cleaner is a food-grade phosphoric acid that is fast acting, yet safe to use. It has been formulated to remove scale deposits from ice machines and coffee urns. It does not give off any harsh fumes or contain chlorine or chlorides that would attack stainless steel. USDA approved. NSF registered.

| 8 fluid ounce bottle | 4207-47 | NSE  |
|----------------------|---------|------|
| 1 gallon bottle      | 4207-08 | INOL |



#### IMS-III Sanitizing Concentrate<sup>†</sup>

IMS-III is an EPA registered sanitizing concentrate formulated to sanitize hard, non-porous surfaces and to eliminate odors and slime growths. No rinsing is required when diluted to 1.6 ounces per gallon. Formulated for general use in ice machines, ice cream dispensing equipment, and other food processing equipment.



#### **6Rsp Micromet®**

6Rsp Micromet is a slow dissolving phosphate specifically formulated for inhibiting scale in ice machines and other equipment using low volumes of water. It is used in Nu-Calgon scale controlling cartridges and requires replacement once every six months. Typical dosage is 8 ounces per 500 pounds of ice (50 gallons of water) a day.

| 50 lb. pail | 4265-50 | (NSF) |
|-------------|---------|-------|
|             |         |       |

+ Product not registered for sale in Canada.







#### Manifold/System Heads



|                   | QL3B Single | QC7I<br>Single | QC7I Twin<br>Parallel | QC7I Triple Parallel | QC7I Quad Parallel |
|-------------------|-------------|----------------|-----------------------|----------------------|--------------------|
| Connection        | 3/8" NPT    | 3/8" NPT       | 3/4" NPT              | 3/4" NPT             | 3/4" NPT           |
| Max Flow Rate     | 1.67 gpm    | 1.67 gpm       | 3.34 gpm              | 5 gpm                | 6.67 gpm           |
| Shut-off Valve    |             | •              | •                     | •                    |                    |
| Mounting Bracket  | •           | •              | •                     | •                    | •                  |
| Flushing Valve    |             | •              | •                     | •                    | •                  |
| Pressure Gauge(s) |             | •              | •                     | •                    | •                  |
| Part Number       | 9259-24     | 9272-41        | 9272-22               | 9272-23              | 9336-11            |

#### Cartridges



#### **4SI and 7SI Cartridges**

Specially designed for ice machines. This cartridge does not include carbon, which allows for compliance with ASHRAE Standard 188. The cartridge reduces sediment and particulate down to 1/2 micron and reduces cyst and Giardia. The filter allows chlorine to pass through, which helps reduce slime and bacteria growth inside the ice machine and ice bin. Helps reduce water borne bacteria that can cause Legionnaires' Disease. Ideal for food service operations where baking of bread and pastries is done on-site.

- Scale inhibition Particulate reduction
- Cyst reduction 1/2 micron rating
- NSF standards 42/53

- - (NSF) 9606-51

Capacity: 15,000 gallons • 2.0 gpm flow rate

(NSF) 9606-01

Capacity: 25,000 gallons • 3.5 gpm flow rate

**EVERPURE® WATER FILTRATION** 



#### i2000<sup>2</sup> and i4000<sup>2</sup> Cartridges

Reduces water-related ice machine problems caused by scale buildup from dirt and dissolved minerals. Provides superior taste and odor reduction of chlorine and other offensive contaminents with filtration of particles as small as 1/2 micron.

- NSF certified under NSF/ANSI standards 42 as well as 53, which reduces parasitic protozoan cysts, such as Cryptosporidium and Giardia
- Micro-Pure® II media limits the passage or growth of bacteria that may already exist in the incoming water

| i2000 <sup>2</sup>               | 9612-27  | (NSF) |
|----------------------------------|--|-------|
| Capacity: 9,000 gallons • 750 lb | s. for most cubers • 1,500 lbs. for most flakers |       |
| i4000²                           | 9612-37  | (NSF) |
|                                  |  |       |

Capacity: 12,000 gallons • 1,000 lbs. for most cubers • 2,000 lbs. for most flakers



#### MC<sup>2</sup> and XC<sup>2</sup> Cartridges

Reduces chlorine taste, odor and other offensive contaminants that can adversely affect the taste of fountain beverages. Pre-coat submicron filtration reduces particles as small as 1/2 micron, and it helps retain carbonation in drinks. NSF registered under NSF/ANSI Standards 42 and 53.

- Pre-coat filtration with Micro-Pure® II antibacterial protection
- Reduces objectionable tastes and odors
- Cyst reduction
- Sanitary quick-change cartridge replacement

| MC <sup>2</sup>         | 9612-55 | (NSF) |
|-------------------------|---------|-------|
| Capacity: 9,000 gallons |         |       |
| XC <sup>2</sup>         | 9613-97 | (NSF) |
| 6 :: 12.222 II          |         |       |

Capacity: 12,000 gallons



#### BH<sup>2</sup> and OCS<sup>2</sup> Cartridges

- Delivers premium quality water for ice and coffee applications
- Designed for applications where the i2000<sup>2</sup> is too long
- Pre-coat submicron particulate reduction
- Inhibits scale formation
- Taste and odor reduction
- NSF registered under NSF/ANSI standards 42 and 53.

| BH <sup>2</sup>   | 9612-51 | (NSF) |
|---|---------|-------|
| Capacity: 3,000 gallons or 6,000 pots of coffee • 0.5 gpm max. flow |         |       |
| OCS <sup>2</sup>  | 9618-07 | (NSF) |

Capacity: 1,500 gallons or 3,000 pots of coffee • 0.5 gpm max. flow



#### **OW200L and OW4**Plus Cartridges

- Ideal for office or residential water systems
- Unique filter blend uses activated carbon to reduce chlorine taste, odor, and other offensive contaminants
- Reduces lead to below the Federal Action Level of 10 ppb
- Pre-coat submicron technology reduces dirt and particles as small as 1/2 micron
- Inhibits scale build-up in water-using appliances
- NSF registered under NSF/ANSI standards 42 and 53

| OW200L                | 9619-06 | NSF   |
|-----------------------|---------|-------|
| Capacity: 480 gallons |         |       |
| OW4 <sup>PLUS</sup>   | 9635-06 | (NSF) |

Capacity: 2,000 gallons

\*Everpure® is a trademark of Everpure, Inc., Westmont, IL.

#### **Cartridges**



#### 4CB5, 7CB5, 4CB5-S, and nu-7CB5-S Cartridges

Carbon Block filter finely polishes water for high-quality beverages and food applications. NSF registered under NSF Standard 42.

- Problem-solving cartridge for high particulate or low flow water pressure areas
- Taste and odor, chlorine reduction
- Particulate reduction down to 5 microns
- 4CB5-S, and nu-7CB5-S cartridges control scale

| 4CB5                     | 9617-16 | (NSF) |
|--------------------------|---------|-------|
| Capacity: 6,000 gallons  |         |       |
| 7CB5                     | 9618-16 | (NSF) |
| Capacity: 10,000 gallons |         |       |
| 4CB5-S                   | 9617-26 | (NSF) |
| Capacity: 6,000 gallons  |         |       |
| 7CB5-S                   | 9618-26 | NSF   |

Capacity: 10,000 gallons



#### 4FC5, 7FC5, 4FC5-S, and 7FC5-S Cartridges

New Fiberdyne™ II media with Agion® antimicrobial protection to inhibit potential bacterial growth. Balanced cartridge for optimum performance in varying water qualities. Helps retain the drink's carbonation.

- Increased capacity 25,000 gallons
- Taste and odor reduction
- Particulate reduction
- NSE standards 42 and 53

- 2.5 gpm flow rate
- 5 micron rating
- Scale inhibition (4FC5-S and 7FC5-S)

| NSF standards 42 and 53  |         |       |
|--------------------------|---------|-------|
| 4FC5                     | 9693-21 | (NSF) |
| Capacity: 15,000 gallons |         |       |
| 7FC5                     | 9693-61 | (NSF) |
| Capacity: 25,000 gallons |         |       |
| 4FC5-S                   | 9693-31 | (NSF) |
| Capacity: 15,000 gallons |         |       |
| 7FC5-S                   | 9693-71 | (NSF) |
| Capacity: 25,000 gallons |         |       |



#### 4FC, 7FC, 4FC-S, and 7FC-S Cartridges

New Fiberdyne™ II media with Agion® antimicrobial protection to inhibit potential bacterial growth.  $Balanced\ cartridge\ for\ optimum\ performance\ in\ varying\ water\ qualities.\ Improves\ the\ taste\ of\ fountain$ drinks and helps retain the drink's carbonation.

- Taste and odor reduction
- Particulate reduction
- 2.5 gpm flow rate

- 1/2 micron rating
- NSF standards 42 and 53
- Scale inhibition (4FC-S, and 7FC-S only)

| 4FC                      | 9692-21 | (NSF) |
|--------------------------|---------|-------|
| Capacity: 15,000 gallons |         |       |
| 7FC                      | 9692-61 | (NSF) |
| Capacity: 25,000 gallons |         |       |
| 4FC-S                    | 9692-31 | (NSF) |
| Capacity: 15,000 gallons |         |       |
| 7FC-S                    | 9692-71 | (NSF) |
|                          |         |       |

Capacity: 25,000 gallons

**EVERPURE® WATER FILTRATION** 

#### **Kleenware HTS-11 Scale Control System**



Scale control for hot temperature applications such as warewashing and booster heaters. Inhibits limescale buildup and reduces corrosion. Features metering flow through head, high temperature housing and transparent HT-10 cartridge. Maximum feeder inlet temperature: 170.0°F/76.7°C

| Kleenware HTS-11            | 9799-11 |
|-----------------------------|---------|
| HT-10 Replacement cartridge | 9799-22 |

#### Replacement Cartridges for CUNO®



The EFS cartridges are replacements that are compatible with the CUNO Series CFS 8000 filter cartridges. Both incorporate a carbon block filter that reduces objectionable tastes and odors, as well as chlorine and other contaminates, providing high-quality beverages and ice. They also reduce extra fine dirt as small as 5 microns. Additionally, the EFS 8002-S provides for the reduction of scale formation.

| EFS 8002 | 9781-10 |
|----------|---------|
|----------|---------|

Capacity: 10,000 gallons (37,850 liters) • 1.5 gpm flow Replaces CFS-8112, CFS-8720 & CFS-8812

| EFS 8002-S | 9781-12 |
|------------|---------|
|------------|---------|

Capacity: 10,000 gallons (37,850 liters) • 1.5 gpm flow Replaces CFS-8112S,CFS-8720S & CFS-8812S

\*Everpure® is a trademark of Everpure, Inc., Westmont, IL. \*CUNO® is a trademark of 3M. This product is not manufactured, sponsored, or affiliated with 3M.

#### **Other Filtration Products**



#### 10" and 20" Coarse Prefilters

A 10" and 20" black housing, each including a 10" and 20" replaceable prefilter cartridge. Filters out larger dirt and rust particles, thereby extending the life of submicron and carbon block filters.

| E-10 | 9795-80 |
|------|---------|
| E-20 | 9795-90 |

Optional: Prefilter bracket kit for all multiple filter head systems manufactured after 2003: 3114-34 (4621-45)



#### **EC110 and EC210**

IMF-7 and IMF-10

of water.

IMF-7

IMF-10

A 10" and 20" 10-micron nominal filtration cartridge for filtering out larger dirt and rust particles, extending the life of primary filters. For use in the E-10 and E-20 housings as well as other 10" and 20" housings.

| EC110 (10") | 9534-40 |
|-------------|---------|
| EC210 (20") | 9534-20 |

Ice Machine Feeder scale inhibition cartridge.

The translucent cartridge allows for easy visual

monitoring of the product's usage. The larger

IMF-10 will last longer or treat higher volumes

Replacement for

AR-X 7" Housing

Replacement for

SS-10 Scale Sticks

9799-32

9799-02

#### **SRX Scale Inhibitor Feeder**

A complete system for the control of scale in ice, coffee, steam, and combination applications. It dispenses a controlled amount of HydroBlend™ compound, which provides for a more consistent feed and longer life. The system includes a black housing and one cartridge

| 1 each 979 | 8-45 |
|------------|------|
|------------|------|

Optional: Post-filter bracket kit for all multiple filter head systems manufactured after 2003: 3114-35

**4JT Flushing/Sanitizing Cartridge** 



The preferred way to introduce ScaleKleen Scale Remover or other sanitizing agents, such as bleach, into all water-using equipment and vending machines. Fits into existing Everpure heads. Eliminates the need for difficult component disassembly. Easy and convenient to help you clean and maintain equipment.

| 1 each | 9608-00 |
|--------|---------|
|--------|---------|

ScaleKleen™ Scale Remover

Restores equipment to peak operating efficiency by removing scale build-up. Quickly removes limescale from coffee brewers. Ideal for deliming steam and ware washing equipment. Great for office coffee system (OCS) applications. Non-toxic, safe to skin, and won't burn clothing. Sewer system disposable; can be poured down the drain. Use with 4JT Flushing/ Sanitizing Cartridge.

| 7 oz. packets (24 per case)   | 9798-33 |
|-------------------------------|---------|
| 2.2 lb. canister (4 per case) | 9798-35 |

#### Water Filtration - OEM Replacements



#### **CFS Filtration System**

#### A family of replacement cartridges and manifolds designed to service existing CUNO® CFS installations.

A cost-effective water filtration system for food service applications: ice machines, fountain beverages, steam ovens, and drinking water. These systems offer manifold and sanitary quick-change cartridges to fit the existing CUNO CFS brand installations and can also support new filtration installations. CFS is the reliable choice for water filtration to prevent unwanted troubles caused by sediment, scale, or taste and odor existing in CUNO installations.

| Sediment – 5 micron              | 4623-10 |
|----------------------------------|---------|
| Sediment – 5 micron / phosphate  | 4623-11 |
| Carbon Block5 micron             | 4623-12 |
| Carbon Block5 micron / phosphate | 4623-13 |

| Single Head | 4623-01 |
|-------------|---------|
| Twin Head   | 4623-02 |
| Triple Head | 4623-03 |
| Twin Series | 4623-06 |

#### The CGSYS-22C5S

A matching product for the Tri-Liminator Filtration System, with application and specifications that are nearly identical. For example, the primary cartridge (CG5-20S) will replace both the K00070 and K00174 cartridges, and it has more scale control ability than either of the Tri-Liminator cartridges.

| CGSYS-22C5S                 | 9101-24 |
|-----------------------------|---------|
| Prefilter - EC210           | 9534-20 |
| Primary cartridge - CG5-20S | 9108-27 |

#### **Water Filtration**



#### Micro-Plus® & Micro-Carbon 4

The complete all-in-one treatment for ice machines, coffee urns and brewers, humidifiers, steamers, etc. The Micro-Plus "in-line" filters contain 6R Micromet® to control scale, high-grade activated carbon for eliminating objectionable tastes and odors, and filter discs to remove silt and sediment down to 20 microns. Available in four sizes with 1/4" FPT connections. When properly sized, each filter will last up to six months. The Micro-Carbon 4 is available for removing objectionable tastes and odors.

| Micro-Plus 2   | 4615-W3 |
|----------------|---------|
| Micro-Plus 4   | 4612-W3 |
| Micro-Plus 8   | 4613-Y8 |
| Micro-Plus 16  | 4614-Y8 |
| Micro-Carbon 4 | 4617-24 |

| Application       | Micro-Plus 2        | Micro-Plus 4         | Micro-Plus 8          | Micro-Plus 16          | Micro-Carbon 4 |
|-------------------|---------------------|----------------------|-----------------------|------------------------|----------------|
| Water (per day)   | 12.5 gallons        | 25 gallons           | 50 gallons            | 100 gallons            | 50 gallons     |
| Ice (per day)     | Up to 125 lbs.      | Up to 250 lbs.       | Up to 500 lbs.        | Up to 1000 lbs.        |                |
| Coffee (per week) | 25 lbs.(1,250 cups) | 50 lbs. (2,500 cups) | 100 lbs. (5,000 cups) | 200 lbs. (10,000 cups) |                |

**WATER FILTRATION** 

# SERIES

#### **NP Series Housings**

These housings are designed to hold one of the NP Cartridges used to filter water for ice machines, coffee urns, and other beverage equipment. The NP24DD and NP48DD housings fit specific NP24 or NP48 cartridges for controlling scale, sediment, or objectionable tastes and odors. The NP24DD is equipped with 3/8" FPT connections and handles up to 4.0 gpm. The NP48DD is equipped with 1/2" FPT connections and can handle flow rates up to 5.0 gpm.

| NP24DD | 4704-24 |
|--------|---------|
| NP48DD | 4714-24 |



#### **6R Micromet®/Carbon Cartridge**

A custom cartridge, combining 6R Micromet for scale-control and a carbon block for sediment (10 microns), taste and odor control.

| NP24PC | 4706-87 |
|--------|---------|
| NP48PC | 4716-87 |



#### **Carbon Block Cartridge**

The NP24C Cartridge fits the NP24DD Housing while the NP48C fits the NP48DD. These carbon blocks will remove most objectionable tastes and odors and are rated to remove particulate down to 10 microns.

| NP24C | 4701-87 |
|-------|---------|
| NP48C | 4711-87 |



#### **Sediment Cartridge**

The NP24S (5") and the NP48S (10") are made from FDA-approved polypropylene construction and filter down to 5 microns. In addition, the 10" and 20" versions are available in bulk packaging.

| NP24S                   | 4702-87 |
|-------------------------|---------|
| NP48S                   | 4712-87 |
| EC210, 20" (10 microns) | 9534-20 |



#### **6R Micromet® Cartridge**

The NP246R Micromet Cartridge contains 1 pound of 6R Micromet, and it fits the NP24DD Housing. The NP486R Cartridge contains 2 pounds of 6R and fits the NP48DD Housing, with 10 micron filtration.

| NP246R | 4705-87 |
|--------|---------|
| NP486R | 4715-87 |



#### **6R Micromet®/Sediment Cartridge**

Another custom cartridge within the NP Series, consisting of polypropylene for filtration (5 microns) and phosphate for scale-control.

| NP48PS       | 4717-87 |
|--------------|---------|
| CG5-205, 20" | 9108-27 |



#### **NP Series Brackets**

Some installations may require two or three NP Series housings to meet more than one specific waterrelated condition. This custom installation can be accomplished through the use of one of the NP Series multi-housing brackets.

| Two housing brackets   | NP2BR |
|------------------------|-------|
| Three housing brackets | NP3BR |

| Problem to Solve |          |              |       | Daily Capacities     |                      |
|------------------|----------|--------------|-------|----------------------|----------------------|
| Cartridge Type   | Sediment | Taste & Odor | Scale | "24's"               | "48's"               |
| "S" Cartridges   | х        |              |       | 1800 lbs. (200 gal.) | 3600 lbs. (400 gal.) |
| "C" Cartridges   | х        | x            |       | 1800 lbs. (200 gal.) | 3600 lbs. (400 gal.) |
| "6R" Cartridges  | х        |              | х     | 900 lbs. (100 gal.)  | 1800 lbs. (200 gal.) |
| "PC" Cartridges  | х        | x            | x     | 600 lbs. (65 gal.)   | 1200 lbs. (135 gal.) |
| "PS" Cartridges  | х        |              | х     | N/A                  | 550 lbs. (60 gal.)   |

#### Serving the United States & Canada with the Finest Direct Factory Sales Force in the HVACR Industry



Free Seminars and Training Classes

- 1. Portland, OR
- 2. Sacramento, CA
- Los Angeles/Central, CA
- 4. Corona, CA
- San Diego, CA
- Phoenix, AZ
- 7. Denver, CO
- 8. San Antonio, TX
- 9. Dallas Fort Worth
- 10. Houston, TX
- 11. St. Paul Minneapolis
- 12. Kansas Citv. MO
- 13. Baton Rouge, LA 14. St. Louis, MO
- 15. Madison, WI
- 16. Chicago, IL
- 17. Indianapolis, IN
- 18. Detroit. MI
- 19. Nashville, TN
- 20. Birmingham, AL
- 21. Columbus, OH
- 22. Atlanta, GA
- 23. Ocala, FL
- 24. Sarasota, FL 25. Delray Beach, FL
- 26. Raleigh, NC
- 27. Richmond, VA
- 28. Philadelphia, PA
- 29. Syracuse, NY
- 30. Baltimore, MD
- 31. NYC/New Jersey, MA
- 32. Boston, MA
- ★ St. Louis, MO (Hdq)

#### NATE training available. Contact your Nu-Calgon Account Manager.

Coil Cleaning: The Clean Coil Program is a comprehensive seminar dedicated to the safe and proper procedures to clean evaporator and condenser coils. The program will help determine which cleaning method should be utilized for a particular job based on the type and condition of the unit. NATE Recognition Classes: 1 hour Continuing Education Accreditation



Indoor Air Quality Management: The seminar covers the past, present and future of indoor air quality (IAQ). Topics covered in the session: how poor IAQ impacts a business, common causes of poor IAQ, and how to prevent poor IAQ from occurring. NATE Recognition Classes: 1 hour Continuing **Education Accreditation** 



Refrigeration Oils: An in-depth look at industry refrigeration oils (Mineral, Alkylbenzene, nd POE) and when and where to use them. NATE Recognition Classes: 1.5 hours Continuing **Education Accreditation** 



Total System Protection: A thorough look at why burnouts occur, how to prevent them and the proper way to flush a system once a burnout occurs. The training will include acid testing and acid neutralization. NATE Recognition Classes: 1 hour Continuing Education Accreditation



Water Treatment: This seminar will cover the fundamentals of water treatment for cooling towers, evaporative condensers, boilers, and chillers. NATE Recognition Classes: 1.5 hours Continuing **Education Accreditation** 



& TRAINING CLASSES

SEMINARS

**NU-CALGON** 









## **Nu-Calgon**

2611 Schuetz Rd., St. Louis, MO 63043 Phone: 800-554-5499

WWW.NUCALGON.COM

VOL. 20, NO. 1













