

4303-07
(43031)



C-3s

MINERAL REFRIGERATION OIL

**VISCOSITY
150 SUS**

(ISO 32)

Replaces 3GS



OEM Approved

Copeland

Carlye

**and Other
Compressor
and Equipment
Manufacturers**

**Superior Miscibility,
Lubrication, and Stability**

R015 Refrigeration Oil

FOR PROFESSIONAL USE ONLY

1 U.S. Gallon (3.785 Liters)



CAUTION: Keep container tightly closed. Moisture in air will contaminate oil.

Contains: Naphthalene (CAS #91-20-3)

KEEP OUT OF REACH OF CHILDREN.

WARNING: This product can expose you to chemicals including Naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65warnings.ca.gov.

1 22NV46



APPLICATION:

Nu-Calgon Refrigeration Oils are recommended for use with all CFC and HCFC refrigerants. FOLLOW THE EQUIPMENT MANUFACTURER'S RECOMMENDATIONS. If none are available, use the following as a guide:

DIRECTIONS FOR USE:

- For Refrigerants 11, 12, 113 with evaporator temperatures above -20°F, use Nu-Calgon's C-3s or C-4s Refrigeration Oils. Below -20°F, use only C-3s Refrigeration Oil.
- For Refrigerants 13, 22, 114, 502, ethane, propane, and isobutane, use Nu-Calgon's C-3s Refrigeration Oil.
- For ammonia with evaporator temperatures above -20°F use Nu-Calgon's C-4s or C-5s Refrigeration Oil. Below -20°F, use C-3s Refrigeration Oil.
- When using "drop-in" refrigerants that call for a mineral oil, select one of the Nu-Calgon Refrigeration Oils in accordance with the appropriate viscosity required and evaporator temperatures.

Mineral Oil	Viscosity at 100°F
C-3s (Calumet R015)	150 SUS (ISO 32)
C-4s (Calumet R030)	300 SUS (ISO 68)
C-5s (Calumet R050)	500 SUS (ISO 100)

Manufactured by: CALUMET LUBRICATIONS COMPANY



Nu-Calgon
2611 Schuetz Rd.
St. Louis, MO 63043
Customer Service: 800-554-5499
Chemical Emergency: 800-424-9300
www.nucalgon.com
(619) Calgon is a licensed trade name.

