

REFRIGERATION OIL  
RECOMMENDATION CHART

OEM	Refrigerant	Zerol Product*
Bitzer	R-22 & Blends*	Zerol 150, 300
Bristol	R-22 & Blends	Zerol 150
Bock	R-22 & Blends	Zerol 150, 500
Carrier	R-22 & Blends	Zerol 300, 400CA
Carlyle	R-22 & Blends	Zerol 150
Danfoss	R-22 & Blends	Zerol 150
Dorin	R-22 & Blends	Zerol 150, 200TD
Emerson (Copeland)	R-22 & Blends	Zerol 200TD, 300
Johnson Controls	R-22 & Blends	Zerol 300
Sabroe	R-22 & Blends	Zerol 150, 300
Tecumseh	R-22 & Blends	Zerol 150, 300
Thermoking	R-22 & Blends	Zerol 150
Bock	Ammonia	Zerol 150, 500
Mycom (Mayekawa)	Ammonia	Zerol 300

\* Blends include: R-401A & B, R-402A & B, R-403B, R-408A, R-409A, R-414B, R-500, R-502. Zerol products are also suitable for R123 and R-124.

\* For other Zerol product options not listed, contact Nu-Calgon.

4308-07



Shrieve

**ZEROL**<sup>®</sup>  
**200TD**

Alkylbenzene Refrigeration Oil  
Viscosity 200 SUS at 100° F (ISO 46)

**Copeland Approved**

High Solubility, Dependable Lubrication  
Excellent Thermal Stability and Compatibility  
Controlled Foaming

Nu-Calgon



**OEM Approved**

Copeland<sup>®</sup> and Other Compressor  
and Equipment Manufacturers

ZEROL<sup>®</sup> 200TD is highly recommended for use with R-22 as well as with HCFC service blends and other HCFC and CFC refrigerants in refrigeration and air conditioning applications.

Keep container tightly closed to maintain dryness of contents. Refrigeration oils can absorb moisture from the air.

**APPLICATION:**

ZEROL<sup>®</sup> 200TD is recommended for use with refrigerants R-401a/R-401b (MP39/MP66) and R-402a/R-402b (HP80/HP81) as well as other HCFC and CFC refrigerants in field service and retrofit applications. Follow the compressor manufacturer's and OEM equipment manufacturer's recommendations.

CAUTION: KEEP OUT OF REACH OF CHILDREN.

DO NOT weld, heat or drill container. Residue may ignite with explosive violence if heated sufficiently.

Manufactured by Shrieve Chemical Products, Inc. The Woodlands, TX.

ZEROL<sup>®</sup> is a trade mark owned and used by The Shrieve Group of Companies.

Copeland is a registered trademark of Emerson Climate Technologies.



Nu-Calgon  
2611 Schuetz Rd.  
St. Louis, MO 63043  
Customer Service: 800-554-5499  
Chemical Emergency: 800-424-9300  
www.nucalgon.com  
(718) Calgon is a licensed trade name.

1 U.S. Gallon (3.8 Liters)