



Calci-Solve

- Removes clogs from pipes and drains
- Gets rid of offensive odors in drains
- Economical and easy to use
- Will not harm lines or drain pipes
- Can be used on hot water heaters, boilers, steam equipment and more

Description

Remove scale from lines and clear clogged drains easily and effectively with Calci-Solve. The product includes a special inhibitor that coats the inside of the pipes with a protective film, allowing the acid in Calci-Solve to quickly dissolve calcium, magnesium, sodium, lime, rust and other such elements without harming pipes.

Application

Use Calci-Solve to remove scale and rust from the following:

Air Conditioning Equipment	Boilers
Pasteurizers and Tanks	Air Filters
Dish Washing Machines	Condensers
Water Sealed Blowers	Water Piping
Refrigerator Drains	Water Pumps

Directions for Use

HOT WATER HEATERS: GAS TYPE. Break at unions leading in and out of heater. Drain water. Use solution of 2 to 5 parts water and pour in enough solution to cover bottom of heater to a depth of one foot. Flush thoroughly before returning to use.

Calci-Solve



HOT WATER COILS: Attach a stand pipe and pour a solution of 2 parts water and 1 part Calci-Solve. If coil is completely stopped use Calci-Solve full strength.

BOILERS: 10 to 15 parts water and 1 part Calci-Solve. Allow to work for at least 12 hours. Extra flushing may be required to remove loose sediment left on bottom.

WATER METERS, VALVES AND STEAM EQUIPMENT: Submerge parts to be cleaned in solution of 2 to 5 parts water, 1 part of Calci-Solve.

Packaging

1 quart	4134-24
1 gallon	4134-08

Drain Solve

- Perfect for clogged A/C condensate lines as well as kitchen, bathtub, & lavatory drains
- Non-fuming (no rotten egg odor).
- No violent eruptions.
- Pours through standing water.
- Does not attack porcelain tubs, sinks, etc.
- Generates heat when added to water to help loosen clogged drains.
- Cuts through grease and organic matter.

Description

Drain Solve is an alkaline-based drain opener which removes grease, hair, vegetable and other organic matter. It is non-fuming and it will clean and clear drains quickly. Simply pour it down the drain and let it work without fear of noxious fumes or reactions that may squirt corrosive chemicals into face and eyes.

Application

Drain Solve does not contain sulfuric acid. Use in the following sites:

Health Clubs/Swimming Pools

Hospitals/Nursing Homes

Beauty/Barber Shops

Restaurants/Bars

Fast Food Chains

Motels/Hotels

Factories

Kennels

Urina-Kleen

- Attacks primary source of odors
- Dissolves urinary salts, mineral scale and rust deposits
- Keeps urinals free flowing

Description

Urinakleen is an acid-based bowl cleaner that removes scale deposits and odors. It is also ideal for dissolving rust, urinary salts and mineral scale from flush tanks, urinal drains and bowls. Monthly application of Urinakleen will effectively keep urinals free flowing and reduce the need for excessive odor control products.

Application

Remove waste debris, urinal screens and urinal blocks. Shut off automatic flush and remove as much standing water as possible. Pour 16 oz. into urinal and allow it to work for 10-15 minutes while acid action takes place. Clean bowl with bowl swab wet with Urinakleen. Flush urinal several times and repeat process if urinal is completely clogged or very slow to drain.

Read and understand the product's label and Safety Data Sheet ("SDS") for precautionary and first aid information.

The SDS is available on the Nu-Calgon website at www.nucalgon.com.



2611 Schuetz Rd. • St. Louis, MO 63043 • 800-554-5499 • www.nucalgon.com
Calgon is a licensed trade name • (517) 3-108

Drain Solve



Directions for Use

For general drains, pour 16 ounces into the drain, allow to work 15-20 minutes, flush with warm water and repeat if necessary. For larger drains, use entire contents and allow to work 30 minutes; flush with warm water. To maintain drains, use 8 ounces for small and 16 ounces for large drains weekly.

Packaging

1 gallon **4165-08**

1 quart **4165-24**

Urina-Kleen



Packaging

1 gallon **4590-08**

1 quart **4590-24**

