Cal-Blue<sup>®</sup> Plus is the complete gas leak detector for today's service technician. The product, formulated to maintain **long lasting bubbles**, finds the smallest leaks in the system since it clings to surfaces for superior contact time. It is ideal for use in and around **food processing areas**; remove or cover all food products during use. Use freely on systems with fluorescent dyes as Cal-Blue Plus will not interfere with the use of ultraviolet or blacklight detection. Suitable for use on any pressurized refrigerant system, natural gas or oxygen line. Cal-Blue Plus is oxygen set. **Freeze protected down to 5°F (and will handle up to 225°F).** 

#### DIRECTIONS FOR USE:

# This product must be used in accordance to the following directions by HVACR professionals only.

Spray a uniform coating liberally on the surfaces wherever leaks are suspected. Visually examine surfaces for signs of white foam or small bubble formation. Be patient - wait a minimum of 5 minutes. Check bottom of all fittings for increased bubbles/foam. If a leak is found, consider Nu-Calgon's EasySeal if the situation is appropriate.

#### WARNING:

Contains gas under pressure; may explode if heated. Keep away from heat. Do not puncture or incinerate container.



PREVENTION: Avoid contact with eyes and skin. Wash hands after handling. RESPONSE: IF IN EYES: Flush with cool water. Remove contact lenses, if applicable, and continue flushing. Obtain medical attention if irritation persists. IF ON SKIN: Flush with cool water. Wash with soap and water. Obtain medical attention if irritation persists. IF INHALED: If symptoms develop, move victim to fresh air. Get medical attention if symptoms persist. IF SWALLOWED: Do not induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Never give anything by mouth if victim is unconscious, or is convulsing. Obtain medical attention. KEEP OUT OF REACH OF CHILDREN.

**STORAGE:** Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 120°F/49°C. **DISPOSAL:** Dispose of contents/container to an approved waste disposal plant. Contains: Propylene Glycol (CAS# 57-55-6).

WARNING: This product can expose you to chemicals including formaldehyde, which is known to the State of California to cause cancer. For more information go to www.P6SWarnings.ca.gov.



Nu-Calgon 2611 Schuetz Rd. St. Louis, MO 63043 Customer Service: 800-554-5499 Iemical Emergency: 800-424-9300 www.nucalgon.com 9) Calgon is a licensed trade name.

**NSF** 

Nonfood Compounds

P1 Registration #150679



Cal-Blue<sup>Phus</sup>

## **MICRO GAS LEAK DETECTOR**

PRESSURIZED SPRAY FOR ANY REFRIGERANT SYSTEM

### **Maximum Bubble Life**

Freeze Protected to 5°F

NSF Registered for Use in Food Processing Areas

Non-Corrosive

FOR PROFESSIONAL USE ONLY CAUTION: CONTENTS UNDER PRESSURE. Read carefully other cautions on back panel.

Net Wt. 7 oz. (198 grams)