

4189-07



Freez-Therm[®]

INHIBITED ETHYLENE GLYCOL

*Heat Transfer Fluid & Freeze-Point
Suppressant for the HVACR Industry*

FOR PROFESSIONAL USE ONLY

1 Gallon (3.8 L)

DIRECTIONS FOR USE:

This product must be used in accordance to the following directions by HVACR professionals only.

1. Wear protective clothing when handling this product. Do not store in open or unlabeled containers.
2. Clean new or lightly corrode existing system with Nu-Calgon System Cleaner (4370-08) prior to installation of Freeze-Therm. Do not use Freeze-Therm with galvanized steel; avoid contact with oxidizing materials.
3. Extensively corroded systems should be cleaned using inhibited acid such as Season Start Scale Remover, Eco-Lyme, or Liquid Scale Dissolver. Job should be handled by an experienced serviceman. All necessary replacements and repairs should be made.
4. Consult applicable Freeze-Therm freeze protection chart and select the lowest expected ambient temperature, then go to a temperature 5°F colder to assure protection.
5. Determine system volume in gallons and multiply this volume by the desired percentage interpreted from the chart below. This will tell you the number of gallons of Freeze-Therm required.
6. For optimum corrosion protection, a minimum concentration of 33% is recommended.
7. Since the empty container can be hazardous, the empty container must be completely drained, rinsed thoroughly with water and recapped with its original enclosure in place. Disposed of properly. All labeled hazard precautions must be observed. Cutting, drilling, grinding or welding on containers might cause fire, explosion or release harmful fumes. Do not use container to store other products.
8. Observe local waste laws and regulations with the disposal of Freeze-Therm.



WARNING

Harmful if swallowed. May cause damage to organs through prolonged or repeated exposure.

PREVENTION: Wash face, hands, and any exposed skin thoroughly after handling. Do not eat, drink, or smoke when using this product. Do not breathe dust/fume/gas/mist/vapors/spray.

RESPONSE: IF SWALLOWED: Call POISON CENTER or doctor/physician if you feel unwell. Rinse mouth.

FIRST AID - EYES: Rinse with large amounts of water, also under eyelids, for at least 15 minutes. Seek immediate medical attention/advice. **SKIN:** In case of contact, immediately wash skin with soap and water for at least 15 minutes. Take of contaminated clothing. If skin irritation persists, call a physician. **INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call physician.

KEEP OUT OF REACH OF CHILDREN.

STORAGE: Store locked up. Do not store in open or unlabeled containers.

DISPOSAL: Dispose of contents/container to an approved waste disposal plant.

TYPICAL FREEZE POINTS VERSUS PRODUCT CONCENTRATION

FREEZE-THERM CONCENTRATION (% BY VOLUME)	25	33 1/3	40	50	60
FREEZE PROTECTION MIN. TEMP. (°F)	19	0	-12	-34	-62

Always use a Nu-Calgon Refractometer (61301) to check ethylene glycol solution freeze protection before leaving job site.



WARNING: This product can expose you to chemicals including ethylene glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov



MADE IN THE
USA



Nu-Calgon
2611 Schuetz Rd.
St. Louis, MO 63043
Customer Service: 800-554-5499
Chemical Emergency: 800-424-9300
www.nucalgon.com
(219) Calgon is a licensed trade name.