

4178-05



Foam-Brite®

CONDENSER COIL CLEANER

*Maximum Foaming Coil Cleaner
and Brightener*



**Removes the
Toughest Deposits
Excellent Degreasing
Capability**



Nonfood Compounds
Program Listed P1
Registration #146046

FOR PROFESSIONAL USE ONLY

2.5 U.S. Gallons (9.46 Liters)

APPLICATION:

Outdoor air conditioning coils of aluminum or copper fin construction. For painted fin or microchannel coils, consider Tri-Pow'r® HD, Cal-Green™, CalClean®, or TriClean 2x™.

DOES NOT CONTAIN ACID. DO NOT USE ON INDOOR COILS. NOT FOR INDOOR USE.

DIRECTIONS FOR USE:

This product must be used in accordance to the following directions by HVACR professionals only.

1. Goggles, gloves and other protective garments should be worn when using this product. System should be shut off.
2. Apply using any of the Nu-Calgon sprayers, or other durable, low pressure, plastic sprayer.
3. Prepare Foam-Brite solution by mixing one part Foam-Brite with four parts of water. Add the water to the sprayer first, then add the Foam-Brite.
4. Spray Foam-Brite onto dirty condenser coils and allow it to remain in contact with the dirty surfaces for 5-10 minutes.

AFFECT ON ROOFING MATERIAL: depending on its composition and condition, the color and finish of roofing material can be affected by coil cleaners (e.g. discoloration or tarnishing). It is recommended that the coil cleaner be tested on a small area of the roof prior to cleaning, particularly galvanizing or standing seam metal roofs. Do not use on aluminum or aluminum-coated surfaces.

RUBBER ROOFS: In general, the product is safe on rubber except where the rubber roof is impregnated with aluminum chips (i.e. modified bitumen roof); do not use on rubber roofs that contain aluminum. In these circumstances, use CalClean, Cal-Green, Nu-Clean or Tri-Pow'r HD - first evaluate in a small test area.

5. Rinse thoroughly with water, ensure cleaning solution is removed from the coil.
6. Apply Cal-Shield® as a coil protectant and return system to service.
7. Rinse out sprayer, spraying wand and nozzle.
8. When the Foam-Brite container is empty, rinse, replace cap and dispose of properly.

NOTE: For maximum results, do not use Foam-Brite undiluted or any stronger than one part cleaner to three parts water.



DANGER

Causes severe skin burns and eye damage.
May be corrosive to metals.

PREVENTION: Keep only in original container. Do not breathe mist or vapor. Wash face, hands and any exposed skin thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

RESPONSE: Absorb spillage to prevent material damage. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician. **IF ON SKIN (or hair):** Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. **IF INHALED:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician. **IF SWALLOWED:** Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician. For additional information, consult Safety Data Sheet (SDS). **KEEP OUT OF REACH OF CHILDREN.**

STORAGE: Store in corrosive resistant container with a resistant inner liner. Store locked up.

DISPOSAL: Dispose of contents/container in accordance with local/regional/national/international regulations.

Contains Sodium Hydroxide (CAS # 1310-73-2).



00681001417853

Qty 1

B82-244

4178-05 Foam-Brite 2.5 gal

CHM00356

4178-05 Foam-Brite 2.5 gal



2.5 GAL CS



Nu-Calgon
2611 Schuetz Rd.
St. Louis, MO 63043
Customer Service: 800-554-5499
Chemical Emergency: 800-424-9300
www.nucalgon.com | (319) Calgon is a licensed trade name.