

4289-05

 Nu-Calgon

**NuLock™**

**Refrigerant  
Thread Sealant**

**Locks and seals threaded  
refrigerant fittings**

**Net .34 fl. oz. (10mL)**

**DIRECTIONS:** For professional use only, use PPE. Surfaces should be dry, clean, and free of any contamination. Apply NuLock to male threads. NuLock performs the best in thin bond gaps. Assemble the threaded fittings normally and allow NuLock to cure.

**WARNING:** Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.



Nu-Calgon  
2611 Schuetz Rd.  
St. Louis, MO 63043

Customer Service: 800-554-5499  
Chemical Emergency: 800-424-9300  
[www.nucalgon.com](http://www.nucalgon.com)

(0620) Calgon is a licensed trade name.

NuLock (P/N: 4289-05) is a high performance anaerobic thread sealant designed for the locking and sealing of metal threaded pipes and fittings on refrigerant systems. Use for threaded fasteners up to 2 inches in diameter. NuLock has excellent chemical resistance to seal against gases and excellent thixotropic property prevents migration of the sealant before or during cure. Handling cure time of 10-30 minutes, functionally cures in 2-4 hours, fully cures in 24 hours. Temperature range between -65°F to 300°F. Meets US Military specifications.

**PREVENTION:** If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash hands thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Dispose of contents/container to local/regional/national/international regulations.