

Pressurized Can for Running Systems



DANGER

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Harmful if swallowed. Causes skin irritation. Causes eye irritation. May cause an allergic skin reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause damage to organs through prolonged or repeated exposure.

Prevention: Pressurised container: Do not pierce or burn, even after use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Contaminated work clothing should not be allowed out of the workplace. In case of inadequate ventilation wear respiratory protection. Do not breathe dust/fume/gas/mist/vapours/spray.

Response: IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see information on this label). Take off contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.



4301-05

Nu-Calgon

R_X-acid scavenger®

Acid Neutralizer for A/C and Refrigeration Systems

- Removes existing acid and prevents future acid
- For moderate acid conditions
1 can treats systems containing
1/8 to 1 gallon of oil
- Quickly injects into running system
in less than 2 minutes
- Works with mineral, alkylbenzene,
POE and PVE oils

DIRECTIONS

If system's low side pressure is **BELOW 65 psi** while running:

1. Shake can well. Make sure system is running and low side is below 65 psi.
2. Be sure Injection Valve handle (4300-89) is turned fully counter clockwise and attach valve to can.
3. Attach short charging hose to Injection Valve and other end to low side service port. Loosen hose slightly from valve to purge air from hose and then re-tighten quickly.
4. With can upright, open valve by turning handle clockwise and hold above low side service port to dispense.
5. Allow approximately 1 minute for R_X-Acid Scavenger to completely enter the system.
6. Once product is dispensed, remove hose from system. Retain hose and valve for future installations and dispose of can properly.

If system's low side pressure is **ABOVE 65 psi** while running:

First pump the system down to achieve a low side pressure between 40 and 50 psi. Then, inject into the low side starting with step 2 above.

REUSABLE INJECTION VALVE, DO NOT DISCARD.

Made in the USA

2008 Altom Ct.

St. Louis, MO 63146

800-554-5499

Emergency: 1-800-424-9300 (CHEMTREC)

www.nucalgon.com

NET WT. 3.8 oz. (109 grams)

(1016) Calgon is a licensed trade name.