APPLICATION:

This Tri-Pow'r® HD 4X container provides equal performance to one gallon of Tri-Pow'r® HD (at 4:1 dilution) when a smaller size is desired. For outdoor air cooled coils of aluminum fin/copper tube construction. Suitable for use with painted fin or microchannel coils. Use with the Clean Connect Sprayer (4773-0).

FOR OUTDOOR USE ONLY.

DIRECTIONS FOR USE:


This product must be used in accordance to the following directions by HVACR professionals only.

- Goggles, gloves and other protective garments must be worn when using this product. System must be shut off.
- Connect hose assembly to Clean Connect Sprayer. If Probe connector is used, adequately tighten with wrenches to Nu-Calgon Probe (4774-1) for the first time, then attach to sprayer.
- Connect Clean Connect Sprayer to bottle, keep bottle cap.
 Toggle to clean mode on sprayer and depress handle to sprayer.
- diluted solution onto dirty condenser coil. Allow it to remain in contact on the dirty surface for 5-10 minutes.
- 5. Toggle to rinse on sprayer and rinse coil thoroughly with water.
- 6. Apply Cal-Shield® as a coil protectant and return system to service.
- When the Tri-Pow'r[®] HD 4X container is empty, replace cap and dispose of properly or if contents remain recap bottle for another job.

6 81001 43719 6

Nu-Calgon 2611 Schuetz Road St. Louis, M0 63043 Customer Service: 800-554-5499 Chemical Emergency: 800-424-9300

220) Calgon is a licensed trade name.





Clean Connect Sprayer P/N: 4773-0

Adapts to Nu-Calgon Probe P/N: 4774-1

Features:

- ✓ Concentrate quart = gallon traditional Tri-Pow'r® HD (4:1 ratio)
- ✓ Takes less space on truck
- ✓ Easier to carry on roof
- ✓ Cleaner connecting no more pouring or spilling
- ✓ Use what is needed simply cap bottle for next job
- ✓ Dilution orifice in bottle less likely for sprayer to clog
- ✓ Easier to ship to job sites

AFFECT ON ROOFING MATERIAL: Depending on its composition and condition, the color and finish of roofing material can be affected by coil cleaners (e.g. discoloration or tarnishing). It is recommended that the coil cleaner be tested on a small area of the roof prior to cleaning, particularly glavanizing or standing seam metal roofs. Do not use on aluminum or aluminum-coated surfaces.

RUBBER ROOFS: In general, the product is safe on rubber except where the rubber roof is impregnated with aluminum chips (i.e. modified bitumen roof); do not use on rubber roofs that contain aluminum. In these circumstances, use CalClean®, Cal-Green™, Green Clean or Tri-Powlr® HD - Fist evaluate in a small test area.

DANGER

May be corrosive to metals. Causes severe skin burns and eye damage.



PREVENTION: Keep only in original packaging. Do not breathe mist or vapor. Wash thoroughly after handling. Wear protective gloves, protective clothing, eye protection and face protection. RESPONSE: Absorb spillage to prevent material-damage. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (OR HAIR): Take off immediately all contaminated clothing. Rinse skin with water. Wash contaminated clothing before reuse. IF INHALED: remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing, STORAGE: Store locked up. Store in a corrosion resistant container with a resistant inner liner. DISPOSAL: Dispose of container in accordance with local, regional, national and international regulations. KEEP OUT OF REACH OF CHILDREN

International regulations. REP **D01 OF READ OF CHILDNEN CONTAINS** (**CAS#**): Water (7732-18-5), Sodium Orthosilicate
(1344-09-8), Potassium Hydroxide (1310-58-3), Sodium Gluconate
(527-07-1), Potassium Carbonate (584-08-7), Lauramine Oxide
(1643-20-5), Capryly/Capryl Glucoside (68515-73-1), Lauryl
Glucoside (110615-47-9), Colorants, Fragrances. Contains fragrance
allergens. For more ingredient information, visit www.nucalgon.com.
800-554-5499