#### Part No. 61107

# Penetrate HD®

**Super Penetrating Oil** 

Penetrate HD is specially formulated with new low surface tension technology to penetrate into the smallest cracks, crevices, seams, or threads of rusted, seized, and corroded parts to quickly dissolve the bonds of rust, corrosion, carbon deposits, gums, varnishes, and grease to free the metal parts. PenetrateHD displaces water and leaves a lubricating film to protect metal parts and prevent rust and corrosion.

## Super Formula Penetrates into the Smallest Spaces. Results Are Amazing!

**APPLICATION:** For use on HVACR blower & motor shafts, fan blades, pulleys & other parts, plant machinery, processing equipment, tools, rusted nuts, bolts, screws, fasteners, hinges, locks, pins, sliders, auto, truck, marine equipment, and for cleaning rifle barrels and guns.

**DIRECTIONS:** Spray **PenetrateHD** on the frozen part. Allow it to work into the affected area. Lightly tap the part to improve penetration. Loosen and remove the part. Repeat if necessary.

#### Penetrate HD

**DANGER:** Flammable aerosol. Contains gas under pressure; may explode if heated. Harmful if inhaled. Causes skin irritation.





Causes serious eye irritation. May cause an allergic skin reaction. May cause cancer. May cause genetic defects. May cause damage to organs through prolonged or repeated exposure. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Wash hands thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves / protective clothing / eye protection / face protection. Do not breathe gas/mist/ vapors/spray. FIRST AID: If exposed or concerned: Get medical advice/attention. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Protect from sunlight. Do not expose to temperatures exceeding 50° C/122° F. Store in a well-ventilated place. Store locked up. Dispose of contents and container in accordance with all well-enthated pieces softentixed up bispose or to otherits and contained in accordance with a local, regional, national and international regulations. **CONTAINS (CAS No):** Distillates, petroleum, hydrotreated heavy naphthenic (64742-52-5), Solvent naphtha, petroleum, light aromatic (64742-95-6), Pine, extract (94266-48-5), Distillates, petroleum, hydrotreated middle (64742-95-6), Pine, extract (94266-48-5), Distillates, petroleum, hydrotreated middle (64742-95-6), Pine, extract (94266-48-5), Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7), Lubricating oils, petroleum, C15-30, hydrotreated neutral oil-based, containing solvent deasphalted residual oil (72623-88-8), Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based, high brook high viricestity, (732-28-80), Lubricating oils, petroleum, C35-20, hydrotreated neutral oil-based, high viricestity, (732-28-80), Lubricating oils, petroleum, C35-20, hydrotreated neutral oil-based, high viricestity, (732-28-80), Lubricating oils, petroleum, C35-20, hydrotreated neutral oil-based, high viricestity, (732-28-80), Lubricating oils, petroleum, C35-20, hydrotreated neutral oil-based, containing solvent deasphalted residual oil (72623-88-81), Lubricating oils, petroleum, C35-20, hydrotreated neutral oil-based, containing solvent deasphalted residual oil (72623-88-81), Lubricating oils, petroleum, C35-20, hydrotreated neutral oil-based, containing solvent deasphalted residual oil (72623-88-81), Lubricating oils, petroleum, C35-20, hydrotreated neutral oil-based, high virial oil-based, high vi neutral oil-based, high-viscosity (72623-85-9), Lubricating oils, petroleum, C15-30, hydrotreated neutral oil-based (72623-86-0), Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based (72623-87-1), 2-Butoxyethanol (111-76-2), 2-Butanol (78-92-2) and Carbon dioxide (124-38-9), 20 % of the mixture consists of inc ©2014 ClenAir by Nu-Calgon, 2008 Altom Ct., St. Louis, MO

CAUTION: Intentional misuse by concentrating and inhaling the product can be harmful or fatal. KEEP OUT OF REACH OF CHILDREN. See Safety Data Sheet for Complete Safety Information. Made in Canada. EMERGENCY PHONE, 24 HOURS: Chemtrec 800-424-9300

63146 USA • 800-554-5499 • www.nucalgon.com • www.ClenAir.com

# Penetrate HD®



**Scan to View Video** 

netrate HD will quickly loosen ee frozen and rusted metal par or your money back.






### **Super Penetrating Oil**

Penetrate<sup>HD</sup> frees stuck fan blades, blower shafts, pulleys, rusted nuts and bolts – any frozen, rusted, or seized metal part. *Results are Amazing!* 

Heavy duty formula penetrates into the smallest spaces and breaks & dissolves the bonds of rust and corrosion. Lubricates & Protects.

Dielectric strength to 31,000 volts.



### For Industrial and Professional Use Only

DANGER: CONTENTS UNDER PRESSURE. VAPOR HARMFUL. HARMFUL OR FATAL IF SWALLOWED. MAY CAUSE EYE & SKIN IRRITATION.

Read additional warnings on back label.



Net Wt. 12 oz. / 340g Part No. 61107