Part No. 61105

Super Penetrating Oil

PenetrateHD is specially formulated with new low surface tension technology to penetrate into metal parts. **PenetrateHD** displaces water and leaves a lubricating film to protect metal parts

Super Formula Penetrates into the Smallest Spaces. **Results Are Amazing!**

APPLICATION: For use on HVACR blower & motor shafts, fan blades, pullevs & other parts, plant

DIRECTIONS: Spray PenetrateHD on the frozen part. Allow it to work into the affected area.

PenetrateHD DANGER: Flammable aerosol.



Scan to View Video

Clen/lii

may explode if heated. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. May cause cancer. May cause genetic defects. May be fatal if swallowed and enters airways. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash hands thoroughly after handling. Avoid breathing gas/mist/vapors/spray. Contaminated work clothing must not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves / protective dothing / eye protection / face protection. FIRST AID: If exposed or concerned: Get medical advice/attention. If on skin: Wash with plenty of water. Take off contaminated dothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Protect from sunlight. Do not expose to temperatures exceeding 50° C/122° F. Store in a well-ventilated place. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations. CONTAINS (CAS No): Distillates, petroleum, hydrotreated heavy naphthenic (64742-52-5), Solvent naphtha, petroleum, light aromatic (64742-95-6), Petroleum distillates, hydrotreated light (64742-47-8), Pine, extract (94266-48-5), 2-Butoxyethanol (111-76-2), 2-Butanol (78-92-2) and Carbon dioxide (124-38-9). 13 % of the mixture consists of ingredient(s) of unknown acute toxicity.

© 2018 ClenAir by Nu-Calgon, 2611 Schuetz Road, St. Louis, MO 63043 USA 800-554-5499 • www.nucalgon.com • www.ClenAir.com

CAUTION: Intentional misuse by concentrating and inhaling the product can be harmful or fatal. KEEP OUT OF REACH OF CHILDREN. See Safety Data Sheet for Complete Safety Information, Made in Canada, EMERGENCY PHONE, 24 HOURS: Chemtrec 800-424-9300

Penetrate^{HD®}

Super Penetrating Oil

Penetrate^{HD} frees stuck fan blades, blower shafts, pulleys, rusted nuts and bolts – any frozen, rusted, or seized metal part. Results are Amazina!

Heavy duty formula penetrates into the smallest spaces and breaks & dissolves the bonds of rust and corrosion. Lubricates & Protects.

Dielectric strength to 40,000 volts.



For Industrial and Professional Use Only

DANGER: CONTENTS UNDER PRESSURE, VAPOR HARMFUL, HARMFUL **OR FATAL IF SWALLOWED. MAY CAUSE EYE & SKIN IRRITATION.** Read additional warnings on back label.

ClepAir Nu-Calgon 2611 Schuetz Road, St. Louis, MO 63043 USA

Net Wt. 12 oz. / 340g Part No. 61105